



UT3414

Power MOSFET

N-CHANNEL ENHANCEMENT MODE



DESCRIPTION

The **UT3414** uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 1.8V. This device is suitable for use as a load switch or in PWM applications.

FEATURES

- * $R_{DS(ON)} < 50m\Omega$ @ $V_{GS} = 4.5V$
- * $R_{DS(ON)} < 63m\Omega$ @ $V_{GS} = 2.5V$
- * $R_{DS(ON)} < 87m\Omega$ @ $V_{GS} = 1.8V$
- * Low capacitance
- * Low gate charge
- * Fast switching capability
- * Avalanche energy specified

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UT3414L-AE3-R	UT3414G-AE3-R	SOT-23	S	G	D	Tape Reel

		(1) Packing Type	(1) R: Tape Reel
		(2) Package Type	(2) AE3: SOT-23
		(3) Lead Plating	(3) G: Halogen Free, L: Lead Free

MARKING



■ ABSOLUTE MAXIMUM RATINGS (T_a = 25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V _{DSS}	20	V
Gate-Source Voltage	V _{GSS}	±8	V
Continuous Drain Current	I _D	4.2	A
Pulsed Drain Current	I _{DM}	15	A
Power Dissipation	P _D	1.4	W
Junction Temperature	T _J	+150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse width limited by T_{J(MAX)}






■ THERMAL DATA

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction to Ambient	θ _{JA}		100	125	°C/W

■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	20			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =16V, V _{GS} =0V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±8V			100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	0.4	0.6	1	V
On State Drain Current	I _{D(ON)}	V _{DS} =5V, V _{GS} =4.5V	15			A
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =4.5V, I _D =4.2A		41	50	mΩ
		V _{GS} =2.5V, I _D =3.7A		52	63	
		V _{GS} =1.8V, I _D =3.2A		67	87	
DYNAMIC PARAMETERS						
Input Capacitance	C _{ISS}	V _{DS} =10V, V _{GS} =0V, f=1.0MHz		436		pF
Output Capacitance	C _{OSS}			66		pF
Reverse Transfer Capacitance	C _{RSS}			44		pF
SWITCHING PARAMETERS						
Turn ON Delay Time	t _{D(ON)}	V _{DS} =10V, V _{GS} =5V, R _L =2.7Ω R _G =6Ω		5.5		ns
Turn ON Rise Time	t _R			6.3		ns
Turn OFF Delay Time	t _{D(OFF)}			40		ns
Turn OFF Fall-Time	t _F			12.7		ns
Total Gate Charge	Q _G	V _{DS} =10V, I _D =4.2A, V _{GS} =4.5V		6.2		nC
Gate Source Charge	Q _{GS}			1.6		nC
Gate Drain Charge	Q _{GD}			0.5		nC
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =1A		0.76	1	V
Maximum Body-Diode Continuous Current	I _S				2	A
Body Diode Reverse Recovery Time	t _{RR}	I _F =4A, dI/dt=100A/μs		12.3		ns
Body Diode Reverse Recovery Charge	Q _{RR}	I _F =4A, dI/dt=100A/μs		3.5		nC

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.