



**BTA12**

Preliminary

TRIAC**12A TRIACS****■ DESCRIPTION**

The UTC **BTA12** is a 12A triacs, it uses UTC's advanced technology to provide customers with high commutation performances and voltage insulated tab, etc.

The UTC **BTA12** is suitable for inductive loads, general purpose AC switching and an ON/OFF function in applications such as motor speed controllers, induction motor starting circuits and static relays, etc.

■ SYMBOL**■ ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
BTA12L-x-xx-TF3-T	BTA12G-x-xx-TF3-T	TO-220F	MT1	MT2	G	Tube

BTA12L-x-xx-TF3-T	
(1)Packing Type	(1) T: Tube
(2)Package Type	(2) TF3: TO-220F
(3)Sensitivity and type	(3) refer to SENSITIVITY AND TYPE
(4)Voltage	(4) 6: 600V, 8: 800V
(5)Lead Free	(5) L: Lead Free, G: Halogen Free

■ SENSITIVITY AND TYPE

PART NUMBER	VOLTAGE		SENSITIVITY	TYPE
	600V	800V		
B	⊙	⊙	50mA	STANDARD
BW	⊙	⊙	50mA	SNUBBERLESS
C	⊙	⊙	25mA	STANDARD
CW	⊙	⊙	35mA	SNUBBERLESS
SW	⊙	⊙	10mA	LOGIC LEVEL
TW	⊙	⊙	5mA	LOGIC LEVEL

⊙: Available

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER			SYMBOL	RATINGS	UNIT
RMS On-State Current (Full Sine Wave)		$T_C=90^{\circ}\text{C}$	$I_{T(RMS)}$	12	A
Non Repetitive Surge Peak On-State Current (Full Cycle, T_J initial= 25°C)	F=50 Hz	t=20ms	I_{TSM}	120	A
	F=60 Hz	t=16.7ms		126	A
I^2t Value for Fusing		$t_P=10\text{ms}$	I^2t	78	A^2s
Critical Rate of Rise of On-State Current $I_G=2I_{GT}$, $t_{rs}\leq 100\text{ns}$		F=120 Hz $T_J=125^{\circ}\text{C}$	di/dt	50	$\text{A}/\mu\text{s}$
Non Repetitive Surge Peak Off-State Voltage		$t_P=10\text{ms}$ $T_J=25^{\circ}\text{C}$	V_{DSM}/V_{RSM}	$V_{DRM}/V_{RRM}+100$	V
Peak Gate Current		$t_P=20\mu\text{s}$ $T_J=125^{\circ}\text{C}$	I_{GM}	4	A
Average Gate Power Dissipation		$T_J=125^{\circ}\text{C}$	$P_{G(AV)}$	1	W
Operating Junction Temperature			T_J	$-40\sim+125$	$^{\circ}\text{C}$
Storage Junction Temperature			T_{STG}	$-40\sim+150$	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL RESISTANCES

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient		θ_{JA}	60	$^{\circ}\text{C}/\text{W}$
Junction to Case (AC)		θ_{JC}	2.3	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$ unless otherwise specified)

FOR SNUBBERLESS TYPE and LOGIC LEVEL TYPE (3 QUADRANTS)

PARAMETER	SYMBOL	TEST CONDITIONS		TW			SW			CW			BW			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
SNUBBERLESS TYPE and LOGIC LEVEL TYPE (3 QUADRANTS)																
Gate Trigger Current (Note 1)	I _{GT}	V _D =12V, R _L =30Ω	I-II-III			5			10			35			50	mA
Gate Trigger Voltage	V _{GT}		I-II-III			1.3			1.3			1.3			1.3	V
Gate Non-Trigger Voltage	V _{GD}	V _D =V _{DRM} , R _L =3.3kΩ, T _J =125°C	I-II-III			0.2	0.2			0.2			0.2			V
Holding Current (Note 2)	I _H	I _T =100mA					10			15			35			50
Latching Current	I _L	I _G =1.2I _{GT}	I-III			10			25			50			70	mA
			II			15			30			60			80	mA
Critical Rate of Rise of Off-State Voltage (Note 2)	dV/dt	V _D =67%V _{DRM} , Gate Open, T _J =125°C			20			40			500			1000		
Critical Rate of Rise of Off-State Voltage at Commutation (Note 2)	(di/dt) _c	(dV/dt) _c =0.1V/μs, T _J =125°C			3.5			6.5								
		(dV/dt) _c =10V/μs, T _J =125°C			1			2.9								
		Without Snubber T _J =125°C								6.5			12			

Notes: 1. Minimum I_{GT} is guaranteed at 5% of I_{GT} max.
2. For both polarities of MT2 referenced to MT1.

ELECTRICAL CHARACTERISTICS(Cont.)

FOR STANDARD TYPE (4 QUADRANTS)

PARAMETER	SYMBOL	TEST CONDITIONS	C			B			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Gate Trigger Current (Note 1)	I_{GT}	$V_D=12V$, $R_L=33\Omega$			25			50	mA
Gate Trigger Voltage	V_{GT}				50			100	mA
Gate Non-Trigger Voltage	V_{GD}	$V_D=V_{DRM}$, $R_L=3.3k\Omega$, $T_J=125^\circ C$			1.3			1.3	V
Holding Current (Note 2)	I_H	$I_T=500mA$			25			50	mA
Latching Current	I_L	$I_G=1.2 I_{GT}$			40			50	mA
Critical Rate of Rise of Off-State Voltage (Note 2)	dV/dt	$V_D=67\%V_{DRM}$, Gate Open, $T_J=125^\circ C$	200			400			V/ μs
Critical Rate of Rise of Off-State Voltage at Commutation(Note 2)	$(dV/dt)_c$	$(dI/dt)_c=5.3A/ms$, $T_J=125^\circ C$	5			10			V/ μs

STATIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Peak On-State Voltage(Note)	V_T	$I_{TM}=17A$, $t_p=380\mu s$			1.55	V
Threshold Voltage(Note)	V_{TO}				0.85	V
Dynamic Resistance(Note)	R_D				35	m Ω
Repetitive Peak Off-State Current	I_{DRM}	$V_{DRM}=V_{RRM}$			5	μA
	I_{RRM}				1	mA

Note: 1. Minimum I_{GT} is guaranteed at 5% of I_{GT} max.

2. For both polarities of MT2 referenced to MT1.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.