



DZ23CXX

Preliminary

ZENER DIODE

300mW DUAL SURFACE MOUNT ZENER DIODE

DESCRIPTION



The UTC **DZ23CXX** is a 300mW dual surface mount zener diode, it uses UTC's advanced technology to provide customers with low reverse leakage current.

The UTC **DZ23CXX** is suitable for automatic insertion, etc.

FEATURES

* Low reverse leakage current

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
DZ23CXXL-AE3-R	DZ23CXXG-AE3-R	SOT-23	A	A	K	Tape Reel

Note: Pin Assignment: A: Anode, K: Cathode

DZ23CXXL-AE3-R	(1)Packing Type	(1) R: Tape Reel
	(2)Package Type	(2) AE3: SOT-23
	(3)Lead Plating	(3) L: Lead Free, G: Halogen Free
	(4)Output Voltage Code	(4) xx: refer to Marking Information

■ **MARKING INFORMATION**

PACKAGE	VOLTAGE CODE	MARKING
SOT-23	22: 2.2V 24: 2.4V	<p data-bbox="762 427 938 465">Voltage Code ←</p>  <p data-bbox="1114 427 1297 488">→ L: Lead Free G: Halogen Free</p> <p>The diagram shows a square SOT-23 package with four leads. The top lead is labeled 'CXX' with a small square above it. The bottom lead is labeled 'G' with a small square below it. The left and right leads are labeled 'L' with small squares above and below them respectively. A double-headed arrow points from the text 'Voltage Code' to the 'CXX' marking, and another double-headed arrow points from the text 'L: Lead Free' and 'G: Halogen Free' to the 'L' and 'G' markings.</p>

■ **ABSOLUTE MAXIMUM RATINGS** ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	RATINGS	UNIT
Power Dissipation	P_D	300	mW
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-65~+150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **THERMAL DATA**

CHARACTERISTIC	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	417	$^{\circ}\text{C}/\text{W}$

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

For DZ23C22

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Zener Voltage Range (Note)	V_Z	$I_{ZT}=5.0\text{mA}$	20.8		23.3	V
Minimum Reverse Voltage (Note)	V_R	$I_R=0.1\mu\text{A}$	17			V
Temperature Coefficient	T_C			+0.09		$\%/^{\circ}\text{C}$
Zener Impedance	Z_{ZT}	$f=1\text{KHz}, I_{ZT}=5.0\text{mA}$			55	Ω
	Z_{ZK}	$f=1\text{KHz}, I_{ZK}=1.0\text{mA}$			220	Ω

For DZ23C24

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Zener Voltage Range (Note)	V_Z	$I_{ZT}=5.0\text{mA}$	22.8		25.6	V
Minimum Reverse Voltage (Note)	V_R	$I_R=0.1\mu\text{A}$	18			V
Temperature Coefficient	T_C			+0.09		$\%/^{\circ}\text{C}$
Zener Impedance	Z_{ZT}	$f=1\text{KHz}, I_{ZT}=5.0\text{mA}$			80	Ω
	Z_{ZK}	$f=1\text{KHz}, I_{ZK}=1.0\text{mA}$			220	Ω

Notes: Short duration test pulse used to minimize self-heating effect.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.