




OneConnect® OCe11102-N

High-performance 10Gb Ethernet Network Adapter

Simplified Networking, Maximum Performance and Increased Business Agility



Optimized Network Connectivity

The OCe11102-N is a high-performance, dual-port network adapter for 10Gb Ethernet (10GbE) networks. Protocol offload for stateless TCP/IP provides maximum bandwidth with minimum use of CPU resources.

Emulex OneConnect Universal CNA platform

The OCe11102-N is a member of the Emulex OneConnect Universal Converged Network Adapter (UCNA) platform that also includes support for Fibre Channel over Ethernet (FCoE) and iSCSI protocol offloads. By using a common infrastructure for Ethernet and storage networks, data centers can reduce capital expenditure (CAPEX) for adapters, switches and cables, and operational expenditure (OPEX) for power, cooling and IT administration.

Greener data centers

The Emulex OneConnect UCNA platform delivers industry-leading performance and scalability per watt, reducing requirements for power and cooling. Protocol offload enables efficient use of computing resources, supports more virtual machine (VMs) per CPU, and reduces the number of servers required to support data center demands.

Advanced error checking

End-to-end data protection with hardware parity, CRC, ECC and other advanced error checking and correcting ensure that data is safe from corruption.

Virtualized I/O

New multi-core servers are enabling much higher virtualization ratios. OneConnect adapters support NetQueue for VMware and Virtual Machine Queue (VMQ) for Microsoft Windows Server 2008 Hyper-V to optimize performance and provide full 10Gbps bandwidth per port.

Universal Multi-Channel

OneConnect Universal Multi-Channel (UMC) allows multiple PCI functions to be created on each adapter port. Each NIC function is presented to the operating system or hypervisor as a physical port with a separate MAC address and user-assigned bandwidth. This enables a single adapter port to provide specialized NIC functions for different uses, such as payload traffic, guest migration and console management for virtualized servers.

Key Features

Superior performance

- TCP/IP stateless offloads

Energy-efficient design

- Industry-leading performance per watt
- Complements data center “green” initiatives

One platform for network and storage connection

- Part of OneConnect family that includes FCoE and iSCSI support

Easy to deploy and manage with OneCommand® Manager application

- One management console for network and storage
- Integrated management of Emulex UCNAs and Host Bus Adapters (HBAs)
- More than 12 million ports administered with Emulex management software

Key Benefits

Optimized for network consolidation

- Maximizes I/O bandwidth with high-performance 10GbE ports
- Multiple PCI NIC functions for each physical port
- Same firmware, drivers and management as OneConnect 10GbE blade and LAN on Motherboard (LOM) solutions

Optimized for server virtualization with vEngine™ technology

- SR-IOV support improves I/O performance with virtual server deployments
- Support for NetQueue for VMware and VMQ for Hyper-V optimize performance for virtualized servers
- More VMs per server with full TCP offloads

Secure management

- Role-based administration integrated with Light Directory Access Protocol (LDAP) and Active Directory (AD) services

Enterprise-ready

- Hardware parity, CRC, ECC and other advanced error checking
- Backed by field-proven Emulex reliability and support



OneConnect®



OneCommand®

OneConnect® OCe11102-N

High-performance 10GbE Network Adapter

Single Root I/O Virtualization (SR-IOV)

With OneConnect support for SR-IOV, VMs can share adapter ports to optimize performance with up to 32 virtual functions per port. VM to VM communication is enabled with a Layer 2 switch that is embedded in the OneConnect adapter. OneConnect adapters are PCI-SIG compliant and will support SR-IOV as available with hypervisors.

Powerful Management Software for Maximum Data Center Efficiency

The Emulex OneCommand® Manager enterprise class management application features a multiprotocol, cross-platform architecture that provides centralized management of all adapters provided by Emulex. This enables IT administrators to manage network connectivity with one tool for maximum efficiency. OneCommand Manager also features:

- **OneCommand® Manager plug-in for VMware vCenter Server**—enables comprehensive control of Fibre Channel HBAs and network (FCoE, iSCSI and TCP/IP NIC) connectivity solutions provided by Emulex from VMware's vCenter Server management console. Emulex OneCommand Manager plug-in for VMware vCenter Server supports both the new VMware vSphere 5.1 Web Client and the VMware vCenter Server desktop client with an identical feature set regardless of the client.

Network boot

Support for Preboot eXecution Environment (PXE) makes the OCe11102-N an ideal solution for blade servers and other diskless deployments.

Note: Some of these products may not be available in the U.S. Please contact your supplier for more information.

Standards

- PCI Express base spec 2.0, PCI Bus Power Management Interface, rev. 1.2, Advanced Error Reporting (AER)
- IEEE 802.3ae (10Gb/s Ethernet)
- IEEE 802.1q (VLAN)
- IEEE 802.1p (QoS/CoS)
- IEEE 802.3ad (Link Aggregation)
- IEEE 802.3x (Flow Control)
- PHP hot plug-hot swap
- Enhanced Error Handling (EEH)

Architecture

- Dual-channel, 10GbE Link speed
- PCIe Express 2.0 (x8, 5GT/s), MSI-X support
- Integrated data buffer and code space memory

Ethernet Features

- IPv4/IPv6 TCP, UDP checksum offload; Large Send Offload (LSO); Large Receive Offload; Receive Side Scaling (RSS); TCP Segmentation Offload (TSO)
- VLAN insertion and extraction
- Jumbo frames up to 9000 Bytes
- Priority Flow Control for Ethernet traffic
- Preboot eXecution Environment (PXE) 2.0 network boot support
- Interrupt coalescing
- Load balancing and failover support including adapter fault tolerance (AFT), switch fault tolerance (SFT), adaptive load balancing (ALB), teaming support, VMW NetQueue v2 and IEEE 802.3ad, VT-d / IOMMU support

I/O Virtualization

- PCI-SIG SR-IOV compliant
- On-chip VM to VM switching
- Quality of Service (QoS) across each Virtual and Physical Function

Comprehensive OS Support

- Windows Server
- VMware ESX
- Red Hat Enterprise Linux Server
- Novell SUSE® Linux Enterprise Server
- CentOS
- Ubuntu
- Oracle Solaris
- FreeBSD

Hardware Environments

- x86, x64 and PPC processor families

Interconnect

- Optical
 - Optics: 10GBASE-SR short wave lasers with LC type connector
- Copper Direct Attach
 - SFP+ Direct Attached Twin-Ax Copper interface
 - Standards compliant passive copper cables up to 5m and active copper cables up to 10m
- Copper Twisted Pair
 - Connectors: IEC 60603-7 8 Position 8 Contact (8P8C), commonly known as RJ45
 - Cables: Cat 6 up to 55m, Cat 6a up to 100m

Physical Dimensions

- Short, low-profile form factor card
- 167.64mm x 68.91mm (6.60" x 2.71")
- Standard bracket (low profile available)

Environmental Requirements

- Operating temperature: 0° to 55° C (32° to 131° F)
- Storage temperature: -40° to 70° C (-40° to 158° F)
- Relative humidity: 5% to 95% non-condensing

Agency Approvals

North America:

- FCC Class A
- UL/CSA Recognized

Europe:

- CE Mark
- EU RoHS compliant
- TUV Bauart Certified

Japan:

- VCCI Class A

Taiwan:

- BSMI Class A

Korea:

- MSIP (formally KCC/MIC) Class A

China:

- China RoHS Compliant

(Please refer to the product page on www.emulex.com for further details)

Ordering Information

- OCe11102-NM
 - Dual-channel, 10GBASE-SR (short reach optical)
- OCe11102-NX
 - Dual-channel, 10GBASE-CR (direct attach copper)
- OCe11102-NT
 - Dual-channel, 10GBASE-T (twisted pair copper)
- OCe10100-OPT
 - Dual-channel transceiver kit
- OC-Storage-01A
 - FCoE/iSCSI enablement



World Headquarters 3333 Susan Street, Costa Mesa, CA 92626 +1 714 662 5600
 Bangalore, India +91 80 40156789 | Beijing, China +86 10 84400221
 Dublin, Ireland +35 3 (0) 1 652 1700 | Munich, Germany +49 (0) 89 97007 177
 Paris, France +33 (0) 158 580 022 | Tokyo, Japan +81 3 5325 3261
 Wokingham, United Kingdom +44 (0) 118 977 2929

www.emulex.com