

Normally – OFF Silicon Carbide Junction Transistor


V_{DS}	=	1700 V
$V_{DS(ON)}$	=	2.0 V
I_D	=	16 A
$R_{DS(ON)}$	=	110 mΩ

Features


- 175 °C maximum operating temperature
- Temperature independent switching performance
- Gate oxide free SiC switch
- Suitable for connecting an anti-parallel diode
- Positive temperature coefficient for easy paralleling
- Low gate charge
- Low intrinsic capacitance

Package

- RoHS Compliant



TO-247AB



Advantages

- Low switching losses
- Higher efficiency
- High temperature operation
- High short circuit withstand capability

Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- Hybrid Electric Vehicles (HEV)
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Induction Heating
- Uninterruptible Power Supply (UPS)
- Motor Drives

Maximum Ratings unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Drain – Source Voltage	V_{DS}	$V_{GS} = 0$ V	1700	V
Continuous Drain Current	I_D	$T_{C,MAX} = 90$ °C	16	A
Gate Peak Current	I_{GM}		5	A
Turn-Off Safe Operating Area	RBSOA	$T_{VJ} = 175$ °C, $I_G = 1$ A, Clamped Inductive Load	$I_{D,max} = 16$ @ $V_{DS} \leq V_{DSmax}$	A
Short Circuit Safe Operating Area	SCSOA	$T_{VJ} = 175$ °C, $I_G = 1$ A, $V_{DS} = 1200$ V, Non Repetitive	20	μs
Reverse Gate – Source Voltage	V_{SG}		30	V
Reverse Drain – Source Voltage	V_{SD}		40	V
Power Dissipation	P_{tot}	$T_C = 25$ °C	234	W
Storage Temperature	T_{stg}		-55 to 175	°C

Electrical Characteristics at $T_j = 175$ °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

On Characteristics

Drain – Source On Voltage	$V_{DS(ON)}$	$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 25\text{ }^{\circ}\text{C}$	2.0	V
		$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 125\text{ }^{\circ}\text{C}$	3.3	
		$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 175\text{ }^{\circ}\text{C}$	4.5	
Drain – Source On Resistance	$R_{DS(ON)}$	$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 25\text{ }^{\circ}\text{C}$	110	mΩ
		$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 125\text{ }^{\circ}\text{C}$	210	
		$I_D = 16\text{ A}, I_G = 1000\text{ mA}, T_J = 175\text{ }^{\circ}\text{C}$	280	
Gate Forward Voltage	$V_{GS(FWD)}$	$I_G = 500\text{ mA}, T_J = 25\text{ }^{\circ}\text{C}$	3.0	V
		$I_G = 500\text{ mA}, T_J = 175\text{ }^{\circ}\text{C}$	2.7	
DC Current Gain	β	$V_{DS} = 5\text{ V}, I_D = 16\text{ A}, T_J = 25\text{ }^{\circ}\text{C}$	69	
		$V_{DS} = 5\text{ V}, I_D = 16\text{ A}, T_J = 175\text{ }^{\circ}\text{C}$	47	

Off Characteristics



Drain Leakage Current	I_{DSS}	$V_R = 1700\text{ V}, V_{GS} = 0\text{ V}, T_j = 25\text{ }^{\circ}\text{C}$	0.1	μA
		$V_R = 1700\text{ V}, V_{GS} = 0\text{ V}, T_j = 125\text{ }^{\circ}\text{C}$	0.5	
		$V_R = 1700\text{ V}, V_{GS} = 0\text{ V}, T_j = 175\text{ }^{\circ}\text{C}$	1.0	
Gate Leakage Current	I_{SG}	$V_{SG} = 20\text{ V}, T_j = 25\text{ }^{\circ}\text{C}$	20	nA

Electrical Characteristics at $T_j = 175^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Capacitance Characteristics						
Gate-Source Capacitance	C_{GS}	$V_{GS} = 0\text{ V}, f = 1\text{ MHz}$		1730		pF
Input Capacitance	C_{ISS}	$V_{GS} = 0\text{ V}, V_D = 1\text{ V}, f = 1\text{ MHz}$		2225		pF
Reverse Transfer/Output Capacitance	C_{RSS}/C_{OSS}	$V_D = 1\text{ V}, f = 1\text{ MHz}$		495		pF
Switching Characteristics						
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 1100\text{ V}, I_D = 16\text{ A},$ $R_{G(on)} = R_{G(off)} = 22\ \Omega,$ $V_{GS} = -8/15\text{ V}, L = 1.1\text{ mH},$ FWD = GB20SLT12, $T_j = 25\text{ }^{\circ}\text{C}$ Refer to Figure 11 for gate current waveform		17		ns
Rise Time	t_r			14		ns
Turn Off Delay Time	$t_{d(off)}$			48		ns
Fall Time	t_f			46		ns
Turn-On Energy Per Pulse	E_{on}			781		μJ
Turn-Off Energy Per Pulse	E_{off}	$V_{DD} = 1100\text{ V}, I_D = 16\text{ A},$ $R_{G(on)} = R_{G(off)} = 22\ \Omega,$ $V_{GS} = -8/15\text{ V}, L = 1.1\text{ mH},$ FWD = GB20SLT12, $T_j = 175\text{ }^{\circ}\text{C}$ Refer to Figure 11 for gate current waveform		188		μJ
Total Switching Energy	E_{ts}			969		μJ
Turn On Delay Time	$t_{d(on)}$			9		
Rise Time	t_r			22		ns
Turn Off Delay Time	$t_{d(off)}$			55		ns
Fall Time	t_f			41		ns
Turn-On Energy Per Pulse	E_{on}			794		μJ
Turn-Off Energy Per Pulse	E_{off}			118		μJ
Total Switching Energy	E_{ts}			912		μJ

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	0.64	$^\circ\text{C/W}$
-------------------------------------	------------	------	--------------------

Figures

Figure 1: Typical Output Characteristics at 25°C

Figure 2: Typical Output Characteristics at 125°C




Figure 3: Typical Output Characteristics at 175 °C




Figure 4: Typical Gate Source I-V Characteristics vs. Temperature




Figure 5: Normalized On-Resistance and Current Gain vs. Temperature




Figure 6: Typical Blocking Characteristics




Figure 7: Capacitance Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Typical Hard-switched Turn On Waveforms




Figure 10: Typical Hard-switched Turn Off Waveforms




Figure 11: Typical Turn On Energy Losses and Switching Times vs. Temperature




Figure 12: Typical Turn Off Energy Losses and Switching Times vs. Temperature




Figure 13: Typical Turn On Energy Losses vs. Drain Current




Figure 14: Typical Turn Off Energy Losses vs. Drain Current




Figure 15: Typical Gate Current Waveform




Figure 16: Typical Hard Switched Device Power Loss vs. Switching Frequency¹




Figure 17: Power Derating Curve




Figure 18: Forward Bias Safe Operating Area




Figure 19: Turn-Off Safe Operating Area




Figure 20: Transient Thermal Impedance

¹ – Representative values based on device switching energy loss. Actual losses will depend on gate drive conditions, device load, and circuit topology.

Gate Drive Technique (Option #1)

To drive the GA16JT17-247 with the lowest gate drive losses, please refer to the dual voltage source gate drive configuration described in Application Note AN-10B (<http://www.genesicsemi.com/index.php/references/notes>).

Gate Drive Technique (Option #2)

The GA16JT17-247 can be effectively driven using the IXYS IXDN614 / IXDD614 non-inverting gate driver IC or a comparable product. A typical gate driver configuration along with component values using this driver is offered below. Additional information is available in GeneSiC Application Note AN-10A and from the manufacturer at www.ixys.com.





Figure 21: Recommended Gate Diver Configuration (Option #2)

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Option #1 Gate Drive Conditions (IXDD614/IXDN614)						
Supply Voltage, High Side Driver	V _{CC}	V _{GH}	15	20	30	V
Supply Voltage, Low Side Driver	V _{CC}	V _{GL}	5	6.5		V
Off State Voltage, Both Drivers	GND	V _{EE}		-10	0	V
Gate Control Input Signal, Low	IN		-5.0	0	0.8	V
Gate Control Input Signal, High	IN		4	5.0	V _{CC} +0.3	V
Enable, Low	EN	IXDD614 Only			1/3*V _{CC}	V
Enable, High	EN	IXDD614 Only	2/3*V _{CC}			V
Output Voltage, Low	V _{OUT}				0.025	V
Output Voltage, High	V _{OUT}		V _{CC} -0.025			V
Output Current, Peak	I _{OUT}	Package Limited			14	A
Output Current, Continuous	I _{OUT}			0.5	4.0	A
Passive Gate Components						
Gate Resistance	R _G	V _{GL} = 6.0 V, I _G ≈ 0.5 A		1.6	5	Ω
Gate Capacitance	C _G	V _{GH} = 20 V, I _{G,pk} ≈ 2.0 A	5	9		nF

Package Dimensions:

NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

Revision History			
Date	Revision	Comments	Supersedes
2013/08/29	3	Updated Switching Characteristics	
2013/06/14	2	Updated Electrical Characteristics	
2013/02/21	1	Revised electrical characteristics	
2012/12/03	0	Initial release	

Published by
 GeneSiC Semiconductor, Inc.
 43670 Trade Center Place Suite 155
 Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

SPICE Model Parameters

Copy the following code into a SPICE software program for simulation of the GA16JT17 SJT device.

```
*      MODEL OF GeneSiC Semiconductor Inc.
*
*      $Revision:   1.0           $
*      $Date:      26-AUG-2013   $
*
*      GeneSiC Semiconductor Inc.
*      43670 Trade Center Place Ste. 155
*      Dulles, VA 20166
*      http://www.genesicsemi.com/index.php/sic-products/sjt
*
*      COPYRIGHT (C) 2013 GeneSiC Semiconductor Inc.
*      ALL RIGHTS RESERVED
*
*  These models are provided "AS IS, WHERE IS, AND WITH NO WARRANTY
*  OF ANY KIND EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED
*  TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
*  PARTICULAR PURPOSE."
*  Models accurate up to 2 times rated drain current.
*
.model GA16JT17 NPN
+ IS      6.03E-47
+ ISE     1.72E-28
+ EG      3.2
+ BF      52
+ BR      0.55
+ IKF     300
+ NF      1
+ NE      1.868
+ RB      0.26
+ RE      0.1
+ RC      0.01
+ CJC     5.68E-10
+ VJC     2.978967839
+ MJC     0.466424924
+ CJE     1.72E-09
+ VJE     2.77859888
+ MJE     0.484150812
+ XTI     3
+ XTB     -1.2
+ TRC1    6.00E-03
+ VCEO    1700
+ ICRATING 16
+ MFG      GeneSiC_Semiconductor
*
*  End of GA16JT17 SPICE Model
```