




8D Series

MIL-DTL-38999 Series III



SOURIAU
Connection Technology

8D Series - MIL-DTL-38999 Series III

Contents

Overview

• MIL-DTL-38999: A universal product platform	04
• 8D Series - Presentation	05
• Product overview	06
• A superior concept	07
• A performing MIL standard connector design	08
• Technical features & benefits	09
• Contact layouts	11
• Contact layouts (matrix)	15

Standard Series

• Aluminum Series	
Part numbers	18
Dimensions	20
Backshells	23
Dummy receptacle	28
Caps	29
Connectors weight	30
• Composite Series	
Part numbers	32
Dimensions	34
Backshells	36
Connectors weight	37
• Stainless Steel Series	
Part numbers	40
Dimensions	42
Connectors weight	45
• Titanium Series	
Part numbers	48
Dimensions	49
Connectors weight	52
• Bronze Series	
Part numbers	54
Dimensions	55
Backshells	58
Dummy receptacle	62
Caps	63

Common Section

• Contents	64
• Orientations	65
• Panel cut-out	65
• Crimp contacts	66
• Straight PC tail contacts	68
• Coaxial contacts #12	69
• Solder cup	69
• Crimp contacts: 1500 mating	69
• Wire wrap contacts	69
• Quadrax #8 contacts	69
• Thermocouple contacts	70
• Dummy contacts	70
• Filler plugs	70
• Insertion and extraction tools	71
• Crimping tools	71
• Wiring instruction	72
• Gaskets	74
• Plastic protective caps	74

Derived Series

• Reinforced sealing Series	75
• Hermetic Series	77
• Clinch nuts	81
• Double flange	85
• Optical ELIO® Contacts	91
• RJ45/USB Series	101

Range Extension

• 8D8 / 8D9 Series	110
• 8DB bulkhead feedthrough	110
• 8D hermetic ELIO® feedthrough	111
• 8D hermetic aluminum power & signal connector	111
• Coordinates for straight PC tail terminations	112

8D Series - MIL-DTL-38999 Series III

MIL-DTL-38999: A universal product platform



Series I: 8LT Series

- ▶ High density (#22D) MIL-spec circular (1980's)
- ▶ Scoop proof
- ▶ Coupling system: Bayonet
- ▶ Method of mounting: screws or jam nut
- ▶ Shell: Aluminum alloy
- ▶ Plating: olive green cadmium or nickel
- ▶ QPL approved
- ▶ Numerous layouts



Series I.5: 8ST Series

- ▶ High density - same layouts as 38999 Series I
- ▶ Lightweight version of Series I
- ▶ Scoop proof, bayonet coupling
- ▶ Method of mounting: screws or jam nut
- ▶ Shell: Aluminum alloy
- ▶ Plating: olive green cadmium or nickel
- ▶ VG 96912 German specification
- ▶ JN 1003 Typhoon specification



Series II: 8T Series

- ▶ Short version of MIL-DTL-38999 Series I
- ▶ Low profile = lightweight
- ▶ High density MIL-spec circular (1980's)
- ▶ Non-scoop proof, bayonet coupling
- ▶ Method of mounting: screws or jam nut
- ▶ Shell: Aluminum alloy
- ▶ Plating: olive green cadmium, nickel, hard anodized
- ▶ QPL approved
- ▶ Numerous layouts

8D Series - MIL-DTL-38999 Series III



8D Series - Presentation

38999 Series III: 8D Series

Since the early 80's, Souriau is a major supplier of 38999 Series III, the screw-coupled version of MIL-C-38999. Present on the main international programs, Souriau has developed a range of products that meet the performance required in extreme environments:

- Civil and military aeronautics
- Ground military
- Industrial
- Marine and offshore

This evolution of MIL-C-38999 allows:

- A high contact density up to 128 contacts #22D
- A quick screw coupling with self locking mechanism
- High resistance to harsh environments (vibration, 200°C)

Always at the cutting edge of innovation, Souriau's teams have continuously improved this range of connectors:

- Composite version in the 90's (Its choice is recommended wherever weight is critical)
 - Titanium version for weight saving and very high and mechanical resistance
 - Today Souriau remains innovative with cadmium free and RoHS solutions.
- In 2009 Souriau was the first to be QPL qualified for Zinc Nickel plating.

This product family is in accordance with MIL-DTL-38999 Series III, EN 3645, CECC (standard for bronze shell), ... and also meets many customers' standards (Rolls Royce, ABS, BACC, ...)