



NOTES:

1. MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-019)
2. COLOR: BLACK.
3. TO FIT IN A $\varnothing 7.9 \pm .002$ [$\varnothing .313 \pm .005$] THREADED HOLE.
MINIMUM RECOMMENDED PANEL THICKNESS: 6 mm [.236]
PART CAN ALSO FIT NON THREADED HOLE DIA. 7 mm [.276]
4. PART DESIGNED IN mm, ALTERNATE UNITS FOR REFERENCE ONLY.
5. TOOL REQUIRED FOR INSTALLATION, AND PHILIPS SCREWDRIVER FOR REMOVAL.

TITLE: BARBED PUSH FASTENER, REMOVABLE				DWG IN mm [IN]	DWG IN mm [IN]	DWG IN mm [IN]
CREATED USING SOLIDWORKS	FILE #: BPFR-1	DWN: SK	APP: S.K.			
GENERAL TOLERANCE UNLESS OTHERWISE NOTED ±0.25 ANG.=±1°	SHEET: 1 OF 1	SHEET SIZE: A	DT: 07/01/08	CHKD: D.Z.	PART #	PRINT TYPE
	RE: RICHCO, INC. --					
					RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060	
A	RELEASED FOR PRODUCTION	SK 12/19/08			BPFR-1	CA
REV.	DESCRIPTION	ENGR.	DATE			