



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: INTERNET350SER

Internet Office 350VA Ultra-compact Standby 120V UPS with Serial port

Highlights



- 350VA ultra-compact 120V standby UPS
- Maintains AC output during power failures
- 3 UPS battery supported outlets, 3 surge-only outlets
- DB9 serial port, TEL/DSL protection
- NEMA 5-15P input plug and 6 NEMA 5-15R outlets

Description

Ultra-compact standby UPS with built-in DB9 serial monitoring port protects PCs, network workstations, and other systems reliant upon a basic communications interface for UPS monitoring and unattended system shutdown. Maintains AC output during blackouts and brownouts starting at 99V. Includes DB9 monitoring port with cabling, TEL/DSL line surge suppression, surge only outlets and LED indicators. PowerAlert software available free via download.

Package Includes

- INTERNET350SER UPS system
- DB9 Serial Cable
- Instruction manual

Features

- INTERNET350SER standby UPS offers protection from blackouts, brownouts and surges on both AC and dialup modem lines
- Provides seamless battery derived AC output during blackouts and severe brownouts so that connected equipment can be shut down without data loss
- Built-in DB9 interface port with basic communication monitoring enables automatic system shutdown if power fails while the system runs unattended
- PowerAlert software available via free download from <http://www.tripplite.com>, DB9 cable included
- 3 battery supported outlets protect computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Attractive stealth black UPS color scheme
- Built-in single line phone jacks with line splitter protects peripherals with a standard dialup phone line connection
- Built-in audible alarm and front panel LEDs offer continuous status information regarding line and battery power operation
- 350VA /180 watt power handling ability supports entry-level PC systems for several minutes during power fail conditions
- Includes attached 6 ft. AC power cord with space saving right-angle plug, on/off power switch
- Compatible with 120V/60 Hz applications in USA, Canada, Mexico and other countries
- \$100,000 [connected equipment insurance](#) (USA, Puerto Rico, & Canada only)

Specifications

| OUTPUT | |
|--|---|
| Output Volt Amp Capacity (VA) | 350 |
| Output Watt Capacity (watts) | 180 |
| Nominal Output Voltage(s) Supported | 115V; 120V |
| Frequency compatibility | 60 Hz |
| Output voltage regulation (Battery mode) | 115V (+/- 5%) |
| Built-in UPS output receptacles | 6 5-15R outlet(s) |
| Surge suppression only outlets | 3 UPS outlets, 3 surge-only outlets |
| Output AC waveform (AC mode) | Sine wave |
| Output AC waveform (battery mode) | PWM sine wave |
| INPUT | |
| Rated input current (at maximum load) | 12A |
| Nominal Input Voltage(s) Supported | 120V AC |
| UPS input connection type | 5-15P |
| UPS Input cord length (ft.) | 6 |
| UPS Input cord length (m) | 1.8 |
| Recommended Electrical Service | 15A 120V |
| Phase | Single-Phase |
| BATTERY | |
| Full load runtime (minutes) | 2.5 min. (180w) |
| Half load runtime (minutes) | 10 min. (90w) |
| DC system voltage (VDC) | 12 |
| LEDS ALARMS & SWITCHES | |
| LED Indicators | 2 LEDs indicate power status and overload/check battery status |
| Alarms | Audible alarm indicates power-failure and overload status |
| Switches | Combination switch controls on/off power status and self-test operation |
| SURGE / NOISE SUPPRESSION | |
| UPS AC suppression joule rating | 510 |
| UPS AC suppression response time | Instantaneous |
| UPS Dataline suppression | 1 line TEL/DSL (1 in / 1 out) |

| | |
|--|---|
| EMI / RFI AC noise suppression | Yes |
| PHYSICAL | |
| Installation form factors supported with included accessories | Tower; Ultra-compact desktop |
| Primary form factor | Desktop |
| UPS / Power Module dimensions in primary form factor (height x width x depth / inches) | 3 x 10.5 x 5 |
| UPS / Power Module dimensions in primary form factor (height x width x depth / cm) | 7.6 x 26.7 x 12.7 |
| UPS / Power Module weight (lbs) | 7.7 |
| UPS / Power Module weight (kg) | 3.5 |
| UPS Shipping dimensions (height x width x depth / inches) | 4.5 x 12.5 x 7.8 |
| UPS Shipping dimensions (height x width x depth / cm) | 11.4 x 31.8 x 19.7 |
| Shipping weight (lbs) | 10 |
| Shipping weight (kg) | 4.5 |
| UPS housing material | ABS |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity | 0 to 95%, non-condensing |
| AC mode BTU / hr. (full load) | 39.1 |
| Battery mode BTU / hr. (full load) | 53.2 |
| COMMUNICATIONS | |
| Communications interface | DB9 Serial |
| PowerAlert software | Free download from www.tripplite.com |
| Communications cable | DB9 interface cable included |
| LINE / BATTERY TRANSFER | |
| Transfer time | 2-4 milliseconds |
| Low voltage transfer to battery power (setpoint) | 99 |
| High voltage transfer to battery power (setpoint) | 139 |
| SPECIAL FEATURES | |

| | |
|---|--|
| Cold Start (startup in battery mode during a power failure) | Cold-start operation supported |
| CERTIFICATIONS | |
| UPS Certifications | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI) |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 3-year limited warranty |
| Product Warranty Period (International) | 2-year limited warranty |
| Product Warranty Period (Mexico) | 3-year limited warranty |
| Product Warranty Period (Puerto Rico) | 3-year limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$100,000 Ultimate Lifetime Insurance |

Related Items

Optional Products

| Related Model | Description | Qty. |
|--------------------------------|--|------|
| CT120 | Instant-Read- AC Outlet Circuit Tester | 1 |
| DCATV | Network Surge Suppressor - Essential protection for TV/VCR coaxial lines | 1 |
| DNET1 | Network Surge Suppressor - Essential protection for data and communication lines | 1 |
| DTEL2 | Network Surge Suppressor - Essential protection for data and communication lines | 1 |
| WEXT5-INTERNET | 5-Year Extended Warranty - For Internet Office, AVR and ECO Series UPS Systems | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2682.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.