



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SMART2200RMXL2U

SmartPro 2.2kVA 1920W Line Interactive Sine Wave UPS, Extended-Run & SNMPWEBCARD options, 2U Rack/Tower, LCD, USB, RS232,EPO, 120V

Highlights

- 2.2kVA / 2200VA / 1920W line interactive 2U rack/tower UPS, Sine Wave
- 120V output, Corrects brownouts and overvoltages from 83V to 145V
- 0.87 Power Factor, Interactive LCD interface
- Extended runtime options up to 1600W
- 4 post compatible mounting accessories
- 96% line-mode efficiency, 2 switched load banks
- USB, RS232, EPO and slot for SNMPWEBCARD option
- 120V NEMA 5-20P input, 4 NEMA 5-15R & 4 NEMA 5-15/20R outlets



Description

Tripp Lite SmartPro Line Interactive UPS with enhanced LCD interface offers network-grade power protection for critical server, network and telecommunications equipment. Line Interactive Uninterruptible Power Supply (UPS) with built-in Auto-Voltage Regulation (AVR) actively corrects brownouts and overvoltages back to usable levels while maintaining a full battery charge in case of power failure. Tripp Lite's unique configuration excels in exceptionally poor-power environments with two separate levels of voltage boost to correct both slight undervoltages and severe brownout conditions. Interactive LCD interface reports UPS operating mode, detailed UPS and site-power data, plus enables a variety of UPS setup and configuration options. Super-fast switchover from line to battery power occurs within milliseconds to maintain operation of connected equipment without interruption or reboot. 96% line-mode efficiency offers reduced heat emissions and operating costs. Network management interfaces support communications via USB, RS-232 and optional SNMPWEBCARD network interface. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Network communications ports enable detailed monitoring of equipment load levels, self-test data and utility power conditions. Includes PowerAlert monitoring software and complete cabling. Switched output load banks enable scheduled and real-time remote reboot and load shedding of select outlets. Emergency Power Off (EPO) interface. LCD display panel easily rotates for viewing in rackmount or tower configurations. Audible alarm with push-button momentary alarm-cancel and silent-mode configuration options. Programmable self-test. Field-replaceable, hot-swappable battery modules.

Package Includes

- SMART2200RMXL2U UPS system
- PowerAlert software with USB, Serial & EPO cabling
- 4 post installation kit
- Owner's manual

Features

- Tripp Lite SMART2200RMXL2U line interactive 2U rack/tower UPS with 2200VA / 2.2kVA / 1920W capacity and extended runtime options
- Line interactive UPS with Automatic Voltage Regulation (AVR) corrects brownouts and overvoltages from 83 to 145V
- NEMA 5-20P input plug; 4 NEMA 5-15/20R and 4 5-15R output receptacles, Two independently switched output load banks
- Maintains uninterrupted operation of connected networking equipment during blackouts, surges, brownouts and overvoltages
- High 96% efficiency rating in line-power mode offers reduced power consumption and BTU emissions
- Internal batteries offer 12 minutes at 50% load (960W) and 4.5 minutes at 100% load (1920W)
- Extended runtime is available with optional BP48V24-2U (limit 1) OR BP48V60RT3U (no limit), Output is reduced to 1600 watts maximum with external battery packs
- External battery configurations require the use of Tripp Lite's External Battery Configuration Software (see manual)
- Hot-swappable, user-replaceable internal batteries and external battery packs can be replaced with no disruption to connected equipment
- Front panel LCD monitoring screen with MODE and ENTER buttons reports operating mode with 5-bar battery charge graphic, plus 7 selectable screens of detailed UPS and site power information
- LCD interface also supports a number of advanced user setup and operating preferences

- Ships with 4 post rackmount installation hardware; Optional 2POSTRMKITWM enables 2 post rackmount/wallmount installation; Optional 2-9USTAND enables tower placement
- Built-in USB, RS-232 and optional SNMPWEBCARD accessory monitoring options
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Included PowerAlert UPS monitoring software; Built-in Emergency Power Off (EPO) interface with cable

Specifications

| OUTPUT | |
|--|--|
| Output Volt Amp Capacity (VA) | 2200 |
| Output kVA capacity (kVA) | 2.2 |
| Output Watt Capacity (watts) | 1920 |
| Output kW capacity | 1.92 |
| Output power factor | 0.87 |
| Output Capacity Details | Output derates to 1600 watts in all external battery pack configurations |
| Nominal Output Voltage(s) Supported | 120V |
| Frequency compatibility | 60 Hz |
| Output voltage regulation (line mode) | -14%, +6% |
| Output voltage regulation (Battery mode) | +/- 5% |
| Built-in UPS output receptacles | 4 5-15R outlet(s); 4 5-15/20R outlet(s) |
| Built-in controllable switched load banks | Two switched single outlet load banks (1 5-15/20R & 1 5-15R) |
| Output AC waveform (AC mode) | Pure Sine wave |
| Output AC waveform (battery mode) | Pure Sine wave |
| INPUT | |
| Rated input current (at maximum load) | 16.0A |
| Nominal Input Voltage(s) Supported | 120V AC |
| UPS input connection type | 5-20P |
| UPS Input cord length (ft.) | 10 |
| UPS Input cord length (m) | 3 |
| Recommended Electrical Service | 20A 120V |

BATTERY

Full load runtime (minutes) 4.5 min. (1920w)

Half load runtime (minutes) 12 min. (960w)

Expandable battery runtime Extended runtime supported via optional external battery packs

External battery pack compatibility [BP48V24-2U](#) (limit 1); [BP48V60RT-3U](#) (multi-pack compatible)

Expandable runtime description Maximum output capacity is 1600 watts when used with external battery packs

DC system voltage (VDC) 48

Battery recharge rate (included batteries) Less than 4.5 hours from 10% to 90%

Replacement battery cartridge (internal UPS battery replacement) [RBC94-2U](#)

Battery Access Front panel battery access door

Battery replacement description Hot-swappable, user replaceable batteries

VOLTAGE REGULATION

Voltage regulation description Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 83 to 145

Overvoltage correction Voltage reduction of 12% applies when input is between 127 and 145

Undervoltage correction Voltage boost of 12% applies when input voltage is between 96 and 108

Severe undervoltage correction Voltage boost of 24% applies when input voltage is between 83 and 95

LEDS ALARMS & SWITCHES

Front panel LCD display Front panel LCD information and configuration screen offers detailed UPS and site power status and operating data, plus configuration of voltage, operating mode, alarm function and a variety of additional options (see manual for detailed LCD configuration and monitoring options)

Alarms Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions

Alarm cancel operation Power-fail alarm can be temporarily silenced using alarm-cancel switch; silent mode alarm configuration option available

Switches 3 pushbutton switches control OFF / ON power status, MODE selection and MUTE / ENTER control functions

SURGE / NOISE SUPPRESSION

UPS AC suppression joule rating 570

UPS AC suppression response time Instantaneous

EMI / RFI AC noise suppression Yes

PHYSICAL

| | |
|---|---|
| Installation form factors supported with included accessories | 4 post 19 inch rackmount |
| Included mounting accessory description | Adjustable mounting rail kit included |
| Installation form factors supported with optional accessories | 2 post rackmount (2POSTRMKITWM); Wallmount (2POSTRMKITWM); Tower (2-9USTAND) |
| Primary form factor | Rackmount |
| UPS / Power Module dimensions in primary form factor (height x width x depth / inches) | 3.46 x 17.32 x 19.29 |
| UPS / Power Module dimensions in primary form factor (height x width x depth / cm) | 8.8 x 44 x 49 |
| Rack Height | 2U |
| Secondary form factor | Tower (requires 2-9USTAND) |
| UPS / Power Module weight (lbs) | 57.6 |
| UPS / Power Module weight (kg) | 26.2 |
| UPS Shipping dimensions (height x width x depth / inches) | 9.1 x 22.44 x 24.2 |
| UPS Shipping dimensions (height x width x depth / cm) | 23 x 57 x 61.5 |
| Shipping weight (lbs) | 68.8 |
| Shipping weight (kg) | 31.2 |
| Cooling method | Fan |
| UPS housing material | Steel |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity | 0 to 95%, non-condensing |
| AC mode BTU / hr. (full load) | 306 |
| COMMUNICATIONS | |
| Communications interface | USB (HID enabled); DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface |

| | |
|---|--|
| Network monitoring port description | Supports detailed monitoring of UPS and site power conditions |
| PowerAlert software | Included |
| Communications cable | USB and DB9 cabling included |
| WatchDog compatibility | Supports Watchdog application, OS and hard-reboot restart options for remote applications |
| LINE / BATTERY TRANSFER | |
| Transfer time | 5 milliseconds (line to battery mode); 1 millisecond (battery to line mode) |
| Low voltage transfer to battery power (setpoint) | 83 |
| High voltage transfer to battery power (setpoint) | 145 |
| SPECIAL FEATURES | |
| Grounding lug | Back panel grounding lug |
| Cold Start (startup in battery mode during a power failure) | Cold-start operation supported |
| High availability UPS features | Hot swappable batteries |
| Green & high efficiency features | Greater than 95% efficiency - GREEN UPS; Individually controllable load banks |
| CERTIFICATIONS | |
| UPS Certifications | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI); ROHS (Restriction of Hazardous Substances) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year warranty, 3 year with registration . Note: registration is required for 3-year warranty. |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 Ultimate Lifetime Insurance |

Related Items

Optional Products

| Related Model | Description | Qty. |
|---------------------------------|--|------|
| WEXT5-2200-3000 | 5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA or less | 1 |
| BP48V24-2U | BP48V242U - External Battery Pack for UPS System | 1 |
| BP48V60RT-3U | External Battery Pack and Cable. 3U, Expandable, Blue 2-Point Connector | 1 |
| SNMPWEBCARD | For remote monitoring and control via SNMP, Web, or Telnet. | 1 |
| MODBUSCARD | For remote monitoring and control via MODBUS protocol | 1 |
| ENVIROSENSE | Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.) | 1 |
| SRSWITCH | Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE | 1 |

| | | |
|------------------------------|--|---|
| 2-9USTAND | Enables Tower Placement of Rackmount UPS Systems | 1 |
| 2POSTRMKITWM | Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems | 1 |
| WATCHDOGSW | WatchDog Service Monitoring / Reboot Software | 1 |
| PDU1220 | Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment | 1 |
| PDUV20 | Single-Phase Basic PDU, 20A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUMH20 | Single-Phase Metered PDU, 20A 120V, 1U Horizontal Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUNV | Single-Phase Basic PDU, 16A 100-240V, 1U Rackmount, C13 C19 outlets, C20 input and C14, L6-20P, L5-20P, 5-20P and 5-15P adapters | 1 |
| PDUMV20 | Single-Phase Metered PDU, 20A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUMNV20 | Single-Phase Monitored PDU, 20A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUMNH20 | Single-Phase Monitored PDU, 20A 120V, 1U Horizontal Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUMV20NET | Single-Phase Switched PDU, 20A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter | 1 |
| PDUMH20AT | Single-Phase Auto Transfer Switch / Metered PDU, 20A 120V, 1U Horizontal Rackmount, 5-15/20R outlets, 2 L5-20P / 5-20P adapters | 1 |
| PDUMH20ATNET | Single-Phase Auto Transfer Switch / Switched PDU 20A 120V, 1U Horizontal Rackmount, 5-15/20R outlets, 2 L5-20P / 5-20P inputs | 1 |
| PDUB20 | Single-Phase Hot-Swap PDU, 20A 120V, 2U Horizontal Rackmount, NEMA 5-15R & 5-15/20R outlets, set of 2 NEMA 5-20P input plugs | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3264.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.