



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUINT2000XL

### SmartOnline Tower UPS System - True on-line power for mission-critical applications



#### Highlights

- 2000VA on-line, double-conversion, extended run tower UPS
- Maintains sine-wave 220/230/240V +/-2% output during overvoltages to 280V and brownouts as low as 80V (50/60Hz auto-sensing)
- Network communications supported via serial port and SNMP/Web card slot
- Input: C20 inlet / Output: 8 x C13 outlets (3 x C13-to-C14 jumper cables included)
- Fault-tolerant auto-bypass and current monitoring

#### Description

Tripp Lite's SmartOnline SUINT2000XL on-line, double-conversion UPS protects critical server, networking and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Space-saving upright tower format. Large capacity 2000VA/1400W UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at selectable 220/230/240V AC (+/-2%). Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS types. True sine wave output and zero transfer time offer guaranteed compatibility with all equipment types. Includes 8 C13 outlets. Battery support can be extended with external battery packs (part# BP72V18). Includes slot for internal SNMP/web card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data.

#### Package Includes

- SUINT2000XL UPS System
- PowerAlert Software CD-ROM and cabling
- 3 C13-to-C14 jumper cables
- Owner's manual with warranty information

#### Features

- True on-line, double conversion UPS provides pure sine wave AC output at all times
- Maintains continuous operation with zero transfer time through blackouts, voltage fluctuations and surges
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems
- Corrects brownout and overvoltages from 175-280V at full load. Input voltage range extends to 80-280V at 50% load or less
- 2000VA/1400W power capacity with 8 C13 outlets
- IEC320-C20 input connection accepts a variety of detachable cordsets to match country or site-specific wall receptacles
- Standard internal battery set provides 14 min. runtime at half load and 5 min. runtime at full load
- Expandable runtime with optional external battery packs (part# BP72V18; multi-pack compatible)
- DB9 serial port for network interface; SNMP compatible
- Slot for optional SNMP/web card (part# SNMPWEBCARD)
- PowerAlert unattended shutdown software and network cable included
- Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- Diagnostic LEDs
- 3 C13-to-C14 jumper cables included

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	2000
Output kVA capacity (kVA)	2
Output Watt Capacity (watts)	1400
Output kW capacity	1.4
Output power factor	0.7
Crest Factor	3:1
Nominal Output Voltage(s) Supported	220V; 230V; 240V
Nominal Voltage details	230V default
Frequency compatibility	50 / 60 Hz
Frequency compatibility details	Output frequency matches input nominal on startup, defaults to 50 Hz on cold-start
Output voltage regulation (line mode)	+/- 2%
Output voltage regulation (Economy line mode)	+/- 10%
Output voltage regulation (Battery mode)	+/- 2%
Built-in UPS output receptacles	8 C13 outlet(s)
Included output power cables	Includes 3 C13 to C14 output power cables
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Pure Sine wave
INPUT	
Rated input current (at maximum load)	7.4A (220V), 7.1A (230V), 6.8 (240V)
Nominal Input Voltage(s) Supported	220V AC; 230V AC; 240V AC
UPS input connection type	C20 inlet
UPS input connection description	IEC320-C20 input connection accepts a variety of detachable cordsets to match country or site-specific wall receptacles
Input circuit breaker	20A
Phase	Single-Phase

<b>BATTERY</b>	
Full load runtime (minutes)	5 min. (1400w)
Half load runtime (minutes)	14 min. (700w)
Expandable battery runtime	Extended runtime supported via optional external battery packs
External battery pack compatibility	<a href="#">BP72V15-2U</a> (limit 1); <a href="#">BP72V28RT-3U</a> (multi-pack compatible)
DC system voltage (VDC)	72
Battery recharge rate (included batteries)	Less than 4 hours from 10% to 90%
Battery replacement description	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
Voltage regulation description	Online, double-conversion power conditioning
Overvoltage correction	2% output voltage regulation during overvoltages to 280
Undervoltage correction	2% output voltage regulation during undervoltages to 175
Severe undervoltage correction	2% output voltage regulation during undervoltages to 80 (under 50% load only)
<b>LEDS ALARMS &amp; SWITCHES</b>	
LED Indicators	14 LEDs indicate line power, online mode, economy/bypass mode, on-battery, overload, battery low, replace battery and fault status information - includes 4-LED meter display for load and battery charge level
Alarms	Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC suppression joule rating	570
UPS AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
<b>PHYSICAL</b>	
Installation form factors supported with included accessories	Tower
Primary form factor	Tower
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	14.7 x 5.5 x 16.7

UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	37.3 x 14 x 42.4
UPS / Power Module weight (lbs)	67.2
UPS / Power Module weight (kg)	30.5
UPS Shipping dimensions (height x width x depth / inches)	19.4 x 9.8 x 23.8
UPS Shipping dimensions (height x width x depth / cm)	49.3 x 24.9 x 60.5
Shipping weight (lbs)	73.8
Shipping weight (kg)	33.5
Cooling method	Fan
UPS housing material	Steel
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	528.9
AC economy mode BTU / hr. (full load)	303.8
Battery mode BTU / hr. (full load)	774.9
AC economy mode efficiency rating (100% load)	94%
Audible Noise	< 45 dB at front side 1m
<b>COMMUNICATIONS</b>	
Communications interface	DB9 Serial; Slot for SNMP/Web interface
Network monitoring port description	Supports detailed monitoring of UPS and site power conditions; DB9 port supports RS232 communications
PowerAlert software	Included
Communications cable	DB9 cabling included
<b>LINE / BATTERY TRANSFER</b>	
Transfer time	No transfer time (0 ms.) in online, double-conversion mode
Low voltage transfer to battery power (setpoint)	175V (100% load), 80V (

High voltage transfer to battery power (setpoint)	280
<b>SPECIAL FEATURES</b>	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
High availability UPS features	Automatic inverter bypass
<b>CERTIFICATIONS</b>	
UPS Certifications	CE
UPS Certification details	CE EN62040-1-1, EN62040-2 Class A
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">AS400CABLE KIT</a>	Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers	1
<a href="#">BP72V15-2U</a>	BP72V15-2U - External Battery Pack for UPS System	1
<a href="#">BP72V28RT-3U</a>	BP72V28RT-3U - External Battery Pack for UPS System	1
<a href="#">DCATV</a>	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	1
<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	1
<a href="#">DTEL2</a>	Network Surge Suppressor - Essential protection for data and communication lines	1
<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3252](http://www.tripplite.com/en/products/model.cfm?txtModelID=3252).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.