



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SPS-615-HG

**Commercial-Grade Surge Suppressor with Hospital-Grade plug and receptacles; diagnostic LEDs and a heavy-duty metal housing**



### Highlights

- 6 hospital-grade outlets
- 1050 joule rating
- 15-ft. cord with molded hospital-grade plug
- All metal housing

### Description

Tripp Lite's SPS-615-HG offers 15A-capacity AC surge suppression and power distribution in a rugged all-metal outlet strip for 120V applications. Offers 6 AC outlets, 15-ft. AC power cord, built-in resettable circuit breaker and 1050-joule AC surge suppression. Features safety-enhanced hospital grade plug and outlets. Switch safety cover prevents accidental shutoff. Optional use keyhole mounting tabs. 15A circuit breaker controls power to all outlets and protects against overloads. LED indicator verifies line power available.

PLUG/OUTLETS: NEMA 5-15PHG Hospital-Grade Plug and 6 x NEMA 5-15RHG Hospital-Grade AC Outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet surge suppression strip

SUPPRESSION: AC: 150V RMS Clamping/1050 joules

#### Applications

- AC power distribution and surge suppression with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

#### Package Includes

- SPS-615-HG Surge Suppressor
- Instruction manual with warranty information

### Features

- 1050-joule AC surge suppression rating
- Rugged all-metal housing withstands years of use without loss of ground path continuity
- 6 NEMA5-15R Hospital-Grad AC outlets
- 15-ft. AC cord with integrated, molded Hospital-Grade NEMA 5-15PHG plug
- Keyhole mounting tabs and flanges
- Switch safety cover prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker

- 120 volt, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)
- UL1449 3rd Edition listed

## Specifications

| <b>OVERVIEW</b>                    |  |
|------------------------------------|--|
| Intended Application               | Hospital/Medical   |
| Model Type                         | NOT For Patient Areas  |
| <b>OUTPUT</b>                      |  |
| Frequency compatibility            | 50 / 60 Hz   |
| Output watts                       | 1800   |
| Circuit Breaker (amps)             | 15   |
| Outlet quantity / type             | 6 NEMA 5-15R-HG  |
| Transformer accommodation          | Supports 1 large transformer plug accessories without covering remaining outlets |
| <b>INPUT</b>                       |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 120V (110-125V)  |
| Input connection type              | NEMA 5-15P-HG Hospital-Grade   |
| Input cord length (ft.)            | 15   |
| Input cord length (m)              | 4.6  |
| Voltage compatibility (VAC)        | 120  |
| Maximum Surge Amps                 | 19500  |
| <b>LEDS ALARMS &amp; SWITCHES</b>  |  |
| Diagnostic LEDs                    | LINE POWER PRESENT (green)   |
| <b>SURGE / NOISE SUPPRESSION</b>   |  |
| AC suppression joule rating        | 1050   |
| AC suppression response time       | < 1 ns   |
| Protection modes                   | Includes full normal mode surge suppression                                      |
| Clamping voltage (RMS)             | 140V   |
| <b>DATALINE SURGE SUPPRESSION</b>  |  |
| Telephone/DSL Protection           | No   |
| Cable (Coax) Protection            | No   |
| Network (Ethernet) Protection      | No   |
| <b>PHYSICAL</b>                    |  |
| Shipping Dimensions (HWD/in)       | 2.25 x 15 x 6  |

|  |   |
|--|---|
| <b>Shipping Dimensions (HWD/cm)</b>        | 5.7 x 38.1 x 15.24                              |
| <b>Shipping weight (lbs)</b>               | 3.5   |
| <b>Shipping weight (kg)</b>                | 1.59  |
| <b>Unit Dimensions (HWD/in)</b>            | 1.5 x 13.75 x 2.5                               |
| <b>Unit Dimensions (HWD/cm)</b>            | 3.81 x 34.9 x 6.35                              |
| <b>Unit weight (lbs)</b>                   | 3.2   |
| <b>Unit weight (kg)</b>                    | 1.45  |
| <b>Material of construction</b>            | Metal   |
| <b>Integrated keyhole mounting tabs</b>    | Includes keyhole mounting tabs and flanges      |
| <b>Receptacle Color</b>                    | White   |
| <b>AC line cord color</b>                  | Gray  |
| <b>Style</b>                               | Strip   |
| <b>CERTIFICATIONS</b>                      |   |
| <b>UL1449 3rd Edition (AC Suppression)</b> | UL1449 3rd Edition (Series Number: AGIB12015SL) |
| <b>UL1363 (Power Tap)</b>                  | UL1363 (Series Number: AGIB12015SL)             |
| <b>cUL / CSA (Canada)</b>                  | cUL (Series Number: AGIB12015SL)                |
| <b>WARRANTY</b>                            |   |
| <b>Product Warranty Period (Worldwide)</b> | Lifetime limited warranty                       |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=130](http://www.tripplite.com/en/products/model.cfm?txtModelID=130).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.