



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SK3-0

### 3 Outlet, Direct Plug-In, 660 Joules - Protect It! Surge Suppressor



#### Highlights

- 3 outlets/direct plug-in
- 660 joule rating
- Diagnostic LEDs
- \$5,000 Ultimate Lifetime Insurance (USA & Canada only)

#### Description

The SK3-0 surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 3 outlets and 660 joules of surge energy absorption. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$5,000 Ultimate Lifetime Insurance (USA & Canada only).

#### Applications

- Ideal for any desktop, network or home computing application requiring AC protection

#### Package Includes

- SK3-0 surge suppressor

#### Features

- 3 outlets / direct plug-in
- Surge suppression rating: 660 joules
- EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$5,000 Ultimate Lifetime Insurance (USA and Canada Only)

#### Specifications

OVERVIEW	
Intended Application	Home/Office
OUTPUT	
Frequency compatibility	60 Hz
Output watts	1875
Circuit Breaker (amps)	15
Outlet quantity / type	3 NEMA 5-15R
Outlet Type	NEMA 5-15R

<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V
Input connection type	NEMA 5-15P input plug
Input plug features	120V, 15A
Input cord length details	Direct Plug-In
Voltage compatibility (VAC)	120
Maximum Surge Amps	39000
<b>UPC ASSIGNMENT</b>	
Unit Carton UPC#	037332148308
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	660
AC suppression response time	< 1ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
Clamping voltage (RMS)	150
AC suppression surge current rating	27,000
UL1449 let through rating	500, 400, 500
Immunity	Conforms to IEE 587/ANSI C62.41
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Unit Dimensions (HWD/in)	2.5 x 3.8 x 2.1
Unit Dimensions (HWD/cm)	6.35 x 9.7 x 5.33
Unit weight (lbs)	.20
Unit weight (kg)	.09
Material of construction	Plastic
Integrated keyhole mounting tabs	Direct plug-in suppressor mounts directly to a wall receptacle
Housing Color	Light Gray
Receptacle Color	Gray
Style	Direct plug-in
<b>CERTIFICATIONS</b>	

<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449 3rd Edition
<b>Approvals</b>	RoHS
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$5,000 <a href="#">Ultimate Lifetime Insurance</a>

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4981](http://www.tripplite.com/en/products/model.cfm?txtModelID=4981).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.