



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: PDUMH32HV

Single Phase Metered PDU, 7.3kW, 2U rackmount, 18 outlets (2 C19, 16 C13), 3.6m cord, IEC-309 Blue 230V 32A input

Highlights

- Metered single phase 32A 230V 2U horizontal rackmount PDU
- Set of 2 current meters reports current in amps for each output load bank
- Attached 12 ft. / 3.6m cord with IEC-309 32A (2P+E) input plug
- 18 total 230V outlets (2 C19, 16 C13)
- Reversible housing, 12.5 in. / 31.75cm depth



Description

Tripp Lite Metered Power Distribution Units / PDU systems continuously report output load level in amps to help network managers prevent overloads and plan for future growth. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. Highly reliable design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Applications

- Ideal for network configurations requiring a metered PDU

Package Includes

- 2U metered PDU
- Mounting brackets
- Plug retention brackets
- User manual

Features

- 32A single phase 230V Metered Power Distribution Unit / PDU
- Set of two lighted current meters separately report power consumption in amps for each output load bank
- Attached IEC-309 32A (2P+E) input plug with 12 ft. / 3.6m line cord
- 2U horizontal rackmount format installs in two rack spaces
- 18 total 230V outlets (2 C19, 16 C13)
- Outlets are arranged in two separately breakered and metered 16A load banks (each with 8 C13 and 1 C19 outlet)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Front-panel grounding lug
- Included cord retention brackets

Specifications

OVERVIEW	
PDU Type	Metered
OUTPUT	

Output kW capacity	7.36
Frequency compatibility	50 / 60 Hz
Output nominal voltage	230V
Overload protection	Outlets are arranged in two 16A banks of 9 outlets each (1 C19 / 8 C13); Each bank is protected by a separate circuit breaker
Outlet quantity / type	16 C13 and 2 C19 outlets
Outlet Type	IEC-C13, IEC-C19
INPUT	
Nominal Input Voltage(s) Supported	230V AC
PDU Input Voltage	230
Maximum Input Amps (A)	32
PDU Plug Type	IEC-309 32A BLUE (2P+E)
Input cord length (ft.)	12
Input cord length (m)	3.65
Voltage compatibility (VAC)	230
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Switches	n/a
PHYSICAL	
Shipping Dimensions (HWD/in)	5.5 x 20.5 x 17
Shipping Dimensions (HWD/cm)	14 x 113 x 80.6
Shipping weight (lbs)	16.2
Shipping weight (kg)	7.4
Unit Dimensions (HWD/in)	3.5 x 17.5 x 12.5
Unit Dimensions (HWD/cm)	8.9 x 44.5 x 31.75
Unit weight (lbs)	13.7
Unit weight (kg)	6.2
Material of construction	Steel
Style	Rackmount
Form factors supported	2U rackmount
PDU Form Factor	Horizontal (1U, 2U, etc)
ENVIRONMENTAL	
Relative Humidity	0-95% non-condensing
CERTIFICATIONS	
Certifications	Tested to CE (IEC 60950-1), UL, CSA, Class A, RoHS compliant

WARRANTY**Product Warranty Period
(Worldwide)**

2-year limited warranty

Related Items**Optional Products**

Related Model	Description	Qty.
P004-002-5	5-Pack of 2-ft. 18AWG Power cord (IEC-320-C14 to IEC-320-C13)	1
P005-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
P005-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
P005-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
P004-002-13RA	AC Power Extension Cable - C13 Right Angle to C14 - 2 ft.	1
P004-004	4-ft. 18AWG Power cord (IEC-320-C14 to IEC-320-C13)	1
P004-006	6-ft. 18AWG Power cord (IEC-320-C14 to IEC-320-C13)	1
P004-006-2C13	6-ft. AC Power Extension Splitter Cable (C14 to 2 x C13)	1
P047-002	2-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
P047-004	4-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
P047-006	6-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
P047-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
P036-002	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
P036-006	6-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
P036-002-19LA	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 Left Angle to IEC-320-C20)	1
P036-002-19RA	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 Right Angle to IEC-320-C20)	1
P032-002-2C13	2-ft. AC Power Splitter Cable (C20 to 2 x C13)	1
P036-006-2C19	6-ft. AC Power Splitter Cable (C20 to 2 x C19)	1
P036-002-20LA	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20 Left Angle)	1
P036-002-20RA	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20 Right Angle)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4812.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.