



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUB30

**Single-Phase Hot-Swap PDU, 30A 120V, 2U Horizontal Rackmount, 6 NEMA 5-15/20R and 1 NEMA L5-30R outlets, 2 NEMA L5-30P inputs**

### Highlights

- Single phase 30A 120V Hot-swap PDU
- Enables live replacement of a standard UPS with zero downtime
- 2U horizontal rackmount installation
- Compatible with any UPS with a L5-30P input plug
- Manual transfer switch controls PDU input power source
- Pair of L5-30P input cables connect to separate Utility and UPS inputs
- 7 outlets (6 5-15/20 & 1 L5-30R)



### Description

Tripp Lite's Hot-swap PDU systems enable live-replacement of standard UPS systems for maintenance with no interruption of connected server or networking loads. Dual input power cables support PDU connection to separate Utility and UPS power sources. Manual transfer switch with lighted status indicators controls the source of power to connected equipment between Utility and UPS. Set the switch to UPS during normal operation and connected equipment will receive full-time conditioned power from the UPS. Set the switch to Utility to momentarily power connected equipment from the Utility line cord and bypass the UPS while the UPS system is removed and replaced with a fresh one. Once the new UPS is up and running with all data and electrical connections restored, set the switch back to the UPS setting to once again provide fully-conditioned UPS power to connected equipment.

#### Applications

Hot-swap PDUs are ideal to install along with standard UPS systems to ensure that connected networking equipment will see no power interruption as the UPS is serviced, replaced or upgraded

#### Package Includes

- Hot-swap PDU System
- 2U mounting brackets
- User manual with warranty information

### Features

- Tripp Lite Hot-swap PDU systems support live-replacement of standard UPS systems for maintenance with no interruption of connected server or networking loads
- PDUB30 is universally compatible with any Tripp Lite or other brand of 100-127V UPS rated up to 3000VA or 2880 watts with a NEMA L5-30P input cable
- 2U horizontal rackmount form factor compatible with 2 or 4 post racks
- Supports space saving rear-post mounting in the same rack space as many Tripp Lite Rackmount UPS systems (select installations, see manual)
- Pair of attached L5-30P PDU input cables connect to separate Utility and UPS power sources
- 6 5-15/20R and 1 L5-30R outlets support critical networking loads in both Utility and UPS operating modes
- One additional L5-30R pass-through outlet supports UPS input power cord
- Dual input power cables support PDU connection to separate Utility and UPS power sources
- Manual transfer switch with lighted status indicators controls the source of power to connected equipment between Utility and UPS
- Set the switch to UPS during normal operation and connected equipment will receive full-time conditioned power from the UPS
- Set the switch to Utility to bypass the UPS and provide connected equipment with unfiltered power directly from the Utility line cord while the

UPS system is removed and replaced with a fresh one

- Once the new UPS is up and running with all connections restored, set the switch back to the UPS setting to once again provide fully-conditioned UPS power to connected equipment

## Specifications

OVERVIEW	
PDU Type	Hot-Swap
OUTPUT	
Output Watt Capacity (watts)	2880
Frequency compatibility	50 / 60 Hz
Output nominal voltage	100V, 120V, 127V
Outlet quantity / type	6 NEMA 5-15/20R and 1 L5-30R outlets support critical connected loads; 1 designated pass-through L5-30R outlet supports UPS L5-30P input plug
Outlet Type	NEMA 5-15/20R, L5-30R
INPUT	
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC
PDU Input Voltage	100; 120; 127
Maximum Input Amps (A)	24
PDU Plug Type	NEMA L5-30P
Input cord length details	Utility input cable (10 ft / 3m) / UPS input cable (6 ft / 1.8m)
Voltage compatibility (VAC)	100-127
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Switches	Manual 2 position transfer switch offers fast switching between UPS and Utility operating modes in less than 6 milliseconds
Front panel LEDs	Lighted indicators confirm UPS and Utility switch position and operating mode
PHYSICAL	
Shipping Dimensions (HWD/in)	9.25 x 20.23 x 6.1
Shipping Dimensions (HWD/cm)	23.5 x 51.4 x 15.5
Shipping weight (lbs)	11
Shipping weight (kg)	5
Unit Dimensions (HWD/in)	3.42 x 17.32 x 3.03
Unit Dimensions (HWD/cm)	8.7 x 44 x 7.7
Unit weight (lbs)	7.7
Unit weight (kg)	3.5

Material of construction	Steel
Style	Rackmount
Form factors supported	2U rackmount in 2 or 4 post racks
PDU Form Factor	Horizontal (1U, 2U, etc)
<b>ENVIRONMENTAL</b>	
Relative Humidity	0-95% non condensing
<b>CERTIFICATIONS</b>	
Certifications	Tested to UL60950 (USA), CSA (Canada)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

### Related Items

#### Optional Products

Related Model	Description	Qty.
<a href="#">P006-006-13LA</a>	6-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13 Left Angle)	1
<a href="#">P006-006-13RA</a>	6-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13 Right Angle)	1
<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
<a href="#">P044-06I</a>	6-inch 12AWG Heavy Duty Power Adapter cord (NEMA-L5-20R to NEMA-5-20P)	1
<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
<a href="#">P030-002-5</a>	5-Pack of 2-ft. 18AWG Power Cords NEMA 5-15P to IEC-320-C13)	1
<a href="#">P006-003</a>	3-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
<a href="#">P006-004</a>	4-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
<a href="#">P006-004-BL</a>	4-ft. 18AWG Power Cord (NEMA 5-15P to IEC-320-C13) with Blue Connectors	1
<a href="#">P006-004-GN</a>	4-ft. 18AWG Power Cord (NEMA 5-15P to IEC-320-C13) with Green Connectors	1
<a href="#">P006-004-RD</a>	4-ft. 18AWG Power Cord (NEMA 5-15P to IEC-320-C13) with Red Connectors	1
<a href="#">P006-004-YW</a>	4-ft. 18AWG Power Cord (NEMA 5-15P to IEC-320-C13) with Yellow Connectors	1
<a href="#">P006-006</a>	6-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
<a href="#">P006-006-2</a>	6-ft. AC Power Splitter Cable (NEMA 5-15P to 2 x IEC-320-C13)	1
<a href="#">P006-006-515MF</a>	6 ft. Piggyback Power Cord (NEMA 5-15P/R to IEC-320-C13 )	1
<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord ( IEC-320-C19 to NEMA 5-15P)	1
<a href="#">P006-010</a>	10-ft. 18AWG Power cord ( NEMA 5-15P to IEC-320-C13)	1
<a href="#">P049-010</a>	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	1
<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4467](http://www.tripplite.com/en/products/model.cfm?txtModelID=4467).

---

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.