



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPDM11

### Corded UPS Backplate Outlet Kit - Adds AC plug-in connection and AC output receptacle to SU6000RT3UHV UPS

#### Highlights

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system from hardware in/out to one with an AC plug and outlets
- 10 ft. / 3m AC input cord with NEMA L6-30P plug
- 2 NEMA L6-30R output receptacle
- Easy quick-connect wiring installs in minutes



#### Description

Tripp Lite's SUPDM11 corded backplate kit converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet. 10 ft./3m input line cord with L6-30P plug enables connection to 200/208/240V 30A mains power. Two L6-30R output receptacles allow for the connection of high current equipment load or power distribution units (PDU). Easy quick-connect wiring installs in minutes.

#### Applications

- Ideal for applications calling for Tripp Lite's SU6000RT3UHV where plug-in AC input and output connections are required

#### Features

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Two L6-30R output receptacles pass 200/208/240V output voltage on to connected equipment
- Easy quick-connect wiring installs in minutes

#### Specifications

| OVERVIEW                    |               |
|-----------------------------|---------------|
| Model Type                  | Outlet Kits   |
| OUTPUT                      |               |
| Output nominal voltage      | 200/208/240V  |
| Outlet quantity / type      | 1 NEMA L6-30R |
| INPUT                       |               |
| UPS Input cord length (ft.) | 10            |
| UPS Input cord length (m)   | 3.05          |

|                                            |                         |
|--------------------------------------------|-------------------------|
| <b>Recommended Electrical Service</b>      | 30A 200/208/240V        |
| <b>Input connection type</b>               | NEMA L6-30P             |
| <b>PHYSICAL</b>                            |                         |
| <b>Shipping Dimensions (HWD/in)</b>        | 5.5 x 9 x 14.25         |
| <b>Shipping Dimensions (HWD/cm)</b>        | 14 x 22.9 x 36.2        |
| <b>Shipping weight (lbs)</b>               | 4.7                     |
| <b>Shipping weight (kg)</b>                | 2.2                     |
| <b>Unit Dimensions (HWD/in)</b>            | 3 x 3.75 x 4.75         |
| <b>Unit Dimensions (HWD/cm)</b>            | 7.6 x 9.5 x 12.1        |
| <b>Unit weight (lbs)</b>                   | 4                       |
| <b>Unit weight (kg)</b>                    | 1.8                     |
| <b>Material of construction</b>            | Steel                   |
| <b>WARRANTY</b>                            |                         |
| <b>Product Warranty Period (Worldwide)</b> | 2-year limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2776](http://www.tripplite.com/en/products/model.cfm?txtModelID=2776).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.