



Model #: RELAYIOMINI

3 Relay I/O Mini-module



Highlights

- Internal contact closure management accessory card
- Three relay output contacts
- Input signal to shutdown UPS

Description

Tripp Lite's RELAYIOMINI allows users to communicate UPS status and events via three contact closure outputs. Installs in the back panel of compatible power modules on select SmartOnline UPS systems only. Requires removal of USB module to install.

NOTE: Compatible with Smart Online UPS systems specifying the use of this accessory from 5 to 20kVA originally shipping with pre installed back panel USB module AND dedicated RS232 DB9 port (Compatible models: SU5000RT4UHV, SU5000RT4UTF, SU6000RT4UHVG, SU6000RT4UHVHW, SU6000RT4UHFHW, SU8000RT3U, SU8000RT3UG, SU8000RT3UHW, SU8000RT3U1TF, SU8000RT3UN50, SU8000RT3UN50TF, SU10000RT3U, SU10000RT3UG, SU10KRT3U, SU10KRT3UHV, SU10000RT3U2TF, SU12KRT4UHW, SU16KRT, SU16KRT-1TF, SU16KRTG, SU16KRTHW, SU20KRT, SU20KRT-1TF, SU20KRTG, SU20KRTHW)

Applications

• Ideal solution for PCs, servers, datacenters, VoIP/telecom/industrial and other mission-critical equipment that requires power management, monitoring and control.

Package Includes

- RELAYIOMINI
- Owner's Manual

Features

- Makes select SmartOnline Tripp Lite UPS capable of providing contact closure output communications
- 3 relay output contacts

Specifications

OVERVIEW	
Model Type	Hardware
PHYSICAL	

Shipping Dimensions (HWD/in)	1.6 x 6 x 6
Shipping Dimensions (HWD/cm)	4.1 x 15.2 x 15.2
Shipping weight (lbs)	.5
Shipping weight (kg)	.2
Unit Dimensions (HWD/in)	.9 x 2.4 x 2.8
Unit Dimensions (HWD/cm)	2.3 x 6.1 x 7.1
Unit weight (lbs)	.08
Unit weight (kg)	.04
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4618.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.