

Model #: SUPDMB568HW

SUPDMB568HW - UPS Accessory - Hardwire PDU Module



Highlights

- Converts compatible SmartOnline Hot-Swappable Modular UPS systems to hardwire input and output
- For use with input voltages of 120/208 or 120/240 VAC split-phase power
- Convenient quick-disconnect terminal block allows installation in minutes
- Manual bypass switch eliminates equipment downtime

Description

The SUPDMB568HW hardwire input/output PDU module converts compatible SmartOnline Hot-Swappable Modular UPS Systems (models SU5000RT4U, SU6000RT4U, and SU8000RT4U) to a totally hardwired solution. Easy quick-connect terminal block allows installation of hardwire distribution module in minutes. Can accept input voltages of 120/208 or 120/240 VAC split-phase power. Detachable hardwire module with manual bypass switch allows for effortless UPS maintenance without the need to power down connected loads and re-wire input/output connections.

Applications

• Use with Tripp Lite SU5000RT4U, SU6000RT4U, and SU8000RT4U UPS systems in 120, 208/240V applications where hardwire input/output connections are required

System Requirements

• Use with SU5000RT4U, SU6000RT4U, and SU8000RT4U split-phase SmartOnline Hot-Swappable Modular UPS Systems

Package Includes

- SUPDMB568HW hardwire PDU
- Mounting Hardware
- Owner's Manual

Specifications

OVERVIEW		
Model Type	PDU Modules	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output nominal voltage	120/208, 120/240	
Outlet quantity / type	Split-phase hardwire (4-wire)	
INPUT		

Input connection type Split-phase hardwire (4-wire) Voltage compatibility (VAC) 100-140 PHYSICAL Shipping Dimensions (HWD/in) 9.5 x 20.5 x 9.75 Shipping Dimensions (HWD/cm) 24.1 x 52.1 x 24.8 Shipping weight (lbs) 14 Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS Certifications Tested to UL 1778 (USA), CSA (Canada), RoHS compliant	Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC; 140V AC	
PHYSICAL Shipping Dimensions (HWD/in) 9.5 x 20.5 x 9.75 Shipping Dimensions (HWD/cm) 24.1 x 52.1 x 24.8 Shipping weight (lbs) 14 Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Input connection type	Split-phase hardwire (4-wire)	
Shipping Dimensions (HWD/in) 9.5 x 20.5 x 9.75 Shipping Dimensions (HWD/cm) 24.1 x 52.1 x 24.8 Shipping weight (lbs) 14 Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Voltage compatibility (VAC)	100-140	
Khipping Dimensions (HWD/cm) 24.1 x 52.1 x 24.8 Shipping weight (Ibs) 14 Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	PHYSICAL		
(HWD/cm) 14 Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS		9.5 x 20.5 x 9.75	
Shipping weight (kg) 6.3 Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS		24.1 x 52.1 x 24.8	
Unit Dimensions (HWD/in) 6 x 17.5 x 6.75 Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Shipping weight (lbs)	14	
Unit Dimensions (HWD/cm) 15.24 x 44.45 x 17.1 Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Shipping weight (kg)	6.3	
Unit weight (lbs) 11.7 Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Unit Dimensions (HWD/in)	6 x 17.5 x 6.75	
Unit weight (kg) 5.3 Material of construction Steel SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Unit Dimensions (HWD/cm)	15.24 x 44.45 x 17.1	
Material of construction SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Unit weight (lbs)	11.7	
SPECIAL FEATURES Appearance All-black color scheme CERTIFICATIONS	Unit weight (kg)	5.3	
Appearance All-black color scheme CERTIFICATIONS	Material of construction	Steel	
CERTIFICATIONS	SPECIAL FEATURES		
	Appearance	All-black color scheme	
Certifications Tested to UL1778 (USA), CSA (Canada), RoHS compliant	CERTIFICATIONS		
	Certifications	Tested to UL1778 (USA), CSA (Canada), RoHS compliant	
WARRANTY			
Product Warranty Period (Worldwide) 2-year limited warranty		2-year limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4188.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.