



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: B118-302-R

### HDMI Splitter, 2-Port



### Highlights

- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p
- HDCP compliant
- Connects to both HDMI and DVI-D Single-Link displays
- ATC certified
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Description

Tripp Lite's HDMI Splitter allows the digital signal from a Blu-Ray player or other HDMI device, to be displayed on multiple HDMI or DVI-D Single Link monitors. Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p. Up to 32 displays can be connected by cascading up to three levels of additional splitters. Locate a monitor up to 41 ft. (12.5 m.) from a HDMI source; up to 16 ft. (5 m.) between the source and the splitter; up to 25 ft. (7.62 m.) between the splitter and a monitor. Splitters can be located up to 100 ft. away from the source using a combination of Tripp Lite long length HDMI cables ( P568-050, P568-100-HD ) and a HDMI Signal Booster ( [B122-000-60](#) or [B123-001-60](#)). Includes mounting hardware that allows the unit to be wallmounted, rackmounted or pole mounted. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

#### Applications

Retail, Classroom, Movie Theaters...anywhere a HD signal needs to be broadcast to multiple digital displays

#### System Requirements

- TV's with an available HDMI port and a HDMI peripheral device (e.g. Blu-Ray player, DVR, etc.)
- The cable connecting the HDMI source to the splitter must be no longer than 16 ft. (5 m.), unless using a signal booster ([B122-000-60](#) or [B123-001-60](#))
- The cable connecting the splitter to a HDMI monitor must be no longer than 25 ft. (7.62 m.)

#### Package Includes

- B118-302-R 2-Port HDMI Splitter
- 1 ft. HDMI cable
- Mounting hardware
- External Power Supply (Input: 100-240V, 50/60Hz, 0.4A Output: 5V, 2A)
- Owner's Manual

### Features

- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p.
- HDCP compliant
- Supports 3D, Lip-Sync Pass Through, and CEC Pass Through
- Connects to both HDMI and DVI-D Single-Link displays
- Cascade up to three levels of splitters to support up to 32 displays
- Includes mounting hardware that allows the unit to be wallmounted, rackmounted, or pole mounted
- Locate a monitor up to 41 ft. (12.5 m.) from a HDMI source; up to 16 ft. (5 m.) between the source and the switch; up to 25 ft. (7.62 m.) between the switch and a monitor

- ATC certified
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

OVERVIEW	
Display Style	Splitter
Model Type	HDMI Splitters
CONNECTIONS	
Connector A	 HDMI (FEMALE)
Connector B	 (X2) HDMI (FEMALE)
Number of Connectors	3
Ports	2
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">B118-304-R</a>	HDMI Splitter, Ver 1.3b, 4-Port	1
<a href="#">P568-006</a>	6-ft. HDMI Gold Digital Video Cable (HDMI M/M)	1
<a href="#">P568-006-FL</a>	6-ft. Flat HDMI Gold Cable (HDMI M/M)	1
<a href="#">P568-006-RA2</a>	6-ft. HDMI Gold Right-angled Digital Video Cable (HDMI-RA M/M)	1
<a href="#">P568-006-SW</a>	6-ft. HDMI Gold Cable with Swivel Connectors (HDMI M/M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4032](http://www.tripplite.com/en/products/model.cfm?txtModelID=4032).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.