



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: B116-004A

DVI + Audio Splitter, 4-Port



Highlights

- Transmits a DVI-D Single Link video signal and 3.5mm audio signal to four sets of DVI monitors and speakers
- Supports DVI Single Link computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p.
- Built-in signal booster extends the distance between the splitter and connected monitors past the 16 ft. (5 m.) distance limitation
- Expand the number of connected monitors/speakers by cascading up to 3 levels of splitters together
- Supports HDCP, EDID and DDC
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

With Tripp Lite's 4-Port DVI + Audio Splitter, you can transmit a DVI-D Single Link video signal and 3.5 mm. audio signal to four sets of monitors and speakers. Supports DVI Single Link computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p. The unit is HDCP, EDID, and DDC compatible. A built-in signal booster allows you to extend the distance between the splitter and connected monitors past the 16 ft. (5 m.) distance limitation.

For source video resolutions anywhere from 1600 x 1200 @ 60Hz to 1920 x 1200 @ 60Hz - The distance between the splitter and the connected monitor/speakers must not exceed 49 ft. (15 m.). This distance can be extended by using a [B120-000-SL](#) DVI extender. The B120-000-SL can be located up to 65 ft. (20 m.) from the splitter, and 16 ft. (5 m.) from the connected monitor.

For source video resolutions lower than 1600 x 1200 @ 60Hz - The distance between the splitter and the connected monitor/speakers must not exceed 65 ft. (20 m.). This distance can be extended by using a [B120-000-SL](#) DVI extender. The B120-000-SL can be located up to 114 ft. (35 m.) from the splitter, and 16 ft. (5 m.) from the connected monitor.

The number of connected monitors/speakers can be expanded by cascading up to three levels of splitters. Plug and Play...no software or drivers required. Mounting hardware is included with the product, and allows it to be rackmounted, wallmounted or pole-mounted. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Applications

- Use where DVI-D Single Link video and 3.5 mm. audio signals need to be displayed on multiple sets of monitors/speakers

System Requirements


- Video graphics card with a DVI-D or DVI-I connector
- Monitors with a DVI-D or DVI-I connector
- Speakers and/or monitor with a 3.5 mm. audio connector

Package Includes

- B116-004A
- Mounting Hardware
- External Power Supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Owner's Manual

Specifications

OVERVIEW	
Display Style	Splitter; Signal Booster

PHYSICAL	
Unit Dimensions (HWD/in)	1.7 x 7.9 x 3.2
Unit Dimensions (HWD/cm)	4.3 x 20.1 x 8.1
Unit weight (lbs)	1.2
Unit weight (kg)	0.54
CONNECTIONS	
Connector A	 (X5) DVI-I (FEMALE)
Connector B	 (X5) 3.5MM (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
B110-INT	International AC Adapter for Tripp Lite Video over CAT5 Extenders	1
B116-002A	DVI Single Link Video / Audio Splitter/Booster, 2-Port	1
P560-006-A	6-ft. DVI Dual Link TDMS + Audio Cable (DVI-D M/M, 3.5mm M/M)	1
P560-010-A	10-ft. DVI Dual Link TDMS + Audio Cable (DVI-D M/M, 3.5mm M/M)	1
P561-006	6-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
P561-010	10-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
P312-006	6-ft. Mini-Stereo Dubbing Cord (3.5mm M/M)	1
P312-010	10-ft. Mini-Stereo Dubbing Cord (3.5mm M/M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4608.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.