



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: 0SU52015

Minicom Universal Phantom Manager - Distributed Cat5 KVM Switch

Highlights



- Single user control of up to 63 servers on a single line
- Advanced OSD management and multi-layered security
- Pure hardware solution - BIOS level access
- Scalable - buy only what you need and add as you grow
- Flexible server/KVM console placement up to 110m/360ft away
- No external power supply at Specter units
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

The Universal Phantom Manager, the first ever distributed micro-sized KVM switch, is specially designed for single user KVM management of up to 63 servers on a single line making it the ideal solution for high density server and rack environments like server farms, data centers or corporate server rooms.

The micro-sized Specter provides much more power than a conventional switch by freeing up rack space, eliminating cable clutter and maximizing your flexibility.

Advanced Management and Security Options

The Universal Phantom Manager features advanced On Screen Display (OSD) management, including multi-layered security, the most efficient way for monitoring, accessing and controlling your servers.

You can also manage your Phantom system via a serial port, using the Phantom's Control Software or any other third party software.

Less Switch Space Means More Server Space

Phantom's Distributed Switching Technology (DST) divides the KVM switch into smaller subunits: a Manager and multiple Remote units. The Remote units can be placed on the side or back of the rack where they occupy no rack space! Now you can dedicate more of your rack to servers instead of wasting space on switches.

Components

The Universal Phantom Manager system consists of two separate units:

- 1 Universal Phantom Manager (UPM) unit per system
- 1 Remote unit (Phantom Specter II USB or PS/2) per computer up to 63 per line

System Requirements

Operating System

- DOS, Windows (3x, 9x, 2000, NT4, ME, XP and later), LINUX, UNIX, HP UX, QNX, SGI, FreeBSD, BeOS, Open VMS, Novell 3.12 - 6, SUN Solaris

Console

- VGA Monitor
- PS/2 Keyboard and Mouse

Resolution

- Supports video resolutions up to 1600 x 1200 @ 75Hz

Package Includes

- 0SU51011
- 3 in 1 KVM Cable Kit
- RJ11 to DB9 Firmware Upgrade Cable
- Power Cord
- Owner's Manual

Features

- Single user control of up to 63 servers on a single line
- Advanced OSD management and multi-layered security
- Pure hardware solution - BIOS level access
- Scalable - buy only what you need and add as you grow
- Flexible server/KVM console placement up to 110m/360ft away
- No external power supply at Specter units
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
# Of Users	1
Console	No
Port Control	Hotkeys, OSD
PC/Server	VGA; USB; PS/2
Cat5 KVM Switch	Yes
IP Remote Access	YES WITH B051-000
Model Type	KVM Switches
UPC ASSIGNMENT	
Unit Carton UPC#	654518201819
PHYSICAL	
Unit Dimensions (HWD/in)	1.6 X 7.1 X 8
Unit Dimensions (HWD/cm)	4.15 X 18 X 20.4
Unit weight (lbs)	2.2
Unit weight (kg)	1
Color	White
Style	Desktop
ENVIRONMENTAL	
Storage Temperature Range	-40 to 40 C (-40 to 104 F)
Operating Temperature	0 to 40 C (32 to 104 F)
CONNECTIONS	
Ports	1
WARRANTY	

Product Warranty Period (Worldwide)	3-year limited warranty
--	-------------------------

Related Items

Required Products

Related Model	Description	Qty.
0SU51011	Minicom Specter II USB - Remote Unit for Phantom KVM Installation	1
0SU51012	Minicom Specter II PS/2 - Remote Unit for Phantom KVM Installation	1
0SU51060	Minicom Specter II PS/2 (8 Pack) - Remote Unit for Phantom Specter	1
N001-007-BK	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N001-014-BK	14-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N001-025-BK	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N201-007-BK	7-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-014-BK	14-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-025-BK	25-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1

Optional Products

Related Model	Description	Qty.
0SU52016	Minicom Phantom MXII - Multi-User Unit for Universal Phantom Manager	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5241.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.