



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B140-101-WP

DVI over Cat5 Passive Extender Wallplate Kit

Highlights



- Extender kit comes with transmitter and receiver units
- Supports DVI-D Single-Link video resolutions up to 1920 x 1080 @ 60Hz
- Extends a 1920 x 1080 @ 60Hz signal up to 50 ft., or a 1024 x 768 @ 60Hz signal up to 100 ft.
- Use 24AWG, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N202-Series](#), to achieve maximum distance and resolution
- Compatible with all operating systems
- Plug and play, no external power, software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

The B140-101-WP is a DVI over Cat5 Passive Extender Wallplate kit, which comes with both transmitter and receiver units. It transmits a DVI-D Single-Link signal up to 100 ft. away using a single Cat5e/6 patch cable. To achieve maximum distance and resolution, use 24AWG Solid Wire Cat5e/6 cable (Tripp Lite's [N202-Series](#)). The B140-101-WP is compatible with all operating systems, and is plug and play, with no external power, software or drivers required. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Installation is simple. Connect the transmitter unit to a DVI source using a Tripp Lite [P561-Series](#) DVI cable (not included). Connect the receiver unit to a display using a Tripp Lite [P561-Series](#) DVI cable (not included). Finally, the 110 punchdown jacks on the transmitter and receiver units are connected using a single Cat5e/6 cable. A 1920 x 1080 @ 60Hz signal can be extended up to 50 ft. from the source, or a 1024 x 768 @ 60Hz signal up to 100 ft..

Package Includes


- B140-101-WP local wallplate
- B140-101-WP remote wallplate
- 110 punchdown tool
- Wallplate screws
- Owner's manual

Features

- Extender kit comes with transmitter and receiver units
- Transmit a DVI-D Single-Link signal up to 100 ft. away using a single Cat5e/6 patch cable
- Supports DVI-D Single-Link video resolutions up to 1920 x 1080 @ 60Hz
- Extends a 1920 x 1080 @ 60Hz signal up to 50 ft., or a 1024 x 768 @ 60Hz signal up to 100 ft.
- Use 24AWG, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N202-Series](#), to achieve maximum distance and resolution
- HDCP compatible
- Compatible with all operating systems
- Plug and play; no external power, software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Specifications

OVERVIEW	
Cable Type	DVI

Display Style	Extender
LEDS ALARMS & SWITCHES	
LED Indicators	The LED on the local unit illuminates to indicate it is connected to, and receiving power from, the source. The LED on the remote unit illuminates to indicate it is connected to, and receiving power from, the monitor.
PHYSICAL	
Color	White
CONNECTIONS	
Connector A	 (X2) DVI-I (FEMALE)
Connector B	 (X2) 110 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Recommended Products

Related Model	Description	Qty.
N046-000	110/66 Punch Down Installation Tool for Cat6a/Cat6/Cat5e/Cat5/Network Cable	1
N022-01K-GY	1000-ft. Cat5e 350MHz Bulk Solid-core PVC Cable - Gray	1
N222-01K-GY	1000-ft. Cat6 Gigabit Bulk Solid PVC Cable - Gray	1

Optional Products

Related Model	Description	Qty.
N202-025-BL	25-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-050-BL	50-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-075-BL	75-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-100-BL	100-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
P561-006	6-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
P561-010	10-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
B140-101	DVI Over CAT5 2pc Extender Kit	1
B140-101X	DVI Over CAT5 2pc Super - Extender Kit up to 200ft	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4458.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.