



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B132-004-1

VGA over Cat5 Extender 4-Port Transmitter

Highlights

- Splits a single VGA signal into 5 (1 local, 4 remote)
- Extends a 1920 x 1440 (60Hz) signal up to 500 ft., or a 1024 x 768 (60Hz) signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#) (Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases



Description

Tripp Lite's B132-004-1 allows you to split a single VGA signal into 5 (1 local, 4 remote). Increase the number of displays to up to 25 (1 local, 24 remote) by daisy-chaining up to six B132-004-1 units together. Along with a [B132-100-1](#) or [B132-100-WP-1](#) remote receiver unit, you can extend a 1920 x 1440 (60Hz) signal up to 500 ft., or a 1024 x 768 (60Hz) signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#) (Cat5) and [N222-01K-GY](#) (Cat6). For optimal video image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#). Includes mounting hardware that allows unit to be wallmounted, rackmounted or pole mounted. Up to three B132-004-1 units can be mounted in 1U of rack space using a Tripp Lite B132-004-RB Extender/Splitter 19 in. rackmount bracket. Ideal for digital signage situations, such as retail, schools, churches, etc.

Package Includes

- 4 Port Extender/Splitter local (Transmitter) unit
- 1 ft. VGA daisychain cable
- Mounting hardware
- External power supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Owner's Manual

Features

- Splits a single VGA signal into 5 (1 local, 4 remote)
- Increase the number of displays to up to 25 (1 local, 24 remote) by daisy-chaining up to six B132-004-1 units together
- A [B132-100-1](#) or [B132-100-WP-1](#) remote receiver unit is required for each connected monitor
- Extends a 1920 x 1440 (60Hz) signal up to 500 ft., or a 1024 x 768 (60Hz) signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#) (Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Includes mounting hardware that allows unit to be wallmounted, rackmounted or pole mounted
- Up to three B132-004-1 units can be mounted in 1U of rack space using a Tripp Lite B132-004-RB Extender/Splitter 19 in. rackmount bracket
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Cable Type	VGA

Display Style	Splitter
PHYSICAL	
Shipping weight (lbs)	1.8
Shipping weight (kg)	0.82
Unit Dimensions (HWD/in)	1.2 x 5.3 x 3.9
Unit Dimensions (HWD/cm)	3.05 x 13.46 x 9.91
Unit weight (lbs)	0.85
Unit weight (kg)	0.39
Color	Black
CONNECTIONS	
Connector A	CZA24 - (X2) HD15 (FEMALE)
Connector B	 (X4) RJ45 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Required Products

Related Model	Description	Qty.
B132-100-1	VGA over Cat5 Receiver	1
B132-100-WP-1	VGA over Cat5 Receiver - RJ45-type Wallplate	1

Recommended Products

Related Model	Description	Qty.
N202-050-BL	50-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-075-BL	75-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-100-BL	100-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-150-BL	150-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-200-BL	200-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N022-01K-GY	1000-ft. Cat5e 350MHz Bulk Solid-core PVC Cable - Gray	1
N222-01K-GY	1000-ft. Cat6 Gigabit Bulk Solid PVC Cable - Gray	1
P524-01K	1000-ft. Zero-Skew UTP Bulk Patch Cable for RGB Video	1
P502-006	6-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1
P502-010	10-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1
P502-015	15-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1

Optional Products

Related Model	Description	Qty.
---------------	-------------	------

B132-004-RB	19" Rack Mount Bracket (holds up to three Cat5 extender/splitter local units)	1
B132-002-2	VGA over Cat5 Extender 2-Port Transmitter	1
B130-101-2	VGA over Cat5 Extender Kit (Transmitter + Receiver)	1
B130-101-WP-1	VGA over Cat5 (RJ45 Type) Extender Wallplate Kit (Transmitter + Receiver)	1
B110-INT	International AC Adapter for Tripp Lite Video over CAT5 Extenders	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4876.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.