



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SRW12US33

SmartRack 12U Extended-Depth Wall-Mount Rack Enclosure Cabinet

Highlights



- 12U with adjustable front and rear vertical rackmount rails
- 33" depth accommodates most 1U servers and simplifies cable management
- Heavy duty construction supports the added leverage
- Hinged cabinet swings away from wall bracket for easy equipment access (swing direction is reversible)
- Locking, reversible front door and locking, removable side panels
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Description

The SRW12US33 12U Extended-Depth Wall-Mount Rack Enclosure Cabinet is designed to integrate wall-mounting, easy equipment access, and cable management in IT network applications with limited floor space. Extended depth to 33" accommodates most 1U servers and provides extra clearance for cable management. It has a heavy-duty steel construction to handle the added leverage. Ventilated front door and side panels allow generous airflow to keep equipment operating safely. Adjustable rack rails with square mounting holes accommodate up to 12U of standard 19" rackmount equipment. Supports up to 250lbs of equipment. A sturdy hinge between the cabinet and the wall-mount bracket allows the cabinet to swing away from the wall for easy access to equipment and cabling. Top and bottom panels include convenient cutouts for cable routing.

Package Includes

- SRW12US33 Wallmount Rack Enclosure
- (36) M6 screws
- (36) M6 cage nuts
- (36) M6 washers
- (2) Keys
- Owner's Manual

Features

- 12U wall-mounted enclosure
- Adjustable mounting depths from 3" to 33" - accommodates most 1U servers and simplifies cable management
- Ventilated front door and side panels for increased airflow
- Hinged cabinet swings away from wall bracket for easy equipment and cable access
- Heavy duty construction to handle added leverage
- Locking, reversible front door
- Locking, removable side panels
- Top and bottom panel cable access openings
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	32.5

Installed whole system maximum rack depth (cm)	82.55
Installed whole system minimum rack depth (inches)	3
Installed whole system minimum rack depth (cm)	7.62
Rack Height	12U
Shipping Dimensions (HWD/in)	37.8 x 26.9 x 25.6
Shipping Dimensions (HWD/cm)	96 x 68.32 x 65.02
Shipping weight (lbs)	120
Shipping weight (kg)	54.43
Unit Dimensions (in.)	EXTERNAL DIMENSIONS: 25 x 23.63 x 33.5
Unit weight (lbs)	100
Unit weight (kg)	45.36
Unit Dimensions (cm)	EXTERNAL DIMENSIONS: 63.5 x 60 x 85.09
Color	Black
Style	Wall Mounted
Weight Capacity - Stationary (lbs)	250
Weight Capacity - Stationary (kg)	113.4
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
SPECIAL FEATURES	
Grounding lug	Front and Back door frames
CERTIFICATIONS	
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	EIA-310-D, IEC 60297-3-100, DIN 41494, IP250 Protection Rating, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
N252-024	24-Port Cat6 Patch Panel 568B, 1U	1
N252-048	48-Port Cat6 Patch Panel 568B	1
SRCABLEDUCT1U	1U Horizontal Cable Manager (Finger duct with cover.)	1

SRCABLEDUCT1UHD	1U High Capacity Horizontal Cable Manager (Finger duct with dual-hinge cover)	1
SRCABLERING1U	1U Horizontal Cable Manager (Flexible ring type.)	1
SRCASTER	Heavy-Duty Rolling Caster Kit (Includes 4 casters. Casters are included with 48/42/25U enclosures.)	1
SRFAN3U	3U Fan Panel, 120V (3 high-performance fans; 210 CFM; 5-15P plug.)	1
SRFANWM	Wall-Mount Roof Fan Kit, 120V (2 high-performance fans; 5-15P plug)	1
SRXFAN3U	3U Fan Panel, 230V (3 high-performance fans; 210 CFM; C14 inlet.)	1
SR1UPANEL10	1U Blanking Panel Kit (10 pieces; toolless mounting.)	1
SR1UPANEL50	1U Blanking Panel Kit (50 pieces; toolless mounting.)	1
UPSHDEARKIT	Heavy-Duty Mounting Ear Kit - Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.)	1
SRCAGENUTS	Square Hole Hardware Kit (Includes 50 M6 screws and washers.)	1
SRSWITCH	Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE	1
SRCABLERING2U	2U Horizontal Cable Manager (Flexible ring type.)	1
SRCABLEDUCT2UHD	2U High Capacity Horizontal Cable Manager (Finger duct with dual-hinge cover)	1
SRSHELF2P1U	1U Cantilever Fixed Shelf (40 lb / 18 kg capacity; 12-in. / 305 mm depth.)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4644.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.