

Matrox Avio™ Series



Dual-DVI Fiber Optic KVM Extender Delivers Uncompromised Performance

Matrox Avio Series KVM extenders enable users to work off their computers from a distance, while maintaining real-time performance. Featuring a transmitter/receiver pair, Avio delivers uncompressed, zero-latency transmission of dual digital video, USB and audio signals from the host system by up to 4 km (2.5 mi) over a single duplex LC-LC fiber optic cable. Users benefit from exceptional graphics and smooth HD video playback, with no dropped frames, while all workstations remain in a climate controlled machine room for simple IT maintenance and security.

Key Features:

- 10Gbps SFP+ transceivers enable uncompressed video transmission at full frame rate across a single duplex LC-LC fiber optic cable
- Smooth HD, 2K, 4K video playback without dropping any frames
- Two Single-link DVI monitor or one Dual-link DVI display support
- USB HID ports for keyboard, mouse, touchscreens and other HID devices.
- USB 2.0 high-speed support for touchscreens, printers, scanners, hard drives, as well as isochronous USB 2.0 audio and video devices (available with Avio F125)
- Maximum distances of 400 m (1312 ft) in multimode and 4 km (2.5 mi) in single-mode ¹
- Digital-to-analog conversion enables support for 2x VGA monitors with a maximum resolution of 1920x1200 60Hz
- Analog stereo audio support to place audio devices such as speakers, microphones and headphones away from the system
- DDC compliance and advanced EDID management ensure a reliable communication between the system and the remote displays
- PS/2 keyboard and mouse support for industrial or legacy systems
- Local outputs on the Avio transmitter unit for easy maintenance or to share the remote desktop on a collaborative video wall
- Passive cooling (no fan) for silent operation and extra reliability
- On-screen Display (OSD) to view diagnostic information and access advanced configuration options
- Rack mountable or stand alone units
- Plug & play design for easy deployment with no software installation
- Compatibility with Microsoft® Windows®, Mac OS X®, Linux® and UNIX® operating systems
- Compatible with select layer one fiber optic network switches
- Global sales and technical support

¹ Matrox Avio SFP+ Single-Mode upgrade kit required (Part# AV-SFP10G-2SMF)



Matrox Avio Series Specifications

	Avio F120		Avio F125	
Product	Transmitter	Receiver	Transmitter	Receiver
Part Number	AV-F120TXF	AV-F120RXF	AV-F125TXF	AV-F125RXF
Connections to Host System				
Video Connector #1	1x DVI-D SL/DL	–	1x DVI-D SL/DL	–
Video Connector #2	1x DVI-D SL	–	1x DVI-D SL	–
USB HID Type Mini-B	2	–	3	–
USB 2.0 Type B	1	–	1	–
PS/2 Keyboard & Mouse	1 & 1	–	1 & 1	–
Line In & Line Out (3.5mm)	1 & 1	–	1 & 1	–
Connections to Local Devices				
Video Connector #1¹	1x DVI-I SL/DL	1x DVI-I SL/DL	1x DVI-I SL/DL	1x DVI-I SL/DL
Video Connector #2	1x DVI-I SL	1x DVI-I SL	1x DVI-I SL	1x DVI-I SL
Analog VGA²	2	2	2	2
USB HID Type A	2	4	2	2
USB 2.0 Type A	2	–	2	4
PS/2 Keyboard & Mouse	1 & 1	1 & 1	1 & 1	1 & 1
Mic In & Headphone out (3.5mm)	1 & 1	1 & 1	1 & 1	1 & 1
Line In & Line Out (3.5mm)	1 & 1	1 & 1	1 & 1	1 & 1
USB Type B (Debug Port)	–	1	–	1
Maximum Video Output Resolution				
DVI Single Link (SL)	2x 1920x1200 60Hz 2x 2048x1080 60Hz		2x 1920x1200 60Hz 2x 2048x1080 60Hz	
DVI Dual Link (DL)	1x 2560x1600 60Hz 1x 4096x2160 24Hz, 30Hz		1x 2560x1600 60Hz 1x 4096x2160 24Hz, 30Hz	
Analog VGA	2x 1920x1200 60Hz		2x 1920x1200 60Hz	
General				
Status LED Indicators	2	2	2	2
OSD Menu	Yes	Yes	Yes	Yes
Enclosure Dimensions	8.5"x1.65"x5.34"	8.5"x1.65"x5.34"	8.5"x1.65"x5.34"	8.5"x1.65"x5.34"
Standalone (S) or Rack-Mountable (R)	S/R	S/R	S/R	S/R
Power Supply Unit (PSU)	1x external 12V	1x external 12V	1x external 12V	1x external 12V
Cables Included³	2x DVI-D Cables, 1x USB A-B, 4x Power Cords	4x Power Cords	2x DVI-D Cables, 1x USB A-B, 2x 3.5mm Audio Stereo Cable, 4x Power Cords	4x Power Cords
Connection between Transmitter and Receiver units⁴				
LC Connectors	2		2	
Maximum Distance in Multimode (MM)	400 m (1312 ft) - OM3, OM4 multi-mode 50/125 µm / 82 m (269 ft) - OM2 multi-mode 50/125µm 33 m (108 ft) - OM1 multi-mode 62.5/125µm			
Maximum Distance in Single-Mode (SM)	4 km (2.5 mi) - OS1, OS2 single-mode 9/125 µm			

¹ In Dual-link DVI mode, only a single display is supported.

² Matrox DVI-to-VGA adapter required (part number ADP-DVI-AF)

³ 6 foot long cables; power cords for North America/Japan, UK, Australia/China, Continental Europe/China

⁴ Matrox Avio Transmitter and Receiver units include the multi-mode transceivers. Single-mode transceivers are sold separately as an upgrade kit.

Learn More or Purchase

North America: 800-361-1408

International: 514-822-6366

Email: graphics@matrox.com

© 2013 Matrox Graphics, Inc. All rights reserved. Matrox reserves the right to change specifications without notice. Matrox and Matrox product names are registered trademarks in Canada or other countries and/or trademarks of Matrox Electronic Systems, Ltd and/or Matrox Graphics Inc. All other company and product names are registered trademarks and/or trademarks of their respective owners.

March 2013

matrox[®]
Graphics for Professionals