

## AT-6102G

### Universal Multi-voltage Gigabit PoE Splitter



#### AT-6102G

Universal multi-voltage Gigabit PoE splitter

#### IEEE 802.3af Power over Ethernet Splitter

The AT-6102G multi-voltage Power over Ethernet splitter allows PoE remote powering of virtually any equipment. Non PoE enabled devices like access points, IP cameras, VoIP phones, etc. can be connected to PoE powered lines with all the benefits of PoE remote powering.

#### Main Applications

Sensible cost savings can be achieved using the AT-6102G multi-voltage PoE splitter for remotely powering virtually any VoIP phones, IP cameras and wireless access points.

There is no need for additional power cabling since the AT-6102G feeds the devices with power received through the PoE connection. Connecting the AT-6102G multi-voltage Power over Ethernet splitter to a UPS protected power line easily protects the powered device from power outages.

The AT-6102G multi-voltage PoE splitter helps in protecting network investments. In fact there's no need to replace the existing device with a PoE enabled one. Simply replace the original power supply with the AT-6102G and set the desired output voltage through the DIP switch.

#### Power over Gigabit Ethernet

The AT-6102G allows you to remotely power any high performance equipment that needs Gigabit Ethernet connection.

High definition cameras and high-speed wireless access points can be freely positioned without any need for additional power cabling.

#### Key Features

- IEEE 802.3af compliant
- Can feed power to Gigabit Ethernet equipments
- Short circuit protection
- Delivering power and data to equipment
- 5, 7.5, 9 and 12V user selectable output voltage
- Plug-and-Play
- Light weight and compact size
- Easy table top and wall-mounting
- Self-sticking velcro strips for attaching to powered device
- For wireless access points, Bluetooth AP, IP camera, VoIP telephones and any other remote power feeding application
- Regulated output voltage
- RoHS and WEEE compliant
- CE, FCC, GOST, C-Tick approved
- UL listed

# AT-6102G | Universal Multi-voltage Gigabit PoE Splitter

## Technical Specifications

### Physical Characteristics

Dimensions 8cm x 5.5cm x 2.6cm  
(W x D x H):  
Weight: 80g (0.18 lbs)

### Status Indicators (LEDs)

Power on

### Power Characteristics

Input power: 48vDC PoE  
Output power: 5, 7.5, 9, 12vDC

Max output  
current: 2.0A @ 5V

## Environmental Specifications

### Operating Conditions

Max temperature: 0°C to 40°C (32°F to 104°F)  
Relative humidity: 10% to 90% (non-condensing)

### Storage Conditions

Max temperature: 0°C to 70°C (32°F to 158°F)  
Relative humidity: 8% to 90% (non-condensing)

### Robustness

MTBF: > 180,000 hrs

## Interfaces

### Data In

LAN: 10/100TX RJ-45 female  
Cable: EIA/TIA-568 100-ohm (100m)  
10T: 2 or 4-pair UTP/STP Cat.3, 4, 5  
100TX: 2 or 4-pair UTP/STP Cat.5  
1000T: 4-pair UTP/STP Cat.5

Power drain: V+ on pins 4 and 5; 1 and 2  
V- on pins 7 and 8; 3 and 6

### Data Out

LAN: 10/100/1000T RJ-45 female

### DC Power Out

Connector: 5.5 x 2.0mm and 5.5 x 2.5mm  
User selectable power jacks  
Cable length: 360mm (1.42 inches)

## Regulatory Approvals

EMI/EMC: FCC Class B, CE  
Safety: UL, cUL, CE/EN60950, UL60950, C-Tick,  
GOST

RoHS Compliant

## Protocols and Standards

IEEE 802.3  
IEEE 802.3u  
IEEE 802.3af  
IEEE 802.3ab

## Ordering Information

### AT-6102G-00

IEEE 802.3af universal multi-voltage Gigabit PoE splitter

## Associated Products

### AT-6101G

IEEE 802.3af Gigabit PoE injector

### AT-FS708/POE

Unmanaged 8 port PoE switch

### AT-8000/8POE

8 port PoE managed Fast Ethernet switch

### AT-8000S/24POE

24 port Layer 2 stackable Fast Ethernet switch

### AT-8000S/48POE

48 port Layer 2 stackable Fast Ethernet switch

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2008 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.

617-000297-00 Rev A