



AT-RPS3204 & AT-PWR3202

Redundant Power Supply Chassis and Power Module

AT-PWR3202

Redundant power supply module (AC supply)

AT-RPS3204

Redundant power supply chassis containing one AT-PWR3202 power supply

Overview

The Allied Telesis AT-RPS3204 and AT-PWR3202 switch accessories provide optional redundant power options to a range of Allied Telesis switches. Installing a redundant power supply increases network reliability, as the switch can continue to operate in the event of a failure of the switch's main internal power supply, or that of the redundant power supply. Failure of either power supply causes an event to be sent to a Network Management System (NMS) allowing a network administrator to take the appropriate remedial action, thus averting a catastrophic failure on the network.

The AT-RPS3204 is a 19" rack-mountable chassis, capable of holding up to four individual AT-PWR3202 power modules.

Each AT-PWR3202 power module is hot swappable/removable from the AT-RPS3204 chassis, thus increasing system reliability on multi-switch installations. Additionally, each power supply can be individually isolated, to help in both installation and troubleshooting.

Compatible Switches

AT-9408LC
 AT-9424T/SP
 AT-9424T/GB
 AT-9424Ts
 AT-9424Ts/XP
 AT-9448T/SP
 AT-9448Ts/XP
 AT-x600-24Ts
 AT-x600-24Ts/XP
 AT-x600-48Ts
 AT-x600-48Ts/XP

Technical Specifications

AT-PWR3202

Input voltage	100~240V AC
Power	200W
Dimensions	24.87cm x 10.9cm x 4.11cm (9.79 x 4.29 x 1.62 in.)
Weight	1.182kgs (2.6 lbs)

AT-RPS3204

Dimensions	44.05cm x 36.06cm x 43.7cm (17.34 x 14.20 x 1.72 in.)
Weight	5.273kgs (11.6 lbs) (including 1 x AT-PWR3202)

Environmental Specifications

Operating temperature	0°C to 40°C
Storage temperature	-20°C to 80°C
Relative humidity	<85% non-condensing

Key Features

- Provides optional redundant power
- Supplies up to four switches
- Hot swappable modules
- Only 1RU high
- Rack-mountable (kit included)
- Individual manual isolation switches

Ordering Information

AT-PWR3202

Redundant power supply module (AC supply)

AT-RPS3204-xx

Redundant power supply chassis containing one AT-PWR3202 power supply

Where xx =
 10 for US power cord
 30 for UK power cord
 40 for Australian power cord
 50 for European power cord

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895
 European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11
 Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.

617-000241 Rev.C