



AT-AR027 FXS-VoIP Port Interface Cards (PICs)

AT-AR027 FXS-VoIP

The AT-AR027 FXS (Foreign Exchange Service) Port Interface Card (PIC) provides low-density, high-quality, full-duplex, inter-site voice/fax communication over IP. Combined with an Allied Telesis router or Rapier™ Layer 3 switch it will allow up to eight telephones or faxes to be connected to a Local Area Network.

Industry Standard Compatibility

The AT-AR027 fully complies with Industry Standard Protocols, such as VoIP, H.323 v2, SIP, G.711 A/μlaw, G.723.1 and G.729 A/B (optional).

High Quality of Voice

The AT-AR027 also provides support for various voice CODECs i.e. G.711 (A/μlaw) vocoder 64Kbps, G.723.1 (5.3 and 6.3Kbps) and G.729 A/B (8Kbps) (optional).

Technical Specifications

Physical Dimensions

Height: 18mm
Width: 84mm
Depth: 120mm
Weight: 0.098kg

Voice CODEC

G.711 A/μ-law, G.723.1, 5K3/6K3, G.729 A/B (Optional)

FXS Ports

2 x RJ-11 ports per card

LED Indications

Off Hook / Ring, PIC Error, Registered State

OS Minimum Requirement

AlliedWare™ 2.5.3

Standards

VoIP
H.323v2
SIP

Host Device Occupancy

Device	No. of AR027 PICs supported
AT-AR410	One
AT-AR410S	One
AT-AR415S	One
AT-AR440S	One
AT-AR441S	One
AT-AR442S	One
AT-AR720	Two
AT-AR725	Two
AT-AR740	Up to a maximum of four
AT-AR745	Up to a maximum of four
Rapier 16f	Up to a maximum of four
Rapier 16fi	Up to a maximum of four
Rapier 24	Up to a maximum of four
Rapier 24i	Up to a maximum of four

Key Features

- Cost savings on long distance calls
- Integration of voice and data networks
- Reduction of resource costs
- Use of open standards
- Port Interface Cards supports 2 POTS ports (RJ-11) per card
- Each PIC supports up to 2 attached analog devices (i.e. phone, fax)
- Voice compression to 5.3K per call with support for multiple algorithms
- Compliant with SIP and H.323
- Programmable country specific tones

Ordering Information

AT-AR027
Two VoIP FXS ports
Order number: 990-001356-00

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-00613-00 Rev.D