


### 3-Electrode Gas Tube Arrester

UN3E5-350L

φ5×7.6

2.5KA×2

#### Dimension



Unit:mm

Nickel-plated

Electrical Specifications			Applications
DC Spark-over Voltage at 100V/S	350±20%	V	<ul style="list-style-type: none"> <li>u Branch exchange(MDF)</li> <li>u Date/Single line protection</li> <li>u Station protection</li> <li>u Telephone / Fax / modem protection</li> <li>u Consumer electronics</li> </ul>
Impulse Spark-over Voltage at 100V/μs at 1KV/μs	<700	V	
	<800	V	
Life:			
Impulse Discharge current	8/20μs (±5 times)	2.5×2 KA	
	10/1000μs (300 times)	100 A	
AC Discharge current	(1S,5times interval 3 minutes)	2.5×2 A	
Insulation resistance at DC 100V	>1000	MΩ	
Electrode Capacitance at 1MHz	<1.5	pF	
Arc Voltage at 1A	~25	V	
Glow Voltage at 1mA	~70	V	
Holdover Voltage at 100mA, <150mS	150	V	
Transverse delay time	< 0.2	μs	
Weight	~0.7	g	
Operation and storage Temperature	-40~+90	°C	
Marking, Black	<p style="text-align: center;"><b>UNION</b> <b>350L-YY</b></p> <p>350 -Nominal voltage L -5KA YY -Year of production</p>		

#### Feature

- u Non-Radioactive
- u ROHS Compliant
- u LOW Capacitance
- u High insulation resistance
- u Fast response-time
- u Very small size

#### Notes:

1. Terms in accordance with ITU-T K.12 and GB/T 9043-2008
2. At delivery AQL 0.65 level II , DIN ISO 2859
3. After life test:  
DC Spark-over Voltage at 100V/S :350±30%  
Impulse Spark-over Voltage at 1KV/μs<900V