

CVR-1200

Pineview (Atom), 3 GbE ports , 2 FXO & 2 FXS ports



FEATURE

- Atom D-series Processor
- 2 SO-DIMMs DDR3
- 3 GbE ports / 4 Analog ports
- One PCI expansion
- One Mini PCI-E socket

SPECIFICATION

CPU Board	-Intel Atom D525 1.8GHz Dual-Core
System Memory	-Two SO-DIMM sockets -Supports DDR3 800 up to 4 GB
Ethernet Port	-3 GbE RJ45 ports
Analog I/O	-2 FXS & 2 FXO ports
Expansion	- One PCI slot & One Mini PCI-E socket
Storage Device	- Support one 3.5" or 2.5" SATA HDD - CF socket on-board
Serial Port	-One front-access RJ45 for Intel system console -One rear-access DB-9 for AudioCode system console
LCD Panel	- 2x16 characters or 128x32 graphic LCD module with 4 buttons
LEDS	Power status, data access, Ethernet status (LNK/ACT), Ethernet speed (10/100/1000) and Analog ports.
USB	- Dual USB 2.0, front accessible
Power	- 100W full-range ATX
Dimension	- 430(W) x 330.2(D) x 44(H) mm - 16.93"(W) x 13"(D) x 1.73"(H)
Operating Environment	-Temperature: 0 to 40°C (32 to 104°F) -Humidity 20% to 90%RH
Storage Environment	-Temperature: -10 to 70°C (14 to 158°F) -Humidity 5% to 95%RH
Certification	CE/FCC Part 68/UL

ORDERING GUIDE

Model	CPU	Ethernet	FXS	FXO	EZIO	PCI Expansion
CVR-1200-3040	Atom D525	3 RJ45 GbE ports	2	2	Optional	1