



CVR-4400

FreeScale (MPC8367), 8 T1/E1 ports,
4 LAN ports, 24 FXO/FXS ports



FEATURE

- Powered by FreeScale MPC8567
- 4 Gb Ethernet ports LAN connection
- V.90 interface
- Mini-PCI socket for wireless application
- Optional 4 or 8 TDM/PCM channels for T1/E1 connection
- Optional Single or Dual DSP module
- Optional 12 ports FXS & FXO module



SPECIFICATION

CPU Board	Built with FreeScale MPC8567
System Memory	One DDR2 DIMM up to 2GB
Network Interface	- 4 10/100/1000 GbE switching LAN ports - 1 x 10/100/1000 GbE WAN port - 1 x V.90 Modem port - Optional 4 or 8 T1/E1 module
PSTN Interface	- Optional 12 ports FXS or FXO ports - 2 Slots for FXS/FXO module
Expansion Slot	Mimi-PCI socket onboard
Serial Port	One RJ45 connector for system console through RS232
LEDs	LED indicators for power and status
USB	Dual USB 2.0
Power	200W ATX Power Supply
Dimension	430(W) x 88(H) x 443(D) mm
Operating Environment	- Temperature: 5 to 40°C (41 to 104°F) - Humidity 20% to 90%RH
Storage Environment	- Temperature: 5 to 70°C (32 to 158°F) - Humidity 5% to 95%RH
Certification	CE/FCC Part 68/UL



Rear View

ORDERING GUIDE

Part No.	CPU	T1/E1	WAN	LAN	FXS	FXO	DSP	PoE
CVR-4400-1000	MPC 8567	1	4	Optional	Optional	Optional	Optional	Optional