



ORION-D4601

460W PS/2 ATX
power supply with active PFC



SPECIFICATION

Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	7.5A@115V, 3.5A@230V
Efficiency	> 71%
Holdup Time	16 ms at full load
Over Voltage Protection	+5V: 5.7 ~ 6.5V; +3.3V: 3.9 ~ 4.3V; +12V: 13.6 ~ 15.
Over Power/Load Protection	Output power over 110% ~ 150%
MTBF	98,302 hrs
EMI & Safety Approval	UL, cUL, TUV, CE, FCC
Temperature/Humidity	Operating: 0 ~ 40°C, 20 ~ 90%RH Storage: -20 ~ 60°C, 5 ~ 95%RH
Dimension (WxDxH)	150x140x86 mm; 5.9"x5.5"x3.4"

FEATURES

- PS/2 ATX power supply suitable for 2U up chassis
- Active PFC, full-range input
- Support for Intel® Pentium® 4 processor
- Max. +5V standby output is 2A

ORDERING GUIDE

- ORION-D4601
460W PS/2 ATX power supply with active PFC

DC OUTPUT

	+5	+3.3V	+12V	-5V	-12V	+5Vsb
Max. Load	40A	30A	27A	0.8A	1A	2A
Min. Load	5A	1A	2.5A	0A	0A	0.1A
Max. Watt.	460W	460W	460W	460W	460W	460W
Load Reg.	±5%	±5%	±5%	±5%	±5%	±5%
Line Reg.	±1%	±1.5%	±0.4%	±1%	±0.4%	±1%
Ripple	±1.2%	±1.8%	±0.8%	±1.2%	±0.8%	±1.2%
Noise	±1.2%	1.8%	±0.8%	±1.2%	±0.8%	±1.2%