

# **ESW726 Series**

## **Industrial 26 Port 19 inch Rackmount Managed Ethernet Switches**

### **Features**

- ✓ Light industrial design EN61000-6-1 specifications
- ✓ -10 to 60°C or -40 to 75°C (-T models) temperature rating
- ✓ Supports IEEE 802.3 10Base-T, 802.3u 100Base-TX
- ✓ RJ-45 port supports auto MDI/MDI-X function
- ✓ SC Single mode and Multi mode fiber connectors
- ✓ Gigabit options with copper and SFP combo ports
- ✓ Web Browser Management and Configuration
- ✓ RingOn redundant rapid recovery system
- ✓ Rapid Spanning Tree Protocol recover system
- ✓ IGMP with Query mode for multimedia application
- ✓ Port based VLAN / 802.1 Q Tag VLAN
- ✓ Relay alarm output for system events
- ✓ Port mirroring for diagnostics
- ✓ 256K bytes packet buffer
- ✓ 8k MAC address table
- ✓ 18 to 36 VDC power input
- ✓ 19-inch rack 1U height
- ✓ 100% burn in testing
- ✓ 5 year warranty



### **Functional Description**

B&B Electronics Elinx family of Industrial rack mount Ethernet switches have been designed to meet light Industrial communication requirements. The ESW726 Managed family offers a variety of Industrial models. The switch configurations range from 26 ports RJ45 copper to RJ45 copper with multi mode, single mode, and or SFP gigabit ports.

Two ports can be used for network redundancy by implementing our RingOn technology. RingOn has been developed to provide a rapid recovery system for Industrial networks. If any part of the ring disconnects the network communications will automatically be restored by RingOn technology.

### **Web-based Management**

Each switch has an embedded HTML web site residing in flash memory, offering advanced management features and allows users to manage the switch from anywhere on the network through a standard web browser.

### **VLAN Configuration**

A Virtual LAN (VLAN) is a logical network grouping that limits the broadcast domain. This allows you to isolate network traffic so that members of a VLAN will only receive traffic from other members of the same VLAN. Creating a VLAN from a switch is the logical equivalent of reconnecting a group of network devices to another Layer 2 switch. However, since it is a virtual network, the network devices remain connected to the same switch physically. Both port-based and 802.1Q (tagged-based) VLAN are supported.

**IGMP**

The Internet Group Management Protocol (IGMP) is a communications protocol used to manage the membership of Internet Protocol multicast groups. IGMP is used by IP hosts to establish multicast group memberships. This allows the port to detect IGMP query and report packets and manage IP multicast traffic through the switch.

**Standards and Managed Protocols**

- Web browser management
- IEEE802.1D STP
- IEEE802.1W RSTP
- RingOn™:Recovery Time within 15ms
- IEEE802.1p Class of Service
- IEEE802.1Q VLAN Tagging
- IEEE802.1ad Port Trunk with LACP
- IEEE802.1x Port-Based Access Control
- Protocols:
  - SNMP V1/V2/V3
  - DHCP Server
  - SNTP
  - SMTP
  - IGMP Snooping/GMRP
  - LACP
  - RMON
  - HTTPS
  - Telnet
  - Syslog
  - HTTP
- Priority Queues: 4
- IGMP Groups: 64
- Maximum VLANs: 256

**Ordering Information:**

Model	10/100	10/100/1000	SFP 1000	Multi-mode Fiber	Single-mode Fiber	Temperature
ESW726	26					-10 to 60°C
ESW726-2MC	24			2 (SC)		-10 to 60°C
ESW726-2SC	24				2 (SC)	-10 to 60°C
ESWG726-2SFP	24	(2)	(2)			-10 to 60°C
ESW726-T	26					-40 to 75°C
ESWG726-2SFP-T	24	(2)	(2)			-40 to 75°C
ESWG726-4MC-2SFP-T	20	(2)	(2)	4 (SC)		-40 to 75°C
ESWG726-4SC-2SFP-T	20	(2)	(2)		4 (SC)	-40 to 75°C



**Accessories**

Model No.	Description
MDR-60-24	24VDC 60W Single Output Industrial DIN Rail Power Supply
C5UMB3FBG	Ethernet Category 5e patch cord, 3 ft. (0.9m), beige
C5UMB7FBG	Ethernet Category 5e patch cord, 7 ft. (0.9m), beige
SFP-1000SX-M-550M-T	SFP Module, 1000Base-SX, Multi-mode 550m, LC Connector (-40 to 85 °C)
SFP-1000LX-S-10KM-T	SFP Module, 1000Base-LX, Single-mode 10km, LC Connector (-40 to 85 °C)
SFP-1000LX-S-20KM-T	SFP Module, 1000Base-LX, Single-mode 20km, LC Connector (-40 to 85 °C)

**Specifications:**

**Technology**

Standards:	IEEE802.3, 802.3u,802.3ab,802.3z, 802.3x
Processing Type:	Store and forward with IEEE802.3x full duplex, non-blocking flow control
Flow Control:	IEEE802.3x flow control, back pressure flow control
Packet buffer memory:	256 K bytes
Address Table Size	8K MAC Addresses

**Interface**

RJ45 Ports:	10/100BaseT(x) auto negation, Full/Half duplex, auto MDI/MDI-connection
Fiber Ports:	100BaseFX ports (multi-mode or single-mode with SC connector) Mini-GBIC SFP Combo Ports
LED Indicators:	Power, Link, Speed, System Status

**Fiber Optics**

Fiber Type	Distance	Wavelength	Output Power	Sensitivity
Multi-mode	2 km	1310 nm	- 20 to - 14 dBm	≤ - 33.9 dBm
Single mode	20 km	1310 nm	- 15 to - 14 dBm	≤ - 31 dBm

**Power**

Input Voltage	18 to 36 VDC
Power Use	20W Max
Input Connection	Terminal Block
Protection	Reverse Polarity Protection

**Environmental**

Op. Temperature	-10 to 60C or -40 to 75C
Storage Temperature	-40 to 80 °C
Op. Humidity	0 to 95% Non-condensing
MTBF	200,000 hours

**Mechanical**

Enclosure	IP 30 Metal
Dimensions	443 x 44 x 220
Installation:	19" Rackmount / 1U

**Regulatory Approvals**

CE, FCC,  
RoHS - Yes



**Mechanical**

