

*Model: EIR618-2SFP-T*

## Eighteen Port Managed Industrial Ethernet Switches with SFP Gigabit Ports



PRODUCT INFORMATION

B&B ELECTRONICS

### Features

- ✓ X-Ring Automatic Recovery
- ✓ 16 10/100 TX RJ45 Ports with MDI/MDI-X
- ✓ 2 Combo 10/100/1000TX RJ45 or 100/1000 SFP Ports
- ✓ Dual 12 to 48 VDC Power Inputs
- ✓ Wide Operating Temperature
- ✓ Relay Alarm Output
- ✓ IP30 DIN Rail or Panel Mount
- ✓ Automatic E-mail Notification for system events
- ✓ SNMP, CLI, or Web Management
- ✓ Port Mirror and Port Trunk with LACP

### Functional Description

The Elinx EIR618-2SFP-T Industrial Managed Ethernet Switch provides powerful functionality in a small package. Designed for industrial applications, this switch contain all the standard features of other switches, such as IGMP Snooping, Port Based VLAN, 802.1Q Tag VLAN, RJ-45 automatic MDI/MDI-X, auto negotiation, store and forward switching, STP, RSTP, Web Based Management, Ingress Packet Filtering, and Egress Rate Control. These managed switches also come with important industrial features to ensure reliability in an industrial application. X-Ring technology with coupling ring and dual homing allows automatic recovery in less than 300 MS. Dual power inputs ensure reliability. A relay alarm output for port failure notification. DIN Rail and Panel Mounting options on the same IP30 case. Another important feature is automatic e-mail notification for system events such as a cold start, change in network topology, power status or SNMP authentication failure.

### Ordering Information

Model Number	Description
EIR618-2SFP-T	Industrial Managed Ethernet Switch, 16 10/100 RJ45 Ports, plus 2 Combo 10/100/1000 RJ45 or SFP Mini-GBIC Ports



**International Headquarters:** 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA  
 815-433-5100 Fax 433-5104 [www.bb-elec.com](http://www.bb-elec.com) [orders@bb-elec.com](mailto:orders@bb-elec.com) [support@bb-elec.com](mailto:support@bb-elec.com)

**European Headquarters:** Westlink Commercial Park Oranmore Co. Galway Ireland  
 +353 91 792444 Fax +353 91 792445 [www.bb-europe.com](http://www.bb-europe.com) [orders@bb-europe.com](mailto:orders@bb-europe.com) [support@bb-europe.com](mailto:support@bb-europe.com)

## Specifications

### Technology

IEEE Standards	802.3 10Base-T Ethernet, 802.3u 100Base-TX and 100Base-FX Fast Ethernet 802.3x Flow Control and Back Pressure, 802.1d Spanning Tree, 802.1w Rapid Spanning Tree 802.1p Class of Service, 802.1Q VLAN Tag, 802.3ad Port Trunk with LACP, 802.1x RADIUS 802.3ab 1000BaseT, 802.3z Gigabit fiber
Processing Type	Store and Forward
Flow Control	Flow control on full duplex, Back Pressure on half duplex
MAC Address Table Size	8 KB
Memory	4MB Flash ROM, 32MB DRAM
Protocol	CSMA/CD
Management	SNMP v1, v2c, v3, Web GUI, TELNET, CLI, Menu Driven Interface
Management Security	Up to 10 IP addresses can have permission to manage the switch. 802.1x (RADIUS) Authentication
Transfer Rate	14,880 bps for 10Base-T Ethernet ports, 14,8800 bps for 100Base-TX/FX Fast Ethernet ports 1,488,000 bps for Gigabit Fiber Ethernet ports
Packet throughput ability	10.7 Mbps @ 64 bytes
X-Ring	2 ports for X-Ring provide redundant backup with a recovery time below 300 MS.
Packet Filter	4 Selection Rules to filter combinations of Broadcast, Multicast, Unicast, and Unknown packets.
VLAN	Port based and Tag. Up to 256 VLAN groups. GVRP (256 Groups)
Port Trunk	LACP Port Trunk. 4 trunk groups / maximum of 4 trunk members.
Class of Service	4 priority queues per port
Quality of Service	Port based, Tag based, or IPv4 Type of Service, IPv4/IPv6 Different Service
IGMP	IGMP Snooping v1, v2, and v3. 256 multicast groups and IGMP query
Clock Synchronization	SNTP
Management Security	IP Address, 802.1x RADIUS
Port Security	Static MAC (100 entries) / MAC Filter (100 entries)
Port Mirror	TX packet only, RX packet only, or TX and RX packet
Firmware Update	TFTP, TFTP backup and restore
DHCP	DHCP Client / DHCP Server
Bandwidth Control	Ingress packet filter and Egress packet limit

### Interface

LAN/WAN Ports	16 RJ45 10/100TX, 2 Combo RJ45 10/100/1000 or SFP ports (RJ45 ports disabled when SFP installed)
Console Port	RS-232 RJ45 (DB9 to RJ45 adapter cable included)
Port Indicators (each port)	10/100: Link/Activity (Green), Full-duplex/Collision (Yellow). Giga Copper: Link/Activity (Green), Speed (1000Mbps Green) SFP: Link/Activity (Green)
System Indicators	Green LEDs for Power, Power 1, Power 2, and Master. Orange LED for Fault.

### Power

Input Voltage	12 to 48 VDC, dual source
Current Consumption	1.1 A max.
Input Connection	Terminal Block
Relay Alarm	1A @ 24VDC

### Mechanical

Enclosure	IP30 Aluminum Case
Mount	35 mm DIN or Panel
Dimensions	2.9 x 4.2 x 6.4 in (7.4 x 10.7 x 16.3 cm)

### Environmental

Operating Temperature	-40 to 167 F (-40 to 75 C)
Storage Temperature	-40 to 185 F (-40 to 85 C)
Operating Humidity	0 to 95% NC
MTBF	243301 hours

### Regulatory Approvals

EMI	FCC Class A EN6100-4-2, -4-3, -4-4, EN6100-4-5, -4-6
Safety	EN60950
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6

#### CE Declaration of Conformity

Manufacturer's Name	B&B Electronics Mfg CO
Manufacturer's Address	707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
Model Numbers	EIR618-2SFP-T
Description	Industrial Managed Switch
Type	Light Industrial ITE Equipment
Application of Council Directive	89/336/EEC
Standards	EN55022 EN61000-4-2, -4-3, -4-4, -4-5 EN61000-4-6, -4-8, -4-11, -4-12 EN61000-6-2, -6-4



Michael J. Fahrion, Director of Engineering



**International Headquarters:** 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA  
 815-433-5100 Fax 433-5104 [www.bb-elec.com](http://www.bb-elec.com) [orders@bb-elec.com](mailto:orders@bb-elec.com) [support@bb-elec.com](mailto:support@bb-elec.com)

**European Headquarters:** Westlink Commercial Park Oranmore Co. Galway Ireland  
 +353 91 792444 Fax +353 91 792445 [www.bb-europe.com](http://www.bb-europe.com) [orders@bb-europe.com](mailto:orders@bb-europe.com) [support@bb-europe.com](mailto:support@bb-europe.com)