

60W to 150W
ARMA-2000X® series

Features

- High gain and linearity
- Output power up to 150W (see table A)
- Gain adjustment (Local & Remote)
- Remote Monitor & Control (Local & Remote)
- Output sample monitor port
- Temperature gain compensation
- Automatic over-temperature shutdown
- Automatic high reflected power shutdown
- Infinite VSWR protection
- Power factor correction
- CE Marking

Overview

The ARMA-2000X® series are the rack-mount solid-state power amplifiers (SSPAs), operating in X-Band frequency range. The amplifier is an integrated unit, complete with power supply and cooling system. Intended for indoor operation, the amplifiers are of compact size and occupy four rack-mounting spaces (4 RU – 7.0") of a standard 19-inch rack. Built-in microprocessor controller provides capability for serial port interfaces (RS485) for remote monitoring and control.

Advantech's SSPAs set the industry standard for linearity and operating efficiency. Built-in design features and assembly methods incorporated with efficient combining techniques result in the trouble-free operation of the amplifier.

Application

The featured SSPAs are designed for X-Band satellite up-link applications. They are designed for 19-inch rack mounting in a protected environment. The ARMA-X series are available in output power from 20W to 800W. For higher power Advantech provides phase-combined systems.

Other SSPAs are available for operation at other satellite frequency bands. With all the features of the ARMA-X, Advantech also offers a built-in converter.

Redundancy

With the addition of the appropriate waveguide and switch kit, the ARMA-X® amplifiers can be easily converted for the operation in 1:1 redundant configuration with full remote monitor and control capability of the redundant system via serial interface.




Table A

Band*	RF Band (GHz)	Output Power (W)
X	7.90 – 8.40 GHz	60 - 150

*Other frequency sub-bands are available. Please consult factory.

Options

- Integrated Block Up Converter
- RF input sample port
- Redundant system

Accessories

- Redundancy Kit
- Shelf slides
- Remote M&C panel (Ethernet port optional)
- Receive Reject Filter

X-Band Rack-mount SSPA

Technical Specifications	60W	80W	100W	125W	150W
Electrical Characteristics					
Availability in this series					
X	√	√	√	√	√
Output power (Psat)	+48 dBm	+49 dBm	+50 dBm	+51 dBm	+52 dBm
Output power (P1dB)	+47 dBm	+48 dBm	+49 dBm	+50 dBm	+51 dBm
Power gain at maximum gain setting	56 dB min	60 dB min			
Operating frequency range	7.90 – 8.40 GHz				
Max input power without damage	+10 dBm				
Gain slope	0.6 dB max over 40 MHz				
Gain flatness over 500 MHz	±1.0 dB max				
Gain variation over temperature	±1.5 dB over full operating temperature range				
Gain variation over 24 hours	±0.25 dB max at constant temperature & drive level				
Gain adjustment range	20 dB min. (0.1 dB resolution)				
Input return loss	18 dB				
Output return loss	19 dB				
Noise power density	-70dBm/Hz max in TX band -110 dBm/Hz max 7.25 – 7.75 GHz RX band				
Spurious at rated power	-65 dBc, max				
Harmonics at rated power	-60 dBc, max				
AM/PM conversion at rated power	2.5 %dB max. at P1dB, 1 %dB max. at 3 dB back-off				
Third order IMD (2 tones 5 MHz apart)	-25 dBc max. at 3 dB total back-off from rated P1dB				
Group delay	Linear: 0.02 nsec/MHz max. Parabolic: 0.003 nsec/MHz ² max. Ripple: 1.0 nsec p-p max.				
Residual AM (F* - frequency in kHz)	0-10 kHz		-45 dBc		
	10 kHz - 500 kHz		-20 (1.25+log F*) dBc		
	500 kHz - 1 MHz		-80 dBc		
Power Requirements					
AC input voltage	90-264 VAC auto ranging (47-63 Hz)				
Power consumption (nominal)	630W	710W	850W	900W	1400W
Mechanical Characteristics					
Panel height	4 RU of 19" rack				
Weight	30 kg (66 lbs)				
Interfaces:	RF input RF output	N-Type (F) CPR-112 contact	Redundancy RS-485 Discrete port	D-sub 15S D-sub 9S D-sub 25S	AC Line Output sample port IEC 320 inlet N-Type (F)
Environmental Conditions					
Operating temperature:	0°C to +50°C				
Humidity	5%-95%, non-condensing				
Altitude	10,000' AMSL, de-rated 2°C/1,000' from AMSL				

NORTH AMERICA
USA
Tel: +1 678 889-1831
Fax: +1 678 889-1756
info.usa@advantechwireless.com

CANADA
Tel: +1 514 420 0045
Fax: +1 514 420 0073
info.canada@advantechwireless.com

EUROPE
UNITED KINGDOM
Tel: +44 1480 357 600
Fax: +44 1480 357 601
info.uk@advantechwireless.com

RUSSIA & CIS
Tel: +7 495 971 59 18
info.russia@advantechwireless.com

SOUTH AMERICA
USA
Tel: +1 678 889-1831
Fax: +1 678 889-1756
info.latam@advantechwireless.com

BRAZIL
Tel: +55 11 3054 5701
Fax: +55 11 3054 5701
info.brazil@advantechwireless.com

An ISO 9001 : 2008 Company



Ref.: PB-ARMA-X-60-150-12106