



Features

- **16 kbps to 10 Mbps in 1 bps Steps**
- **BPSK ,QPSK, 8PSK & 16QAM Operation**
- **Viterbi FEC**
- **Optional: Reed Solomon**
- **L-band or 70MHz interfaces**
- **Bridging and/or IP routing (standard)**
- **Multi-demod configurations**
- **Optional: Turbo Product Code**

Overview

The AMT 30 modem series provide unparalleled flexibility in interfaces and capabilities stemming from its modular construction. The AMT supports two modulator/demodulator stuffing slots allow the AMT 30 modem series to support the following configurations:

Tx-only	Modulator only
Rx-only	Demodulator only
Tx-Rx	Mod/Demod
Tx-2RX	Mod/Dual-demod
4Rx (referred to as AMT34)	2x Dual-Demod or Quad-demod

The modem modulates carriers directly at L-band, resulting in an efficient uplink system with an extremely pure output spectrum. A 70+18hz/140+36Mhz option is also available. The modem includes support for BPSK, QPSK, 8PSK and 16QAM with data rates from 16 kbps to 10 Mbps in 1 bps steps. The AMT-30 provides Viterbi forward error correction (FEC) as standard. Available options include Intelsat compliant Reed Solomon outer FEC codec, or Turbo FEC option that greatly improves BER performance. Monitor and Control (M&C) is available via RS-232 and RS-485 ports to provide access to a command line interface, with an Ethernet option for SNMP and Telnet interfaces. In addition, the modem can be configured via an optional front panel or hand held controller. DC power and high stability 10 MHz reference can be supplied for powering and synchronizing a Block Up Converter (BUC) and Low Noise Block Down Converter (LNB).

The standard data interface for the AMT 30 modem family is a 10/100BaseT Ethernet providing supporting forwarding rates of up to 10Mbps for bridging or IP routing applications. In the AMT34 configuration, the AMT34 forwarding rate is limited to 10Mbps. Alternatively, the AMT30 can be ordered with EIA530 serial port interface capable of supporting 10Mbps speeds. In the AMT34 configuration, each of the four EIA530s is capable of supporting 10Mbps.

In addition, Advantech's PowerTrack™ system provides additional stability (control) over the transmission chain when using compatible AMT BUC's. AMT BUCs include a power detector on the output, which the modem monitors and adjust its own Tx output level in response and maintaining a constant output power from the BUC. This closed loop power control maintains the output power from the BUC stable within ± 1 dB under all environmental conditions.

OPTIONAL FEATURES:

- **Available with 4Mbps and 10Mbps options.**
- **Turbo FEC 3/4, 7/8, 0.95 Rates**
- **EIA530 in lieu of 10/100BaseT as standard data interface.**
- **Concatenated Reed Solomon outer/ Viterbi inner FEC**
- **Power Supplies and High Stability**
- **Reference for BUC and LNB**
- **Optional Front Panel Display and Keypad (as shown)**
- **1:1 redundancy solutions available**

The AMT30. Versatile. Effective. Affordable.

Performance specifications

Modulation modes: BPSK, QPSK, Optional: 8PSK, 16QAM

FEC: Viterbi: 1/2, 3/4 or 7/8 rate, k=7

Optional : Reed Solomon Outer Codec for Viterbi

Optional: Turbo Product Code, 3/4, 7/8 or 0.95

Data and code rates (in 1 bps increments):

BPSK, 3/4 rate:	14.4 to 4425 kbps
BPSK, 7/8 rate:	16.8 to 5162 kbps
BPSK, 19/20 rate:	18.5 to 5686 kbps
QPSK, 3/4 rate:	28.8 to 8850 kbps
QPSK, 7/8 rate:	33.6 to 10000 kbps
QPSK, 19/20 rate:	37.0 to 10000 kbps
8PSK, 3/4 rate:	43.2 to 10000 kbps
8PSK, 7/8 rate:	50.4 to 10000 kbps
8PSK 19/20 rate:	55.5 to 10000 kbps
16QAM, 3/4 rate:	57.6 to 10000 kbps
16QAM 7/8 rate:	67.2 to 10000 kbps

Scrambling: V.35, IESS 308/309 CCITT

Roll off: 0.15, 0.20, 0.25, 0.30, 0.35

Spectral Shape: IESS 308/309 compliant

RF Frequency:

L-band: 950 to 1750Mhz in 1Hz steps

(optional: 950 to 2000Mhz).

Optional: 70+/-18Mhz

140+/-36Mhz

Modulator specific:

IF Output Connector:

Type N (f) 50 Ohm for L-band

BNC (f) for 70/140Mhz, 50 Ohm

Return Loss ≥ 17 dB

RF Output Power:

Range: -5 to -35 dBm, in 0.10 dB steps

Accuracy: +0.5 dB; Temp

Stability: +0.25 dB

Output spurious/Harmonics: -55dBc DC to 2500Mhz/-50dBc; 1900 Mhz to 2500Mhz

Phase Noise: IESS 308/309 compliant

BUC Reference Frequency and Stability

Frequency: 10 MHz, 0 dBm, +2 dB

Stability: 5 x 10⁻⁹/per day; 5 x 10⁻⁸/year, no

frequency/phase hits for external ref.

Optional: BUC Power Supply 24VDC@4A,

48VDC@2A, 48VDC@4A.

Demodulator specific:

IF Input Connector:

Type N (f) 75 Ohm for L-band

Option: BNC (f) for 70/140Mhz. 50 Ohm

Return loss: ≥ 12 dB

LNB Alarm for Short Circuit

RF Input Power Levels:

Lband: -70 to -40dBm, with AGC

70/140: -55 to -35dBm, -5dBm max composite level, with AGC

LNB Power and Control

Selectable LNB Supply Voltage: ON/OFF, 18 VDC

(Horizontal Pol.) or 13 VDC (Vert Pol.), 0.5A max

LNB Control: 22 +4 kHz single tone burst, amplitude =

0.6 +0.2 V p-p

Typical Eb/No Performance @ 10⁻⁶ BER QPSK:

Rate	Viterbi	Viterbi+RS	TPC
1/2	6.1dB	4.3dB	---
3/4	7.6dB	5.7dB	3.9dB
7/8	8.7dB	6.7dB	5.4dB
.95			7.5dB

Data Interfaces:

10/100Mbps Ethernet (IP router/ Bridge)

IP options:

Static and Dynamic IP routing (RIPv1&2)

OSPF

DHCP Server

Network Address Translation

Packet Filtering (Firewall)

Quality of Service support to Level 3

Command line interface (Industry Standard)

SNMP v.1 & v.2c, MIB II

AAA (Authentication, Authorisation & Accounting)

Local AAA (Access Rights Table)

PAP, CHAP, MS-CHAP (Client/Server Authentication)

RADIUS, TACACS+ (Client, Remote server authentication)

Ping, Traceroute, Discovery Protocol

IP, TCP, UDP, ICMP Protocol Statistics

Interface Statistics

Multicast

VPN Support

IP Header Compression

Payload Compression

Telnet

Large IP/ethernet packet support (MPLS)

Bridging options:

Spanning Tree Protocol (STP)

Rapid STP (RSTP)

MAC filtering

EIA-530 (RS422)

Can either be transported transparently or can

interface and interoperate with Frame relay or HDLC.

Management and Control

Active Front Panel:

Provides display and keypad on front panel for access to all functions, alarms and status messages

Hand Held Terminal

Allows text-based access to all functions, alarms and status messages

Remote Monitor and Control

10/100 Base-T port, RS-485, and RS-232 at rear

panel. Can be managed by CLI, Telnet, SNMP v2c.

Physical and Power Specifications

Dimensions:

1RU standalone chassis,

19W X 19D X 1.75H inches

(48W X 48D X 4.4H cms)

Weight: 11lbs (5kgs)

Power: 90 – 264VAC (50/60Hz)

or -48VDC (32 to 72VDC).

Power consumption: 50Watts (no BUC power supply)

Operating temp: 0°C to 45°C (32°F to 122°F)

Storage temp: -25°C to 85°C (-13°F to 185°F)

Relative humidity:

Operating: Up to 90% non-condensing

Non-Operating: Up to 95% non-condensing

Altitude: Operating: up to 10,000' (3,045M)

During Transit: up to 40,000' (12,180M)

NORTH AMERICA USA

Tel: +1 703 659 9796

Fax: +1 703 635 2212

info.usa@advantechwireless.com

CANADA

Tel: +1 514 420 0045

Fax: +1 514 420 0073

info.canada@advantechwireless.com

EUROPE

UNITED KINGDOM

Tel: +44 1480 357 600

Fax: +44 1480 357 601

info.uk@advantechwireless.com

RUSSIA & CIS

Tel: +7 495 971 59 18

info.russia@advantechwireless.com

INDIA

Tel: +91 33 2415 5922

info.india@advantechwireless.com

SOUTH AMERICA

Tel: +1 514 420 0045

Fax: +1 514 420 0073

info.latam@advantechwireless.com

BRAZIL

Tel: +55 11 3054 5701

Fax: +55 11 3054 5701

info.brazil@advantechwireless.com

An ISO 9001 : 2008 Company



Ref.: PB-AMT30-001-13150