

## ULTRA LOW CAPACITANCE TVS ARRAY



### DESCRIPTION

The PAM03SD2303CI is an ultra low capacitance transient voltage suppressor array, designed to protect automotive applications. This device is available in a bidirectional configuration and is rated at 250 Watts for an 8/20 $\mu$ s wave-shape.

The PAM03SD2303CI meets IEC 61000-4-2 (ESD) and IEC 61000-4-4 (EFT) requirements. At higher operating frequencies or faster edge rates, insertion loss and signal integrity are a major concern. This device offers a ultra low capacitance and low leakage current in a miniature SOD-323 package.

### FEATURES

- Compatible with IEC 61000-4-2 (ESD): Air - 15kV, Contact - 8kV  
*Exceeds Level 4: Handles 10kV Contact & 25kV Air Discharge*
- Compatible with IEC 61000-4-4 (EFT): 40A - 5/50ns
- 250 Watts Peak Pulse Power per Line ( $t_p = 8/20\mu$ s)
- Replacement for MLV (0805)
- Bidirectional Configuration
- Protects One Power or I/O Port
- ESD Protection > 25kV
- Low Clamping Voltage
- Ultra Low Capacitance: 0.6pF (Typical)
- RoHS Compliant
- REACH Compliant


### APPLICATIONS

- Automotive Applications

### MECHANICAL CHARACTERISTICS

- Molded JEDEC SOD-323 Package
- Approximate Weight: 5 milligrams
- Lead-Free Pure-Tin Plating (Annealed)
- Solder Reflow Temperature:  
Pure-Tin - Sn, 100: 260-270°C
- 8mm Tape and Reel Per EIA Standard 481
- Flammability Rating UL 94V-0

### PIN CONFIGURATION



**TYPICAL DEVICE CHARACTERISTICS**
**MAXIMUM RATINGS @ 25°C Unless Otherwise Specified**

| PARAMETER                                     | SYMBOL    | VALUE      | UNITS |
|---|-----------|------------|-------|
| Peak Pulse Power (tp = 8/20μs) - See Figure 1 | $P_{PP}$  | 250        | Watts |
| Operating Temperature                         | $T_A$     | -55 to 150 | °C    |
| Storage Temperature                           | $T_{STG}$ | -55 to 150 | °C    |

**ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified**

| PART NUMBER   | DEVICE MARKING | RATED STAND-OFF VOLTAGE<br><br>$V_{WM}$<br>VOLTS | MINIMUM BREAKDOWN VOLTAGE<br><br>@ 1mA<br>$V_{(BR)}$<br>VOLTS | MAXIMUM CLAMPING VOLTAGE (Fig. 2)<br><br>@ IP = 1A<br>$V_C$<br>VOLTS | MAXIMUM LEAKAGE CURRENT<br><br>@ $V_{WM}$<br>$I_D$<br>μA | TYPICAL CAPACITANCE<br><br>@ 0V, 1MHz<br>C<br>pF |
|---------------|----------------|--|---|--|--|--|
| PAM03SD2303CI | CC             | 3.0  | 4.0   | 7.0  | 5  | 0.6  |

## TYPICAL DEVICE CHARACTERISTICS

FIGURE 1  
PEAK PULSE POWER VS PULSE TIME






FIGURE 2  
PULSE WAVE FORM



## SPICE MODEL

**FIGURE 1**  
**SPICE MODEL**



ABD - Avalanche Breakdown Diode (TVS)  
 LCRD: Low Capacitance Rectifier Diode  
 Lg - Lead Inductance


| SPICE PARAMETERS |               |          |       |
|------------------|---------------|----------|-------|
| PARAMETER        | UNIT          | ABD(TVS) | LCRD  |
| BV               | V             | 4.0      | 100   |
| IBV              | $\mu\text{A}$ | 1        | 0.5   |
| $C_{jo}$         | pF            | 200      | 0.3   |
| $I_s$            | A             | 1E-11    | 1E-11 |
| Vj               | V             | 0.6      | 0.6   |
| M                | -             | 0.33     | 0.33  |
| N                | -             | 1        | 1     |
| $R_s$            | Ohms          | 0.22     | 0.75  |
| TT               | s             | 1E-8     | 1E-9  |
| EG               | eV            | 1.11     | 1.11  |

**SOD-323 PACKAGE INFORMATION**
**OUTLINE DIMENSIONS**

| DIM | MILLIMETERS |      | INCHES |       |
|-----|-------------|------|--------|-------|
|     | MIN         | MAX  | MIN    | MAX   |
| A   | 1.60        | 1.90 | 0.063  | 0.075 |
| B   | 1.15        | 1.45 | 0.045  | 0.057 |
| C   | 2.39        | 2.70 | 0.094  | 0.106 |
| D   | 0.80        | 1.10 | 0.031  | 0.043 |
| E   | 0.25        | 0.40 | 0.010  | 0.016 |
| F   | 0.10        | 0.20 | 0.004  | 0.008 |
| H   | -           | 0.10 | -      | 0.004 |
| L   | 0.20        | -    | 0.008  | -     |

**NOTES**


- Controlling dimension: millimeters.
- Dimensioning and tolerances per ANSI Y14.5M, 1985.
- Dimensions are exclusive of mold flash and metal burrs.


**PAD LAYOUT DIMENSIONS**


| DIM | MILLIMETERS |      | INCHES |       |
|-----|-------------|------|--------|-------|
|     | MIN         | MAX  | MIN    | MAX   |
| A   | 2.87        | 3.12 | 0.113  | 0.123 |
| B   | 0.66        | 0.91 | 0.026  | 0.036 |
| C   | 0.66        | 0.91 | 0.026  | 0.036 |

**NOTES**

- Controlling dimension: millimeters.



## TAPE AND REEL



## SPECIFICATIONS

| REEL DIA.  | TAPE WIDTH | A0          | B0          | K0          | D           | E           | F           | W           | P0          | P2          | P           | tmax |
|------------|------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|------|
| 178mm (7") | 8mm        | 1.55 ± 0.10 | 2.90 ± 0.10 | 1.35 ± 0.10 | 1.50 ± 0.10 | 1.75 ± 0.10 | 3.50 ± 0.05 | 8.00 ± 0.30 | 4.00 ± 0.10 | 2.00 ± 0.05 | 4.00 ± 0.10 | 0.25 |

## NOTES

1. Dimensions are in millimeters.
2. Surface mount product is taped and reeled in accordance with EIA-481.
3. Suffix - T7 = 7" Reel - 3,000 pieces per 8mm tape.
4. Marking on Part - marking code (see page 2).

Package outline, pad layout and tape specifications per document number 06010.R4 9/10.

## ORDERING INFORMATION

| BASE PART NUMBER | LEADFREE SUFFIX | TAPE SUFFIX | QTY/REEL | REEL SIZE | TUBE QTY |
|------------------|-----------------|-------------|----------|-----------|----------|
| PAM03SD2303CI-NQ | n/a             | -T7         | 3,000    | 7"        | n/a      |

This device is only available in a Lead-Free configuration.

Suffix -NQ = This is a commercial grade device and is not qualified to the AEC-Q101 standard. Please contact customer service for more information.

## COMPANY INFORMATION

---

### COMPANY PROFILE

In business more than 20 years, ProTek Devices™ is a privately-held company located in Tempe, Arizona, that offers a product line of transient voltage suppressors (TVS); avalanche breakdown diodes; steering diode TVS arrays and other surge suppressor component products. These TVS devices protect electronic systems from the effects of lightning, electrostatic discharge (ESD), nuclear electromagnetic pulses (NEMP), inductive switching and EMI / RFI. ProTek Devices also offers high performance interface and linear products that include analog switches; multiplexers; LED drivers; audio control ICs; RF and related high frequency products. The analog devices work in a host of consumer; industrial; automotive and other applications.

### CONTACT US

#### Corporate Headquarters

2929 South Fair Lane  
Tempe, Arizona 85282  
USA

#### By Telephone

General: 602-431-8101  
Sales: & Marketing: 602-414-5109  
Customer Service: 602-414-5114  
Product Technical Support: 602-414-5107

#### By Fax

General: 602-431-2288

#### By E-mail:

Sales: [sales@protekdevices.com](mailto:sales@protekdevices.com)  
Customer Service: [service@protekdevices.com](mailto:service@protekdevices.com)  
Technical Support: [support@protekdevices.com](mailto:support@protekdevices.com)

#### ProTek Devices (Asia Pacific) Pte. Ltd.

8 Ubi Road 2, #06-19  
Zervex  
Singapore - 408538  
Tel: +65-67488312  
Fax: +65-67488313

#### Web

[www.protekdevices.com](http://www.protekdevices.com)

COPYRIGHT © ProTek Devices 2011 - This literature is subject to all applicable copyright laws and is not for resale in any manner.

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice.

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance. ProTek assumes no responsibility with respect to the selection or specifications of such products. ProTek makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ProTek assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability without limitation special, consequential or incidental damages.

LIFE SUPPORT POLICY: ProTek Devices products are not authorized for use in life support systems without written consent from the factory.