

SG12232B (122 DOTS X 32 DOTS)

FEATURES

- BUILT-IN CONTROLLER (S6B1713 OR EQUIVALENT)
- +5 V POWER SUPPLY
- 1/32 DUTY CYCLE
- 8-BIT PARALLEL INTERFACE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	74.0 x 28.0 x 6.5	mm
Viewing Area (W x H)	58.9 x 18.4	mm
Active Area (W x H)	54.87 x 14.37	mm
Dot Size (W x H)	0.41 x 0.41	mm
Dot Pitch (W x H)	0.45x 0.45	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	V _{SS}	0V	Power Supply Ground
2	V _{DD}	5V	Power Supply Voltage
3	V ₀	-	Contrast Adjustment Voltage
4	RS	H/L	H : Data, L : Instruction Code
5	R/W	H/L	H : Read / L : Write
6	E	H→L	Enable Signal
7~14	DB0-DB7	H/L	Data Bus Line
15	/CS1	L	Chip Select Signal For IC1
16	CS2	H	Chip Select Signal For IC2
17	/RET	L	Reset Signal
18	V _{EE}	-	Power Supply Voltage For LCD
19	A	4.2V	LED Power (+)
20	K	0V	LED Power (-)

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	V _{DD-VSS}	0	-	7	V
Supply Voltage For LCD Drive	V _{DD-V₀}	0	-	17	V
Input Voltage	V _I	V _{SS}	-	V _{DD}	V

ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage For Logic	V _{DD-VSS}	-	2.4	3	3.6	V	
Supply Voltage For LCD	V _{DD-V₀}	V _{DD} =5V Ta=25.	4.4	4.8	5.2	V	
Supply Current	I _{DD}	V _{DD} =5V	-	2.5	4.5	mA	
Input Voltage	"HIGH" Level	V _{IH}	-	2.2	-	V _{DD}	V
	"LOW" Level	V _{IL}	-	-	-	0.6	V
Output Voltage	"HIGH" Level	V _{OH}	-	2.4	-	-	V
	"LOW" Level	V _{OL}	-	-	-	0.4	V

EXTERNAL DIMENSIONS

