


HSF300-12-□



Features:

- 300 Watt
- A, AD Type = IP66, NONE, D Type = IP67
- Built in PFC function (Active)
- Inrush current limit
- Wide input voltage (Universal input range)
- Over voltage protection
- Over current protection
- Outdoor LED lighting
- LED street lighting
- 5 year warranty



HSF300-S Specifications



	MODEL		HSF300-12	HSF300-24	HSF300-36	HSF300-48
INPUT	VOLTAGE, FREQUENCY		AC 100-240V (AC 90 ~ 264V or DC 127 ~ 370V), 50/60Hz (47 ~ 63Hz), Universal output			
	CURRENT [A]	110V	4.0 (I _o =100%)			
		220V	2.5 (I _o =100%)			
	EFFICIENCY [%]	110V	86 typ	88 typ	89 typ	90 typ
		220V	89 typ	91 typ	92 typ	92 typ
	POWER FACTOR	110V	0.99 typ			
		220V	0.98 typ			
INRUSH CURRENT			25A typ (AC IN 110V I _o =100%), 45A typ (AC IN 220V, I _o =100%) at cold start			
OUTPUT	VOLTAGE [V]		12	24	36	48
	VOLTAGE ADJ RANGE *NOTE1 [V]		10.8 ~ 13.2	21.6 ~ 26.4	32.4 ~ 49.8	43.2 ~ 51.5
	CURRENT [A]		20	12.5	8.3	6.25
	CURRENT ADJ RANGE *NOTE1 [A]		10 ~ 20	6.25 ~ 12.5	4.16 ~ 8.3	3.12 ~ 6.25
	REGULATION, LINE [mV]		120 Max	120 Max	180 Max	240 Max
	REGULATION, LOAD [mV]		120 Max	120 Max	180 Max	240 Max
	RIPPLE MAX [mV]		120 Max	120 Max	150 Max	150 Max
	RIPPLE NOISE MAX 1 [mV]		150 Max	150 Max	250 Max	250 Max
	RIPPLE NOISE MAX 2 *NOTE3 [mV]		600 Max	600 Max	800 Max	800 Max
	TEMPERATURE DRIFT [mV]		180 Max	360 Max	540 Max	720 Max
	RISE TIME [ms]		1500 Max (AC IN 100V I _o =100%)			
	HOLDING TIME [ms]		17 typ (AC IN 100V I _o =100%)			
FUNCTION	OVER CURRENT PROTECTION [A]	Works at 95 ~ 110% of rating				
	OVER VOLTAGE PROTECTION [V]		14 ~ 17	28 ~ 34	41 ~ 46	54 ~ 60
	DIMMING *NOTE2 [A]	1 ~ 10V (Percentage or rated current: 10% ~ 100%)				
ELECTRICALLY ISOLATED	INPUT-OUTPUT		AC 3,000V 1 minute current 20 mA, DC 500V 100MΩ (At room temperature & humidity)			
	INPUT-CASE, FG		AC 2,000V 1 minute current 20 mA, DC 500V 100MΩ (At room temperature & humidity)			
	OUTPUT-CASE,FG		AC 500V 1 minute current 100 mA, DC 500V 100MΩ (At room temperature & humidity)			
ENVIRONMENT	OPERATING TEMP AND HUMID		-40 ~ +70°C (Required derating), 20 ~ 90% RH (Non condensing)			
	STORAGE TEMP AND HUMID		-20 ~ +75°C, 20 ~ 90% RH (Non condensing)			
	VIBRATION		10 ~ 55Hz at 1G, 3 minute period, 30 minutes along X, Y and Z axis			
	IMPACT		10G for 20ms, once on each X, Y and Z axis			

*NOTE1 : Type A, AD only

*NOTE2 : Type D, AD only

*NOTE3 : FREQUENCY 50 / 60Hz

