


5-6 WATT 2:1 INPUT RANGE DC-DC CONVERTERS



H/HM Versions Only

Features:

- 5-6W Isolated Output
- 24-Pin DIP Package
- Efficiency to 87%
- 2:1 Input Range
- Regulated Outputs
- Pi Input Filter
- Continuous Short Circuit Protection
- Meet EMI EN55022 class A ("-E" model)
- No Tantalum Capacitor inside ("-E" model)
- Wide Operating Temperature Range ("-E" model)

Electrical Characteristics:

MODEL Number(1)	INPUT VOLTAGE(2)	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT				%EFF.(3)		Cap. Load
					NO LOAD		FULL LOAD			"-E"	
				"-E"		"-E"		"-E"			
EC4A01	9-18 VDC	5 VDC	1000 mA	1000 mA	7.5 mA	7.5 mA	541 mA	514 mA	77	81	4700uF
EC4A02	9-18 VDC	12 VDC	470 mA	500 mA	7.5 mA	10 mA	573 mA	595 mA	82	84	4700uF
EC4A03	9-18 VDC	15 VDC	400 mA	400 mA	7.5 mA	15 mA	625 mA	588 mA	80	85	4700uF
EC4A04	9-18 VDC	±12 VDC	±230 mA	±250 mA	12 mA	12 mA	554 mA	588 mA	83	85	2200uF
EC4A05	9-18 VDC	±15 VDC	±190 mA	±200 mA	12 mA	18 mA	556 mA	588 mA	81	85	2200uF
EC4A06	9-18 VDC	±5 VDC	±500 mA	±500 mA	12 mA	12 mA	541 mA	514 mA	77	81	2200uF
EC4A07	9-18 VDC	3.3 VDC	1000 mA	1200 mA	7.5 mA	7.5 mA	382 mA	429 mA	72	77	4700uF
EC4A11	18-36 VDC	5 VDC	1000 mA	1000 mA	5 mA	5 mA	260 mA	251 mA	80	83	4700uF
EC4A12	18-36 VDC	12 VDC	470 mA	500 mA	5 mA	8 mA	280 mA	291 mA	84	86	4700uF
EC4A13	18-36 VDC	15 VDC	400 mA	400 mA	5 mA	8 mA	298 mA	287 mA	84	87	4700uF
EC4A14	18-36 VDC	±12 VDC	±230 mA	±250 mA	7.5 mA	8 mA	280 mA	291 mA	82	86	2200uF
EC4A15	18-36 VDC	±15 VDC	±190 mA	±200 mA	7.5 mA	10 mA	293 mA	287 mA	81	87	2200uF
EC4A16	18-36 VDC	±5 VDC	±500 mA	±500 mA	7.5 mA	8 mA	260 mA	254 mA	80	82	2200uF
EC4A17	18-36 VDC	3.3 VDC	1000 mA	1200 mA	5 mA	5 mA	186 mA	209 mA	74	79	4700uF
EC4A21	36-72 VDC	5 VDC	1000 mA	1000 mA	2 mA	3 mA	132 mA	126 mA	79	83	4700uF
EC4A22	36-72 VDC	12 VDC	470 mA	500 mA	2 mA	6 mA	142 mA	144 mA	83	87	4700uF
EC4A23	36-72 VDC	15 VDC	400 mA	400 mA	2 mA	6 mA	154 mA	144 mA	81	87	4700uF
EC4A24	36-72 VDC	±12 VDC	±230 mA	±250 mA	3 mA	6 mA	142 mA	144 mA	81	87	2200uF
EC4A25	36-72 VDC	±15 VDC	±190 mA	±200 mA	3 mA	6 mA	147 mA	144 mA	81	87	2200uF
EC4A26	36-72 VDC	±5 VDC	±500 mA	±500 mA	3 mA	5 mA	130 mA	126 mA	80	83	2200uF
EC4A27	36-72 VDC	3.3 VDC	1000 mA	1200 mA	2 mA	2 mA	93 mA	104 mA	74	79	4700uF

NOTE: 1. Suffix "-E" of the models are high efficiency and wide operating temperature version.

2. Nominal Input Voltage is 12, 24 or 48 VDC.

3. Typical value at nominal input voltage and full load.

Specification

INPUT SPECIFICATIONS:

Input Voltage Range	12V	9-18V
	24V	18-36V
	48V	36-72V
Input Surge Voltage (100ms max.)	12V	25Vdc max
	24V	50Vdc max
	48V	100Vdc max
Input Filter		Pi Type


OUTPUT SPECIFICATIONS:

Voltage Accuracy		±2.0% max.
Voltage Balance(Dual)		±2.0% max
Temperature Coefficient		±0.05%/°C
Ripple & Noise, 20MHz BW (Note 5)	3.3V/5V	100mV p-p, max
	12V/15V	1% p-p max
Short Circuit Protection		Continuous
Line Regulation	Single/Dual (Note 1)	±0.5% max
Load Regulation	Single (Note 2)	±0.5% max
	Dual (Note 3)	±1.0% max
Start up time		5 ms max

GENERAL SPECIFICATIONS:

Efficiency		See Table
Isolation Voltage:		
500 VDC min.		Standard Models
3K VDC min. ... (Non-Conductive Black Plastic Only)		Suffix "H" Models
1.5K VDC min.		Suffix "HM" Models
Isolation Resistance		10 ⁹ ohm min
Isolation Capacitance		250pF Typ
Switching Frequency		1000KHz, min
Operating Ambient Temperature Range		-25°C to +71°C
		"-E" models: -40°C to +85°C with Derating
Power de-rating Curve		see Figure 1
Case Temperature (Note 4)	Plastic/Copper case	95°C/100°C max
Cooling		Natural Convection
Storage Temperature Range		-40°C to +100°C
Humidity		95% RH max. Non condensing
MTBF	MIL-STD-217F	T.B.D. hrs
Dimensions	DIP	1.25×0.80×0.40 inches(31.8×20.3×10.2mm)
	SMD	1.25×0.80×0.45 inches(31.8×20.3×11.4mm)
Case Material:		
Standard Models		Non-Conductive Black Plastic
Suffix "M" Models		Black Coated Copper with Non-conductive Base
Suffix "S" Models		SMD package
Weight		12.5g

EC4A Derating curve




NOTE:

1. Measured From High Line to Low Line
2. Measured From Full Load to 10% Load
3. Measured From Full Load to 1/4 Load
4. Maximum case temperature under any operating condition should not exceed 95°C(Plastic Case),100°C(Copper Case)
5. The output noise is measured with 0.1uF MLCC across for SMD package

All Specifications Typical At Nominal Line, Full Load, and 25°C Unless Otherwise Noted

Case A Dimensions

NOTE: Pin Size is 0.02 ±0.002Inch (0.5±0.05mm)DIA
All Dimensions In Inches (mm)
Tolerances Inches: X.XX= ±0.02 , X.XXX= ±0.010
Millimeters: X.X= ±0.5 , X.XX=±0.25



Data sheets are subject to change without notice

PIN CONNECTION									
Pin	500 VDC				1.5K & 3K VDC				
	Single Output		Dual Output		Single Output		Dual Output		
	DIP	SMD	DIP	SMD	DIP	SMD	DIP	SMD	
1,24	+V Input	+V Input	1,24	NP	NC	NP	NC	NP	NC
2,23	NC	-V Output	2,3	-V Input	-V Input				
3,22	NC	Common	4,5	NP	NC	NP	NC		
4	NP	NC	NP	NC	9	NC	Common		
5	NP	NC	NP	NC	10,15	NC	NC		
9	NP	NC	NP	NC	11	NC	-V Output		
10,15	-V Output	Common	12,13	NP	NC	NP	NC	NP	NC
11,14	+V Output	+V Output	14	+V Output	+V Output				
12,13	-V Input	-V Input	16	-V Output	Common				
16	NP	NC	NP	NC	20,21	NP	NC	NP	NC
20,21	NP	NC	NP	NC	22,23	+V Input	+V Input		

* NP-NO PIN
* NC-NO CONNECTION WITH PIN