

0600 Toggle Switches 1A 250Vac



C0600HD ---



C0600CC ---

- Toggle switch
- Brass and nylon actuators
- Single pole
- Latching and momentary action
- Choice of actuator profiles



C0602SC ---

Approvals and specifications

In house test: **1A 250Vac** — Indicative rating only
3A 12/24Vdc — Indicative rating only


3mm contact gap.
 Technical data on pages 4 & 5.

C 0600 H D ---
 TERMINAL FUNCTION ACTUATOR BODY OPTIONS

► TERMINAL	► FUNCTION	► ACTUATOR	► BODY	► OPTIONS
C 6.3 x 0.8	0600 ON - OFF 0602 ON - OFF (momentary ON)	C Chromed brass (0600) U Nylon (0600) G Nylon (0600) H Nylon (0600) S Chromed brass stem/nylon paddle (0602 only) 	D Nylon neck and top plate (Used with actuator codes U, G and H) C Metal neck and top plate (Used with actuator codes C and S) Panel thickness - 3.5mm Back nut must be fitted Fixing nuts (Standard is M506 & T92) T5 Hex brass M506 Hex nylon T92 Knurled brass - slotted M279 Knurled nylon 	Cover A0331M0AAA (C Actuator only) Neck Seal A0539M0AAA (C, H & U Actuators) Actuator visible Cover A1080M0AAA (C Actuator only) Covers have internal nylon nuts.

Dimensions (mm)

0600 (U actuator shown)



0602

