

Safety Cut-out Switches 16A 250Vac



- ▶ Safety cut-out switches
- ▶ Ratings up to 16A, 250V ac
- ▶ Snap action switches
- ▶ NC contacts
- ▶ Pendulum or lever tilt operation

Approvals and specifications



C0320AA
15A 125/250Vac 1E4

15A 125/250Vac UL file no. E91274
15A 1/2HP, 125/250Vac CSA file no. LR85259-2









16(4)A 250Vac 5E4 T85

16A 125/250Vac 3/4hp T85 50E3 UL file no. E45221
125V 1/2 HP, 250V 3/4 HP, 0.4A 125Vdc, 0.2A 250Vdc

μ contact gap.


C0320AA - - -

TERMINAL FUNCTION ACTUATOR MOUNTING

▶ ORDER CODE	▶ TERMINAL	▶ FUNCTION	▶ ACTUATOR	▶ MOUNTING
C0320AA		 ON - OFF (momentary OFF)		 2 off 3.4mm mounting holes or M3 screw holes
C0320BB		 ON - OFF (momentary OFF)		 3 holes Ø3.0


Dimensions (mm)

C0320AA



* Switching point
at dimension indicated

C0320BB



Switch actuating
point 40° in any
direction off vertical