

2000 Slide Switches - up to 5 position 10A 250Vac



- ▶ Slide switches
- ▶ Ratings up to 16A, 250V ac
- ▶ PCB and solder terminals
- ▶ 2, 3, 4 and 5 position
- ▶ Choice of circuits
- ▶ Choice of actuators

Approvals and specifications



10A 250Vac T85
6(3)A 250Vac T85



UL CSA 16A 250Vac Non Inductive
UL CSA 4A 300Vac
UL 65°C, file no. E45221, CSA file no. LR10990

μ contact gap

Please specify: Standard action (SP116) or Light action (SP118).
2000 series lubrication is inorganic and does not degrade plastics.


Technical data on pages 4 & 5.

T 2 2 20 5 C ---

TERMINAL SERIES POSITIONS CIRCUIT SLIDER BODY PRINT, COLOUR, ETC

slide switches


TERMINAL	SERIES	POS'N	CIRCUIT Viewed from back	SLIDER			
K 2.8 x 0.8	2	2 Switching positions	10 	0 	6 	D 	L
R 2.8 x 0.8			20 	1 	7 	E 	N
T Solder			30 	2 	9 	G 	P
X PCB 0.8 Sq.			40 	3 	A 	H 	R
Y PCB 0.8 Sq. For mounting stability switches have extra "support" terminals * Nominal - Dimension varies with body type. For exact figure call sales		3 Switching positions	10 	4 	B 	J 	S
			20 	5 	C 	K 	T
			30 				
			40 				
		4 Switching positions	10 				
			20 				
			30 				
			40 				
		5 Switching positions	10 				
			20 				
			30 				
			40 				



X22205C ---



T2220EC ---



T23206A ---



T24306A ---




T25302A ---




T25100A ---

BODY


C 2 positions




H 2 positions




A 3 positions




H 3 positions




A 4 positions



H 4 positions



A 5 positions




OPTIONS

Colour


For custom slider colours call sales. A full range is available for large orders

DIMENSIONS (mm)


2 Position C body




2 Position H body





Cut-out/PCB Matrix




3 Position A body





3 Position H body



4 Position A body



4 Position H body



5 Position A body

