

Coaxial Amplifier

50Ω Low Power 0.2 to 750 MHz

ZFL-750+



CASE STYLE: Y460

Features

- wideband, 0.2 to 750 MHz
- rugged shielded case
- low noise figure, 6 dB typ.
- protected by US Patent, 6,943,629

Applications

- VHF/UHF
- lab use
- instrumentation

Connectors	Model	Price	Qty.
SMA	ZFL-750+	\$74.95 ea.	(1-9)
BRACKET (OPTION "B")		\$5.00	(1+)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Amplifier Electrical Specifications

MODEL NO.	FREQUENCY (MHz)		GAIN (dB)		MAXIMUM POWER (dBm)		DYNAMIC RANGE		VSWR (:1) Typ.		DC POWER	
	f_L	f_U	Min.	Flatness Max.	Output (1 dB Compr.)	Input (no damage)	NF (dB) Typ.	IP3 (dBm) Typ.	In	Out	Volt (V) Nom.	Current (mA) Max.
ZFL-750+	0.2	750	18	±0.55	+9*	+5	6.0	+18	1.5	2.0	15	90

* +7dBm from 500 to 750 MHz

Open load is not recommended, potentially can cause damage.
With no load derate max input power by 20 dB

Maximum Ratings

Operating Temperature -20°C to 71°C


Storage Temperature -55°C to 100°C

DC Voltage +17V Max.


Permanent damage may occur if any of these limits are exceeded.

Outline Drawing

STANDARD



OPTION "B"



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
1.25	1.25	.75	.63	.36	1.000	1.000	.125	.125	.46	2.18	1.688	.06	.750	.50	.80	.45	.29	grams
31.75	31.75	19.05	16.00	9.14	25.40	25.40	3.18	3.18	11.68	55.37	42.88	1.52	19.05	12.70	20.32	11.43	7.37	38

Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp








www.minicircuits.com P.O. Box 35166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. B
M131858
ZFL-750+
131015
Page 1 of 2

Typical Performance Data/Curves

ZFL-750+

FREQUENCY (MHz)	GAIN (dB)			DIRECTIVITY (dB)			VSWR (:1)		NOISE FIGURE (dB)	POUT at 1 dB COMPR. (dBm)
	12V	15V	16V	12V	15V	16V	IN	OUT		
0.20	18.30	19.78	20.01	22.90	22.20	22.00	1.14	1.10	—	10.39
1.00	18.36	19.85	20.08	23.90	22.90	22.60	1.10	1.08	—	10.50
9.30	18.38	19.86	20.10	23.70	22.60	22.50	1.11	1.09	—	10.61
83.50	18.38	19.84	20.07	23.10	22.10	21.90	1.11	1.09	6.17	10.55
288.60	18.57	19.79	20.00	22.70	22.30	20.70	1.10	1.19	6.22	10.14
365.50	18.55	19.74	19.97	22.40	22.10	20.40	1.11	1.23	6.25	10.07
461.60	18.44	19.64	19.87	22.60	20.60	20.80	1.12	1.32	6.25	9.94
557.70	18.66	19.88	20.07	21.80	20.40	19.70	1.14	1.40	6.20	9.87
653.90	18.87	20.06	20.29	22.10	19.80	20.30	1.17	1.54	6.13	9.54
750.00	18.98	20.20	20.39	19.40	19.30	19.50	1.18	1.69	6.09	9.26



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

