

SMA/BNC

Adaptenuator

50Ω 0.5W 6dB DC to 2000 MHz
SM-BM-6


Maximum Ratings

Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 150°C

Permanent damage may occur if any of these limits are exceeded.

Features

- improved interface matching
- wideband, DC to 2000 MHz, useable to 4000 MHz
- excellent VSWR, 1.1:1 typ.
- excellent flatness, ± 0.1 dB typ.
- rugged unibody construction


CASE STYLE: DJ869

Connectors	Model	Price	Qty.
Conn1 SMA-Male	Conn2 BNC-Male	SM-BM-6	\$19.95 ea. (1-24)

Applications

- instrumentation
- provides attenuation and connector type change
- minimizes hardware

Outline Drawing



Electrical Specifications

FREQ. (MHz)	ATTENUATION (dB)							VSWR (:1)						MAX. INPUT POWER (W)
	Flatness*													
	f _L -f _U	DC-500 MHz		DC-1000 MHz		DC-2000 MHz		DC-500 MHz		DC-1000 MHz		DC-2000 MHz		
	Nom.	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	
DC-2000	6±0.3	0.05	0.15	0.10	0.20	0.15	0.25	1.1	1.2	1.1	1.2	1.2	1.25	0.5

*Flatness defined as peak to peak attenuation over band divided by 2.




Typical Performance Data

FREQUENCY (MHz)	ATTENUATION (dB)	VSWR (:1)	
		BNC-Male	SMA-Male
1.00	6.00	1.00	1.00
5.00	5.98	1.00	1.00
10.00	6.00	1.00	1.00
50.00	6.00	1.00	1.00
100.00	6.00	1.01	1.01
500.00	6.05	1.03	1.02
1000.00	6.11	1.06	1.03
1500.00	6.15	1.07	1.03
1700.00	6.17	1.08	1.02
2000.00	6.19	1.08	1.03

Outline Dimensions (inch/mm)

A	B	D	wt
.312	.61	1.89	grams
7.92	15.49	48.01	25.8

Electrical Schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp


www.minicircuits.com P.O. Box 35166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

 REV. B
 M96826
 EE-9890
 SM-BM-6
 URJ/TD/CP/AM
 130912