

Plug-In

Directional Coupler

50Ω

860 to 970 MHz

PDC20-970HP



Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C

Pin Connections

INPUT	1
OUTPUT	4
COUPLED	3
GROUND	2,5,7,8
CASE GROUND	2,5,7,8
NOT USED	6

Features

- high power, up to 5W power input
- low mainline loss, 0.25 dB typ.
- excellent directivity, 24 dB typ.
- rugged welded construction, hermetically sealed


Applications

- cellular
- power levelling & monitoring
- VSWR measurement

CASE STYLE: A01

PRICE: \$42.20 ea. QTY. (1-9)

Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	H	J	K		wt
.200	.20	.14	.031		grams
5.08	5.08	3.56	0.79		5.2




Directional Coupler Electrical Specifications

FREQ. (MHz)	COUPLING (dB)		MAINLINE LOSS ¹ (dB)		DIRECTIVITY (dB)		VSWR (:1)	POWER INPUT, W
	Nom.	Flatness	Typ.	Max.	Typ.	Min.		
860-970	20.2±0.6	±0.5	0.25	0.5	24	20	1.1	5.0


1. Mainline loss includes theoretical power loss at coupled port.
External heat sinking is recommended to reduce case temperature.

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
				In	Out	Cpl
849.75	0.29	19.95	57.27	23.08	25.72	18.88
860.25	0.28	19.95	48.96	22.83	25.40	18.79
870.75	0.27	19.95	38.63	22.61	25.07	18.71
879.50	0.28	19.96	36.22	22.24	24.82	18.65
890.00	0.28	19.94	33.98	22.23	24.54	18.58
895.25	0.29	19.97	32.11	22.15	24.42	18.54
900.50	0.27	19.94	31.38	22.05	24.26	18.51
925.00	0.30	19.97	27.48	21.62	23.64	18.36
949.50	0.32	19.98	25.33	21.25	23.12	18.23
970.50	0.30	19.99	23.29	20.95	22.65	18.12

PDC20-970HP
MAINLINE LOSSPDC20-970HP
COUPLING & DIRECTIVITYPDC20-970HP
RETURN LOSS

Electrical Schematic



* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMER(S) THAT ROUTES DC FROM RF PORTS TO GROUND.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 35166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. A
M119986
PDC20-970HP
WZ/TD/CP/AM
120914