

Coaxial

Low Pass Filter

NLP-2950+

50Ω DC to 2700 MHz

Maximum Ratings

Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 100°C

RF Power Input 0.5W max.

Permanent damage may occur if any of these limits are exceeded.

Features

- rugged shielded case
- other NLP models available with wide selection of cut-off frequencies

Applications

- lab use
- test equipment
- video equipment



CASE STYLE: FF57

Connectors	Model	Price	Qty.
N-Type	NLP-2950+	\$37.95 ea.	(1-9)


+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Low Pass Filter Electrical Specifications

PASSBAND (MHz)	fco (MHz) Nom.	STOPBAND (MHz)	VSWR (:1)
(loss < 1 dB)	(loss 3 dB)	(loss > 20 dB) (loss > 40 dB)	Passband Typ. Stopband Typ.
DC-2700	2950	3700-4500 4500-6000	1.3 18


Outline Drawing




Outline Dimensions (inch/mm)

B	D	E	wt
.67	2.90	.82	grams
17.02	73.66	20.83	90.0

typical frequency response





electrical schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
	$\bar{x}$ σ			
10.00	0.01 0.00	52.68	10.00	0.49
151.57	0.04 0.00	32.88	151.57	0.47
293.15	0.07 0.00	28.39	293.15	0.47
434.73	0.09 0.01	26.51	434.73	0.47
576.31	0.10 0.01	25.60	576.31	0.47
859.47	0.12 0.01	27.73	859.47	0.48
1142.63	0.14 0.01	36.13	1142.63	0.49
1425.78	0.19 0.02	26.10	1425.78	0.51
1708.94	0.21 0.02	23.87	1708.94	0.52
1992.10	0.23 0.01	30.78	1992.10	0.56
2275.26	0.30 0.02	22.41	2275.26	0.61
2558.42	0.41 0.04	19.38	2558.42	0.71
2700.00	0.58 0.12	16.56	2700.00	0.78
2950.00	3.40 0.95	3.51	2950.00	0.97
3325.00	15.26 1.29	0.29	3325.00	0.53
3700.00	26.05 1.34	0.14	3700.00	0.38
4100.00	35.49 1.43	0.03	4100.00	0.36
4500.00	43.92 1.60	0.07	4500.00	0.25
5250.00	56.88 1.91	0.10	5250.00	0.23
6000.00	65.29 2.87	0.03	6000.00	0.25



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

RF/MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs & shopping online see web site

REV. B
M120055
NLP-2950+
090820