


Coaxial Low Pass Filter

50Ω DC to 650 MHz (40 dB Isolation up to 20 GHz)

VLFX-650+ VLFX-650



CASE STYLE: FF1118

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	10W max. at 25°C

*Passband rating, derate linearly to 3.5W at 100°C ambient. Permanent damage may occur if any of these limits are exceeded.

Features

- very good isolation, 40 dB up to 20 GHz
- 21 sections
- excellent power handling, 10W
- temperature stable LTCC internal structure
- re-entry frequency > 20 GHz
- rugged unibody construction
- protected by US patent 6,943,646

Applications


- harmonic rejection
- transmitters/receivers
- lab use
- test instrumentation

Connectors	Model	Price	Qty.
SMA	VLFX-650+	\$39.95 ea.	(1-9)
SMA	VLFX-650	\$39.95 ea.	(1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing




Outline Dimensions (inch mm)

B	D	E	wt.
.410	2.67	.312	grams
10.41	67.82	7.92	17.0


Low Pass Filter Electrical Specifications @ 25°C

MODEL NO.	PASSBAND (MHz) (Loss < 1.2dB) Max.	Fco, MHz Nom (Loss 3 dB) Typ	STOPBAND (MHz) (Loss, dB)		VSWR (:1)		NO. OF SECTIONS
			F20 Min.	F40 Typ.	Stopband Typ.	Passband Typ.	
VLFX-650 (+)	DC-650	1025	1275	1450-20000	10	1.2	21

Typical Frequency Response





Functional Schematic



Typical Performance Data @ 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
50	0.29	1.08
200	0.39	1.13
400	0.54	1.11
650	0.89	1.20
800	1.22	1.27
900	1.57	1.20
1025	2.92	1.32
1125	9.11	2.42
1275	31.28	6.45
1450	41.47	16.47
1575	53.44	24.07
2000	51.81	41.80
3000	82.03	89.22
5000	82.92	52.93
7500	75.09	48.67
10000	99.20	7.09
12500	60.25	14.19
15000	69.31	6.64
17500	61.54	19.28
20000	60.47	11.14



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. D
M131810
VLFX-650
EDU-0399
ED-11930A/11
URJ/AD/CP
130319
Page 1 of 1