

Coaxial

50Ω

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W max.

Permanent damage may occur if any of these limits are exceeded.

Features

- rugged shielded case
- other standard and custom BHP models available with wide selection of fco


Applications

- lab use
- transmitters/receivers
- radio communications

High Pass Filter Electrical Specifications

STOPBAND (MHz)		fco (MHz) Nom.	PASSBAND (MHz)	VSWR (:1)	
(loss > 40 dB)	(loss > 20 dB)	(loss 3 dB)	(loss <1 dB)	Stopband Typ.	Passband Typ.
DC-90	90-116	164	185-3000	17	1.6


Outline Drawing




Outline Dimensions (inch/mm)

B	D	wt
.54	2.59	grams
13.72	65.79	40.0

typical frequency response






electrical schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)		Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
	$\bar{x}$	σ			
10.00	71.62	2.72	0.06	75.00	2.93
50.00	87.09	4.73	0.13	90.00	2.71
70.00	73.00	0.87	0.10	95.00	2.71
75.00	68.35	1.20	0.09	100.00	3.03
90.00	55.00	0.48	0.11	104.00	3.20
95.00	50.91	0.53	0.13	108.00	3.21
100.00	47.05	0.54	0.14	112.00	3.36
108.00	41.12	0.52	0.19	116.00	3.60
116.00	35.41	0.54	0.25	120.00	3.87
120.00	32.62	0.56	0.28	140.00	6.03
140.00	18.90	0.65	0.52	150.00	8.41
160.00	5.88	0.58	2.57	160.00	11.87
170.00	1.99	0.26	7.68	170.00	12.82
180.00	0.82	0.06	18.19	180.00	10.02
185.00	0.68	0.03	22.90	185.00	8.64
200.00	0.55	0.03	21.35	200.00	6.12
300.00	0.28	0.02	30.67	300.00	2.20
400.00	0.31	0.01	17.13	400.00	1.28
500.00	0.35	0.01	14.65	500.00	0.90
600.00	0.34	0.01	14.54	600.00	0.70
700.00	0.32	0.01	15.30	700.00	0.59
800.00	0.29	0.01	16.38	800.00	0.52
900.00	0.27	0.01	17.76	900.00	0.47
1000.00	0.25	0.01	19.27	1000.00	0.44
1100.00	0.25	0.01	20.89	1100.00	0.41
1200.00	0.25	0.01	22.44	1200.00	0.39
1300.00	0.26	0.01	24.09	1300.00	0.38
1400.00	0.25	0.01	25.43	1400.00	0.36
2000.00	0.31	0.01	27.03	2000.00	0.33
3000.00	0.51	0.02	17.33	3000.00	0.32



For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. C
M108294
BHP-200+
090818

