

Coaxial High Pass Filter

50Ω 780 to 3000 MHz

Maximum Ratings

Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 100°C

RF Power Input 0.5W max.

Permanent damage may occur if any of these limits are exceeded.

Features

- rugged shielded case
- other standard and custom NHP models available with wide selection of fco

Applications

- lab use
- transmitters/receivers
- radio communications

NHP-800+



CASE STYLE: FF57

Connectors	Model	Price	Qty.
N-Type	NHP-800+	\$39.95 ea.	(1-9)


+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

High Pass Filter Electrical Specifications

STOPBAND (MHz)	fco (MHz) Nom.	PASSBAND (MHz)	VSWR (:1)
(loss > 40 dB)	(loss > 20 dB)	(loss < 3 dB)	(loss < 1 dB)
DC-445	445-570	710	780-3000
			Stopband Typ. Passband Typ.
			17 2.1


Outline Drawing




Outline Dimensions (inch mm)

B	D	E	wt
.67	2.90	.82	grams
17.02	73.66	20.83	90.0

typical frequency response





electrical schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
$\bar{x}$	σ			
10.00	74.59	6.84	200.00	0.49
100.00	94.26	7.80	300.00	0.44
200.00	80.68	1.20	400.00	0.81
300.00	68.07	0.23	485.00	0.90
400.00	54.92	0.50	490.00	0.92
485.00	41.80	0.71	495.00	0.95
490.00	41.00	0.71	500.00	0.95
495.00	40.19	0.72	550.00	1.10
500.00	39.38	0.73	600.00	1.42
550.00	31.17	0.81	610.00	1.50
600.00	22.58	0.88	620.00	1.59
620.00	19.06	0.91	625.00	1.64
650.00	13.62	0.95	650.00	2.05
660.00	11.79	0.95	660.00	2.29
670.00	9.98	0.94	670.00	2.55
700.00	5.03	0.77	700.00	3.46
710.00	3.71	0.66	710.00	3.77
750.00	1.03	0.15	750.00	3.59
800.00	0.67	0.03	800.00	2.37
965.00	0.44	0.01	965.00	1.30
1070.00	0.41	0.00	1070.00	1.04
1180.00	0.40	0.00	1180.00	0.87
1290.00	0.40	0.01	1290.00	0.75
1400.00	0.42	0.02	1400.00	0.67
1460.00	0.43	0.02	1460.00	0.63
1570.00	0.46	0.03	1570.00	0.58
1680.00	0.48	0.03	1680.00	0.54
1790.00	0.48	0.04	1790.00	0.50
2000.00	0.49	0.04	2000.00	0.46
3000.00	0.57	0.03	3000.00	0.37



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at [minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs & shopping online see web site

REV. C
M108294
NHP-800+
090820