

High IP3

Frequency Mixer

Level 17 (LO Power +17 dBm) 220 to 710 MHz

LAVI-711H+



Maximum Ratings

Operating Temperature	-45°C to 85°C
Storage Temperature	-55°C to 100°C
LO Power	+23 dBm
RF Power	+21 dBm

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

LO	10
RF	2
IF	14
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16

Features

- very high IP3, 30 dBm typ.
- low conversion loss, 7.3 dB typ.
- excellent L-R isolation, 50 dB typ. and L-I isolation, 40 dB typ.
- high 1 dB compression, 20 dBm typ.
- shielded metal cover
- aqueous washable
- protected by US Patent 6,807,407

Applications

- cellular/PCS base stations
- ISM applications
- defense communications

CASE STYLE: CK605

PRICE: \$22.95 ea. QTY. (1-9)
\$15.95 ea. QTY. (100)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)


The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications (T_{AMB} = 25°C)

FREQUENCY (MHz)			CONVERSION LOSS (dB)			RF in at 1dB Compr (dBm)	IP3 (dBm)	LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)	
RF	LO	IF	Typ.	σ	Max.	Typ.	Typ.	Typ.	Min.	Typ.	Min.
220-710	250-740	10-500	7.3	0.25	9.0	+20	30	50	40	40	29

Outline Drawing

PCB Land Pattern




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K
.500	.500	.180	.100	.080	.115	.060	.040	.540	.060
12.7	12.7	4.572	2.54	2.032	2.921	1.524	1.016	13.72	1.524

L	M	N	P	Q	R	S	T	wt.
.100	.135	.135	.115	.140	.070	.150	.070	grams
2.54	3.429	3.429	2.921	3.556	1.778	3.81	1.778	1.0


Demo Board MCL P/N: TB-433+ Suggested PCB Layout (PL-012)



Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)	IP3 (dBm)	IF Freq. (MHz)	VSWR IF (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm		LO +17dBm
220.10	250.10	7.37	58.20	42.61	1.24	3.44	27.05	10.10	1.07
245.10	275.10	7.33	58.37	41.84	1.27	3.44	27.24	50.10	1.10
270.10	300.10	7.38	58.15	41.44	1.27	3.40	27.47	100.10	1.18
295.10	325.10	7.39	59.45	40.60	1.28	3.35	27.83	150.10	1.30
320.10	350.10	7.29	57.31	40.07	1.30	3.31	28.59	200.10	1.37
345.10	375.10	7.31	56.89	39.15	1.30	3.22	28.92	250.10	1.49
370.10	400.10	7.33	56.33	38.49	1.31	3.12	28.72	300.10	1.55
395.10	425.10	7.26	55.25	37.32	1.33	2.96	29.29	350.10	1.68
420.10	450.10	7.27	54.20	36.46	1.35	2.78	30.08	360.10	1.66
445.10	475.10	7.28	54.23	35.93	1.34	2.57	30.08	370.10	1.71
470.10	500.10	7.31	53.26	35.82	1.34	2.34	30.88	380.10	1.72
495.10	525.10	7.34	50.69	34.89	1.36	2.11	31.80	390.10	1.69
520.10	550.10	7.57	48.58	32.99	1.35	1.92	32.30	400.10	1.74
545.10	575.10	7.78	48.42	31.25	1.32	1.78	30.64	410.10	1.81
570.10	600.10	7.55	47.58	31.44	1.30	1.75	30.23	420.10	1.79
595.10	625.10	7.40	45.58	32.28	1.31	1.81	30.72	430.10	1.81
620.10	650.10	7.43	43.91	33.02	1.32	1.92	30.51	440.10	1.86
645.10	675.10	7.47	42.94	33.63	1.33	2.06	30.05	450.10	1.86
670.10	700.10	7.49	42.71	34.42	1.34	2.24	29.07	460.10	1.83
710.10	740.10	7.55	43.16	35.55	1.37	2.52	27.02	500.10	1.94

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. OR
M112970
LAVI-711H+
ED-12982/2
DJ/CP/AM
071207
Page 1 of 2

